

# Package ‘iotools’

January 25, 2018

**Version** 0.2-5

**Title** I/O Tools for Streaming

**Author**

Simon Urbanek <Simon.Urbanek@r-project.org>, Taylor Arnold <taylor.arnold@acm.org>

**Maintainer** Simon Urbanek <Simon.Urbanek@r-project.org>

**Depends** R (>= 2.9.0)

**Imports** methods, parallel, utils

**Suggests** testthat

**Description** Basic I/O tools for streaming and data parsing.

**License** GPL-2 | GPL-3

**URL** <http://www.rforge.net/iotools>

**NeedsCompilation** yes

**Repository** CRAN

**Date/Publication** 2018-01-25 15:09:59 UTC

## R topics documented:

.default.formatter . . . . .	2
as.output . . . . .	3
chunk . . . . .	4
chunk.apply . . . . .	5
chunk.map . . . . .	6
ctapply . . . . .	7
dstrfw . . . . .	8
dstrsplit . . . . .	10
fdrbind . . . . .	12
idstrsplit . . . . .	13
imstrsplit . . . . .	14
input.file . . . . .	16
line.merge . . . . .	17
mstrsplit . . . . .	17

output.file . . . . .	19
read.csv.raw . . . . .	20
readAsRaw . . . . .	21
which.min.key . . . . .	22
write.csv.raw . . . . .	23

<b>Index</b>	<b>24</b>
--------------	-----------

---

<code>.default.formatter</code>	<i>Default formatter, corresponding to the <code>as.output</code> functions</i>
---------------------------------	---

---

## Description

This function provides the default formatter for the `iotools` package; it assumes that the key is separated from the rest of the row by a tab character, and the elements of the row are separated by the pipe ("`|`") character. Vector and matrix objects returned from the output via `as.output`.

## Usage

```
.default.formatter(x)
```

## Arguments

`x` character vector (each element is treated as a row) or a raw vector (LF characters '`\n`' separate rows) to split

## Value

Either a character matrix with a row for each element in the input, or a character vector with an element for each element in the input. The latter occurs when only one column (not counting the key) is detected in the input. The keys are stored as `rownames` or `names`, respectively.

## Author(s)

Simon Urbanek

## See Also

[mstrsplit](#)

## Examples

```
c <- c("A\tB|C|D", "A\tB|B|B", "B\tA|C|E")
.default.formatter(c)

c <- c("A\tD", "A\tB", "B\tA")
.default.formatter(c)
```

---

`as.output`*Character Output*

---

**Description**

Create objects of class `output`.

**Usage**

```
as.output(x, ...)
```

**Arguments**

`x` object to be converted to an instance of `output`.

`...` optional arguments to be passed to implementing methods of `as.output`. For `matrix`, and `data.frame` types this includes a `sep` argument indicating a field separator.

**Details**

`as.output` is generic, and methods can be written to support new classes. The output is meant to be a character vector suitable for writing to the disk or sending over a connection.

**Value**

`as.output.default` outputs a character vector by default, though other formats (such as a raw vector) may be returned by other methods.

**Author(s)**

Simon Urbanek

**Examples**

```
m = matrix(sample(letters), ncol=2)
as.output(m)
```

```
df = data.frame(a = sample(letters), b = runif(26), c = sample(state.abb,26))
as.output(df)
```

---

chunk

*Functions for very fast chunk-wise processing*

---

## Description

`chunk.reader` creates a reader that will read from a binary connection in chunks while preserving integrity of lines.

`read.chunk` reads the next chunk using the specified reader.

## Usage

```
chunk.reader(source, max.line = 65536L, sep = NULL)
read.chunk(reader, max.size = 33554432L, timeout = Inf)
```

## Arguments

<code>source</code>	binary connection or character (which is interpreted as file name) specifying the source
<code>max.line</code>	maximum length of one line (in bytes) - determines the size of the read buffer, default is 64kb
<code>sep</code>	optional string: key separator if key-aware chunking is to be used character is considered a key and subsequent records holding the same key are guaranteed to be
<code>reader</code>	reader object as returned by <code>chunk.reader</code>
<code>max.size</code>	maximum size of the chunk (in bytes), default is 32Mb
<code>timeout</code>	numeric, timeout (in seconds) for reads if source is a raw file descriptor.

## Details

`chunk.reader` is essentially a filter that converts binary connection into chunks that can be subsequently parsed into data while preserving the integrity of input lines. `read.chunk` is used to read the actual chunks. The implementation is very thin to prevent copying of large vectors for best efficiency.

If `sep` is set to a string, it is treated as a single-character separator character. If specified, prefix in the input up to the specified character is treated as a key and subsequent lines with the same key are guaranteed to be processed in the same chunk. Note that this implies that the chunk size is practically unlimited, since this may force accumulation of multiple chunks to satisfy this condition. Obviously, this increases the processing and memory overhead.

In addition to connections `chunk.reader` supports raw file descriptors (integers of the class "fileDescriptor"). In that case the reads are performed directly by `chunk.reader` and `timeout` can be used to perform non-blocking or timed reads (unix only, not supported on Windows).

**Value**

chunk.reader returns an object that can be used by read.chunk. If source is a string, it is equivalent to calling chunk.reader(file(source, "rb"), ...).

read.chunk returns a raw vector holding the next chunk or NULL if timeout was reached. It is deliberate that read.chunk does NOT return a character vector since that would result in a high performance penalty. Please use the appropriate parser to convert the chunk into data, see [mstrsplit](#).

**Author(s)**

Simon Urbanek

---

chunk.apply

*Process input by applying a function to each chunk*

---

**Description**

chunk.apply processes input in chunks and applies FUN to each chunk, collecting the results.

**Usage**

```
chunk.apply(input, FUN, ..., CH.MERGE = rbind, CH.MAX.SIZE = 33554432, parallel=1)
```

```
chunk.tapply(input, FUN, ..., sep = "\t", CH.MERGE = rbind, CH.MAX.SIZE = 33554432)
```

**Arguments**

input	Either a chunk reader or a file name or connection that will be used to create a chunk reader
FUN	Function to apply to each chunk
...	Additional parameters passed to FUN
sep	for tapply, gives separator for the key over which to apply. Each line is split at the first separator, and the value is treated as the key over which to apply the function over.
CH.MERGE	Function to call to merge results from all chunks. Common values are list to get lapply-like behavior, rbind for table-like output or c for a long vector.
CH.MAX.SIZE	maximal size of each chunk in bytes
parallel	the number of parallel processes to use in the calculation (*nix only).

**Value**

The result of calling CH.MERGE on all chunk results.

**Note**

The input to FUN is the raw chunk, so typically it is advisable to use [mstrsplit](#) or similar function as the first step in FUN.

**Author(s)**

Simon Urbanek

**Examples**

```
## Not run:
## compute quantiles of the first variable for each chunk
## of at most 10kB size
chunk.apply("input.file.txt",
  function(o) {
    m = mstrsplit(o)
    quantile(as.numeric(m[,1]), c(0.25, 0.5, 0.75))
  }, CH.MAX.SIZE=1e5)

## End(Not run)
```

---

 chunk.map

---

*Map a function over a file by chunks*


---

**Description**

A wrapper around the core iotools functions to easily apply a function over chunks of a large file. Results can be either written to a file or returned as an internal list.

**Usage**

```
chunk.map(input, output = NULL, formatter = .default.formatter,
  FUN, key.sep = NULL, max.line = 65536L,
  max.size = 33554432L, output.sep = ",", output.nsep = "\t",
  output.keys = FALSE, skip = 0L, ...)
```

**Arguments**

input	an input connection or character vector describing a local file.
output	an optional output connection or character vector describing a local file. If NULL, the results are returned internally as a list.
formatter	a function that takes raw input and produces the input given to FUN
FUN	a user provided function to map over the chunks. The result of FUN is either wrapper in a list item, when output is NULL, or written to the output file using <a href="#">as.output</a>
key.sep	optional key separator given to <a href="#">chunk.reader</a>
max.line	maximum number of lines given to <a href="#">chunk.reader</a>
max.size	maximum size of a block as given to <a href="#">read.chunk</a>
output.sep	single character giving the field separator in the output.
output.nsep	single character giving the key separator in the output.

output.keys	logical. Whether as.output should interpret row names as keys.
skip	integer giving the number of lines to strip off the input before reading. Useful when the input contains a row a column headers
...	additional parameters to pass to FUN

**Value**

A list of results when output is NULL; otherwise no output is returned.

**Author(s)**

Taylor Arnold

---

 ctapply

*Fast tapply() replacement functions*


---

**Description**

ctapply is a fast replacement of tapply that assumes contiguous input, i.e. unique values in the index are never separated by any other values. This avoids an expensive split step since both value and the index chunks can be created on the fly. It also cuts a few corners to allow very efficient copying of values. This makes it many orders of magnitude faster than the classical lapply(split(), ...) implementation.

**Usage**

```
ctapply(X, INDEX, FUN, ..., MERGE=c)
```

**Arguments**

X	an atomic object, typically a vector
INDEX	numeric or character vector of the same length as X
FUN	the function to be applied
...	additional arguments to FUN. They are passed as-is, i.e., without replication or recycling
MERGE	function to merge the resulting vector or NULL if the arguments to such a function are to be returned instead

**Details**

Note that ctapply supports either integer, real or character vectors as indices (note that factors are integer vectors and thus supported, but you do not need to convert character vectors). Unlike tapply it does not take a list of factors - if you want to use a cross-product of factors, create the product first, e.g. using paste(i1, i2, i3, sep='\01') or multiplication - whatever method is convenient for the input types.

ctapply requires the INDEX to contiguous. One (slow) way to achieve that is to use [sort](#) or [order](#).

ctapply also supports X to be a matrix in which case it is split row-wise based on INDEX. The number of rows must match the length of INDEX. Note that the indexed matrices behave as if drop=FALSE was used and currently dimnames are only honored if rownames are present.

### Note

This function has been moved to the fastmatch package!

### Author(s)

Simon Urbanek

### See Also

[tapply](#)

### Examples

```
i = rnorm(4e6)
names(i) = as.integer(rnorm(1e6))
i = i[order(names(i))]
system.time(tapply(i, names(i), sum))
system.time(ctapply(i, names(i), sum))

## ctapply() also works on matrices (unlike tapply)
m=matrix(c("A","A","B","B","B","C","A","B","C","D","E","F","","X","X","Y","Y","Z"),,3)
ctapply(m, m[,1], identity, MERGE=list)
ctapply(m, m[,1], identity, MERGE=rbind)
m2=m[,-1]
rownames(m2)=m[,1]
colnames(m2) = c("V1","V2")
ctapply(m2, rownames(m2), identity, MERGE=list)
ctapply(m2, rownames(m2), identity, MERGE=rbind)
```

---

dstrfw

*Split fixed width input into a dataframe*

---

### Description

dstrfw takes raw or character vector and splits it into a dataframe according to a vector of fixed widths.

### Usage

```
dstrfw(x, col_types, widths, nsep = NA, strict=TRUE, skip=0L, nrows=-1L)
```



**Arguments**

<code>x</code>	character vector (each element is treated as a row) or a raw vector (newlines separate rows)
<code>col_types</code>	required character vector or a list. A vector of classes to be assumed for the output dataframe. If it is a list, <code>class(x)[1]</code> will be used to determine the class of the contained element. It will not be recycled, and must be at least as long as the longest row if <code>strict</code> is <code>TRUE</code> .  Possible values are "NULL" (when the column is skipped) one of the six atomic vector types ('character', 'numeric', 'logical', 'integer', 'complex', 'raw') or <code>POSIXct</code> . 'POSIXct' will parse date format in the form "YYYY-MM-DD hh:mm:ss.sss" assuming GMT time zone. The separators between digits can be any non-digit characters and only the date part is mandatory. See also <code>fasttime::asPOSIXct</code> for details.
<code>widths</code>	a vector of widths of the columns. Must be the same length as <code>col_types</code> .
<code>nsep</code>	index name separator (single character) or NA if no index names are included
<code>strict</code>	logical, if <code>FALSE</code> then <code>dstrsplit</code> will not fail on parsing errors, otherwise input not matching the format (e.g. more columns than expected) will cause an error.
<code>skip</code>	integer: the number of lines of the data file to skip before beginning to read data.
<code>nrows</code>	integer: the maximum number of rows to read in. Negative and other invalid values are ignored.

**Details**

If `nsep` is specified, the output of `dstrsplit` contains an extra column called 'rowindex' containing the row index. This is used instead of the rownames to allow for duplicated indices (which are checked for and not allowed in a dataframe, unlike the case with a matrix).

**Value**

If `nsep` is specified then all characters up to (but excluding) the occurrence of `nsep` are treated as the index name. The remaining characters are split using the `widths` vector into fields (columns). `dstrfw` will fail with an error if any line does not contain enough characters to fill all expected columns, unless `strict` is `FALSE`. Excessive columns are ignored in that case. Lines may contain fewer columns (but not partial ones unless `strict` is `FALSE`) in which case they are set to NA.

`dstrfw` returns a `data.frame` with as many rows as there are lines in the input and as many columns as there are non-NA values in `col_types`, plus an additional column if `nsep` is specified. The colnames (other than the row index) are set to 'V' concatenated with the column number unless `col_types` is a named vector in which case the names are inherited.

**Author(s)**

Taylor Arnold and Simon Urbanek

**Examples**

```
input = c("bear\t22.7horse+3", "pear\t 3.4mouse-3", "dogs\t14.8prime-8")
z = dstrfw(x = input, col_types = c("numeric", "character", "integer"),
          width=c(4L,5L,2L), nsep="\t")
z

# Now without row names (treat seperator as a 1 char width column with type NULL)
z = dstrfw(x = input,
          col_types = c("character", "NULL", "numeric", "character", "integer"),
          width=c(4L,1L,4L,5L,2L))
z
```

---

**dstrsplit***Split binary or character input into a dataframe*

---

**Description**

dstrsplit takes raw or character vector and splits it into a dataframe according to the separators.

**Usage**

```
dstrsplit(x, col_types, sep="|", nsep=NA, strict=TRUE, skip=0L, nrows=-1L,
          quote="")
```

**Arguments**

x	character vector (each element is treated as a row) or a raw vector (newlines separate rows)
col_types	required character vector or a list. A vector of classes to be assumed for the output dataframe. If it is a list, <code>class(x)[1]</code> will be used to determine the class of the contained element. It will not be recycled, and must be at least as long as the longest row if <code>strict</code> is <code>TRUE</code> . Possible values are "NULL" (when the column is skipped) one of the six atomic vector types ('character', 'numeric', 'logical', 'integer', 'complex', 'raw') or <code>POSIXct</code> . 'POSIXct' will parse date format in the form "YYYY-MM-DD hh:mm:ss.sss" assuming GMT time zone. The separators between digits can be any non-digit characters and only the date part is mandatory. See also <code>fasttime::asPOSIXct</code> for details.
sep	single character: field (column) separator. Set to <code>NA</code> for no separator; in other words, a single column.
nsep	index name separator (single character) or <code>NA</code> if no index names are included
strict	logical, if <code>FALSE</code> then <code>dstrsplit</code> will not fail on parsing errors, otherwise input not matching the format (e.g. more columns than expected) will cause an error.
skip	integer: the number of lines of the data file to skip before beginning to read data.
nrows	integer: the maximum number of rows to read in. Negative and other invalid values are ignored.

`quote` the set of quoting characters as a length 1 vector. To disable quoting altogether, use `quote = ""` (the default). Quoting is only considered for columns read as character.

## Details

If `nsep` is specified then all characters up to (but excluding) the occurrence of `nsep` are treated as the index name. The remaining characters are split using the `sep` character into fields (columns). `dstrsplit` will fail with an error if any line contains more columns than expected unless `strict` is `FALSE`. Excessive columns are ignored in that case. Lines may contain fewer columns in which case they are set to `NA`.

Note that it is legal to use the same separator for `sep` and `nsep` in which case the first field is treated as a row name and subsequent fields as data columns.

If `nsep` is specified, the output of `dstrsplit` contains an extra column called `'rowindex'` containing the row index. This is used instead of the `rownames` to allow for duplicated indices (which are checked for and not allowed in a dataframe, unlike the case with a matrix).

## Value

`dstrsplit` returns a data.frame with as many rows as there are lines in the input and as many columns as there are non-NULL values in `col_types`, plus an additional column if `nsep` is specified. The `colnames` (other than the row index) are set to `'V'` concatenated with the column number unless `col_types` is a named vector in which case the names are inherited.

## Author(s)

Taylor Arnold and Simon Urbanek

## Examples

```
input = c("apple\t2|2.7|horse|0d|1|2015-02-05 20:22:57",
          "pear\t7|3e3|bear|e4|1+3i|2015-02-05",
          "pear\te|1.8|bat|77|4.2i|2001-02-05")
z = dstrsplit(x = input,
             col_types = c("integer", "numeric", "character", "raw", "complex", "POSIXct"),
             sep="|", nsep="\t")
lapply(z, class)
z

# Ignoring the third column:
z = dstrsplit(x = input,
             col_types = c("integer", "numeric", "character", "raw", "complex", "POSIXct"),
             sep="|", nsep="\t")
z
```

---

`fdrbind`*Fast row-binding of lists and data frames*

---

**Description**

`fdrbind` takes a list of data frames or lists and merges them together by rows very much like `rbind` does for its arguments. But unlike `rbind` it specializes on data frames and lists of columns only and performs the merge entirely at C level which allows it to be much faster than `rbind` at the cost of generality.

**Usage**

```
fdrbind(list)
```

**Arguments**

`list`            lists of parts that can be either data frames or lists

**Details**

All parts are expected to have the same number of columns in the same order. No column name matching is performed, they are merged by position. Also the same column in each part has to be of the same type, no coercion is performed at this point. The first part determines the column names, if any. If the parts contain data frames, their rownames are ignored, only the contents are merged. Attributes are not copied, which is intentional. Probably the most common implocation is that if you use factors, they must have all the same levels, otherwise you have to convert factor columns to strings first.

**Value**

The merged data frame.

**Author(s)**

Simon Urbanek

**See Also**

[rbind](#)

---

idstrsplit	<i>Create an iterator for splitting binary or character input into a dataframe</i>
------------	--

---

### Description

`idstrsplit` takes a binary connection or character vector (which is interpreted as a file name) and splits it into a series of dataframes according to the separator.

### Usage

```
idstrsplit(x, col_types, sep="|", nsep=NA, strict=TRUE,
           max.line = 65536L, max.size = 33554432L)
```

### Arguments

<code>x</code>	character vector (each element is treated as a row) or a raw vector (newlines separate rows)
<code>col_types</code>	required character vector or a list. A vector of classes to be assumed for the output dataframe. If it is a list, <code>class(x)[1]</code> will be used to determine the class of the contained element. It will not be recycled, and must be at least as long as the longest row if <code>strict</code> is <code>TRUE</code> . Possible values are "NULL" (when the column is skipped) one of the six atomic vector types ('character', 'numeric', 'logical', 'integer', 'complex', 'raw') or <code>POSIXct</code> . 'POSIXct' will parse date format in the form "YYYY-MM-DD hh:mm:ss.sss" assuming GMT time zone. The separators between digits can be any non-digit characters and only the date part is mandatory. See also <code>fasttime::asPOSIXct</code> for details.
<code>sep</code>	single character: field (column) separator. Set to <code>NA</code> for no separator; in other words, a single column.
<code>nsep</code>	index name separator (single character) or <code>NA</code> if no index names are included
<code>strict</code>	logical, if <code>FALSE</code> then <code>dstrsplit</code> will not fail on parsing errors, otherwise input not matching the format (e.g. more columns than expected) will cause an error.
<code>max.line</code>	maximum length of one line (in bytes) - determines the size of the read buffer, default is 64kb
<code>max.size</code>	maximum size of the chunk (in bytes), default is 32Mb

### Details

If `nsep` is specified then all characters up to (but excluding) the occurrence of `nsep` are treated as the index name. The remaining characters are split using the `sep` character into fields (columns). `dstrsplit` will fail with an error if any line contains more columns than expected unless `strict` is `FALSE`. Excessive columns are ignored in that case. Lines may contain fewer columns in which case they are set to `NA`.

Note that it is legal to use the same separator for `sep` and `nsep` in which case the first field is treated as a row name and subsequent fields as data columns.

If `nsep` is specified, the output of `dstrsplit` contains an extra column called `'rowindex'` containing the row index. This is used instead of the rownames to allow for duplicated indices (which are checked for and not allowed in a dataframe, unlike the case with a matrix).

### Value

`idstrsplit` returns an iterator (closure). When `nextElem` is called on the iterator a dataframe is returned with as many rows as there are lines in the input and as many columns as there are non-NULL values in `col_types`, plus an additional column if `nsep` is specified. The colnames (other than the row index) are set to `'V'` concatenated with the column number unless `col_types` is a named vector in which case the names are inherited.

### Author(s)

Michael Kane

### Examples

```
col_names <- names(iris)
write.csv(iris, file="iris.csv", row.names=FALSE)
it <- idstrsplit("iris.csv", col_types=c(rep("numeric", 4), "character"),
                sep=",")
# Get the elements
iris_read <- it$nextElem()[-1,]
# or with the iterators package
# nextElem(it)
names(iris_read) <- col_names
print(head(iris_read))
unlink("iris.csv")
```

---

imstrsplit

*Create an iterator for splitting binary or character input into a matrix*

---

### Description

`imstrsplit` takes a binary connection or character vector (which is interpreted as a file name) and splits it into a character matrix according to the separator.

### Usage

```
imstrsplit(x, sep="|", nsep=NA, strict=TRUE, ncol = NA,
           type=c("character", "numeric", "logical", "integer", "complex",
                 "raw"), max.line = 65536L, max.size = 3354432L)
```

**Arguments**

<code>x</code>	character vector (each element is treated as a row) or a raw vector (LF characters '\n' separate rows) to split
<code>sep</code>	single character: field (column) separator. Set to NA for no separator; in other words, a single column.
<code>nsep</code>	row name separator (single character) or NA if no row names are included
<code>strict</code>	logical, if FALSE then <code>mstrsplit</code> will not fail on parsing errors, otherwise input not matching the format (e.g. more columns than expected) will cause an error.
<code>ncol</code>	number of columns to expect. If NA then the number of columns is guessed from the first line.
<code>type</code>	a character string representing one of the 6 atomic types: 'character', 'numeric', 'logical', 'integer', 'complex', or 'raw'. The output matrix will use this as its storage mode and the input will be parsed directly into this format without using intermediate strings.
<code>max.line</code>	maximum length of one line (in bytes) - determines the size of the read buffer, default is 64kb
<code>max.size</code>	maximum size of the chunk (in bytes), default is 32Mb

**Details**

If the input is a raw vector, then it is interpreted as ASCII/UTF-8 content with LF ('\n') characters separating lines. If the input is a character vector then each element is treated as a line.

If `nsep` is specified then all characters up to (but excluding) the occurrence of `nsep` are treated as the row name. The remaining characters are split using the `sep` character into fields (columns). If `ncol` is NA then the first line of the input determines the number of columns. `mstrsplit` will fail with an error if any line contains more columns than expected unless `strict` is FALSE. Excessive columns are ignored in that case. Lines may contain fewer columns in which case they are set to NA.

The processing is geared towards efficiency - no string re-coding is performed and raw input vector is processed directly, avoiding the creation of intermediate string representations.

Note that it is legal to use the same separator for `sep` and `nsep` in which case the first field is treated as a row name and subsequent fields as data columns.

**Value**

A matrix with as many rows as they are lines in the input and as many columns as there are fields in the first line. The storage mode of the matrix will be determined by the input to `type`.

**Author(s)**

Michael Kane

### Examples

```
mm <- model.matrix(~., iris)
f <- file("iris_mm.io", "wb")
writeBin(as.output(mm), f)
close(f)
it <- imstrsplit("iris_mm.io", type="numeric", nsep="\t")
iris_mm <- it$nextElem()
print(head(iris_mm))
unlink("iris_mm.io")
```

---

input.file

*Load a file on the disk*

---

### Description

input.file efficiently reads a file on the disk into R using a formatter function. The function may be mstrsplit, dstrsplit, dstrfw, but can also be a user-defined function.

### Usage

```
input.file(file_name, formatter = mstrsplit, ...)
```

### Arguments

file\_name      the input filename as a character string  
formatter      a function for formatting the input. mstrsplit is used by default.  
...            other arguments passed to the formatter

### Value

the return type of the formatter function; by default a character matrix.

### Author(s)

Taylor Arnold and Simon Urbanek



---

line.merge	<i>Merge multiple sources</i>
------------	-------------------------------

---

**Description**

Read lines for a collection of sources and merges the results to a single output.

**Usage**

```
line.merge(sources, target, sep = "|", close = TRUE)
```

**Arguments**

sources	A list or vector of connections which need to be merged
target	A connection object or a character string giving the output of the merge. If a character string a new file connection will be created with the supplied file name.
sep	string specifying the key delimiter. Only the first character is used. Can be "" if the entire string is to be treated as a key.
close	logical. Should the input to sources be closed by the function.

**Value**

No explicit value is returned. The function is used purely for its side effects on the sources and target.

**Author(s)**

Simon Urbanek

---

mstrsplit	<i>Split binary or character input into a matrix</i>
-----------	--

---

**Description**

mstrsplit takes either raw or character vector and splits it into a character matrix according to the separators.

**Usage**

```
mstrsplit(x, sep="|", nsep=NA, strict=TRUE, ncol = NA,
          type=c("character", "numeric", "logical", "integer", "complex", "raw"),
          skip=0L, nrows=-1L, quote="")
```

**Arguments**

x	character vector (each element is treated as a row) or a raw vector (LF characters '\n' separate rows) to split
sep	single character: field (column) separator. Set to NA for no separator; in other words, a single column.
nsep	row name separator (single character) or NA if no row names are included
strict	logical, if FALSE then mstrsplit will not fail on parsing errors, otherwise input not matching the format (e.g. more columns than expected) will cause an error.
ncol	number of columns to expect. If NA then the number of columns is guessed from the first line.
type	a character string representing one of the 6 atomic types: 'character', 'numeric', 'logical', 'integer', 'complex', or 'raw'. The output matrix will use this as its storage mode and the input will be parsed directly into this format without using intermediate strings.
skip	integer: the number of lines of the data file to skip before parsing records.
nrows	integer: the maximum number of rows to read in. Negative and other invalid values are ignored, and indicate that the entire input should be processed.
quote	the set of quoting characters as a length 1 vector. To disable quoting altogether, use quote = "" (the default). Quoting is only considered for columns read as character.

**Details**

If the input is a raw vector, then it is interpreted as ASCII/UTF-8 content with LF ('\n') characters separating lines. If the input is a character vector then each element is treated as a line.

If nsep is specified then all characters up to (but excluding) the occurrence of nsep are treated as the row name. The remaining characters are split using the sep character into fields (columns). If ncol is NA then the first line of the input determines the number of columns. mstrsplit will fail with an error if any line contains more columns than expected unless strict is FALSE. Excessive columns are ignored in that case. Lines may contain fewer columns in which case they are set to NA.

The processing is geared towards efficiency - no string re-coding is performed and raw input vector is processed directly, avoiding the creation of intermediate string representations.

Note that it is legal to use the same separator for sep and nsep in which case the first field is treated as a row name and subsequent fields as data columns.

**Value**

A matrix with as many rows as there are lines in the input and as many columns as there are fields in the first line. The storage mode of the matrix will be determined by the input to type.

**Author(s)**

Simon Urbanek

**Examples**

```
c <- c("A\tB|C|D", "A\tB|B|B", "B\tA|C|E")
m <- mstrsplit(gsub("\t","|",c))
dim(m)
m
m <- mstrsplit(c,, "\t")
rownames(m)
m

## use raw vectors instead
r <- charToRaw(paste(c, collapse="\n"))
mstrsplit(r)
mstrsplit(r, nsep="\t")
```

---

output.file

*Write an R object to a file as a character string*

---

**Description**

Writes any R object to a file or connection using an output formatter. Useful for pairing with the `input.file` function.

**Usage**

```
output.file(x, file, formatter.output = NULL)
```

**Arguments**

<code>x</code>	R object to write to the file
<code>file</code>	the input filename as a character string or a connection object open for writing.
<code>formatter.output</code>	a function for formatting the output. Using null will attempt to find the appropriate method given the class of the input <code>x</code> .

**Value**

invisibly returns the input to `file`.

**Author(s)**

Taylor Arnold and Simon Urbanek

---

read.csv.raw	<i>Fast data frame input</i>
--------------	------------------------------

---

### Description

A fast replacement of `read.csv` and `read.delim` which pre-loads the data as a raw vector and parses without constructing intermediate strings.

### Usage

```
read.csv.raw(file, header=TRUE, sep=",", skip=0L, fileEncoding="",
             colClasses, nrows = -1L, nsep = NA, strict=TRUE,
             nrowsClasses = 25L, quote="'\"")
```

```
read.delim.raw(file, header=TRUE, sep="\t", ...)
```

### Arguments

<code>file</code>	A connection object or a character string naming a file from which to read data.
<code>header</code>	logical. Does a header row exist for the data.
<code>sep</code>	single character: field (column) separator.
<code>skip</code>	integer. Number of lines to skip in the input, no including the header.
<code>fileEncoding</code>	The name of the encoding to be assumed. Only used when <code>con</code> is a character string naming a file.
<code>colClasses</code>	an optional character vector indicating the column types. A vector of classes to be assumed for the output dataframe. If it is a list, <code>class(x)[1]</code> will be used to determine the class of the contained element. It will not be recycled, and must be at least as long as the longest row if <code>strict</code> is <code>TRUE</code> . Possible values are "NULL" (when the column is skipped) one of the six atomic vector types ('character', 'numeric', 'logical', 'integer', 'complex', 'raw') or <code>POSIXct</code> . 'POSIXct' will parse date format in the form "YYYY-MM-DD hh:mm:ss.sss" assuming GMT time zone. The separators between digits can be any non-digit characters and only the date part is mandatory. See also <code>fasttime::asPOSIXct</code> for details.
<code>nrows</code>	integer: the maximum number of rows to read in. Negative and other invalid values are ignored.
<code>nsep</code>	index name separator (single character) or NA if no index names are included
<code>strict</code>	logical, if <code>FALSE</code> then <code>dstrsplit</code> will not fail on parsing errors, otherwise input not matching the format (e.g. more columns than expected) will cause an error.
<code>nrowsClasses</code>	integer. Maximum number of rows of data to read to learn column types. Not used when <code>col_types</code> is supplied.
<code>quote</code>	the set of quoting characters as a length 1 vector. To disable quoting altogether, use <code>quote = ""</code> . Quoting is only considered for columns read as character.
<code>...</code>	additional parameters to pass to <code>read.csv.raw</code>

**Details**

See [dstrsplit](#) for the details of `nsep`, `sep`, and `strict`.

**Value**

A data frame containing a representation of the data in the file.

**Author(s)**

Taylor Arnold and Simon Urbanek

---

readAsRaw	<i>Read binary data in as raw</i>
-----------	-----------------------------------

---

**Description**

`readAsRaw` takes a connection or file name and reads it into a raw type.

**Usage**

```
readAsRaw(con, n, nmax, fileEncoding="")
```

**Arguments**

<code>con</code>	A connection object or a character string naming a file from which to save the output.
<code>n</code>	Expected number of bytes to read. Set to 65536L by default when <code>con</code> is a connection, and set to the file size by default when <code>con</code> is a character string.
<code>nmax</code>	Maximum number of bytes to read; missing or <code>Inf</code> to read in the entire connection.
<code>fileEncoding</code>	When <code>con</code> is a connection, the file encoding to use to open the connection.

**Value**

`readAsRaw` returns a raw type which can then be consumed by functions like `mstrsplit` and `dstrsplit`.

**Author(s)**

Taylor Arnold

## Examples

```
mm <- model.matrix(~., iris)
f <- file("iris_mm.io", "wb")
writeBin(as.output(mm), f)
close(f)
m <- mstrsplit(readAsRaw("iris_mm.io"), type="numeric", nsep="\t")
head(mm)
head(m)
unlink("iris_mm.io")
```

---

which.min.key

*Determine the next key in bitwise order*

---

## Description

which.min.key takes either a character vector or a list of strings and returns the location of the element that is lexicographically (using bitwise comparison) the first. In a sense it is which.min for strings. In addition, it supports prefix comparisons using a key delimiter (see below).

## Usage

```
which.min.key(keys, sep = "|")
```

## Arguments

keys	character vector or a list of strings to use as input
sep	string specifying the key delimiter. Only the first character is used. Can be "" if the entire string is to be treated as a key.

## Details

which.min.key considers the prefix of each element in keys up to the delimiter specified by sep. It returns the index of the element which is lexicographically first among all the elements, using bitwise comparison (i.e. the locale is not used and multi-byte characters are not considered as one character).

If keys is a character vector then NA elements are treated as non-existent and will never be picked.

If keys is a list then only string elements of length > 0 are eligible and NAs are not treated specially (hence they will be sorted in just like the "NA" string).

## Value

scalar integer denoting the index of the lexicographically first element. In case of a tie the lowest index is returned. If there are no eligible elements in keys then a zero-length integer vector is returned.

## Author(s)

Simon Urbanek

**See Also**[which.min](#)**Examples**

```

which.min.key(c("g", "a", "b", NA, "z", "a"))
which.min.key(c("g", "a|z", "b", NA, "z|0", "a"))
which.min.key(c("g", "a|z", "b", NA, "z|0", "a"), "")
which.min.key(list("X", 1, NULL, "F", "Z"))
which.min.key(as.character(c(NA, NA)))
which.min.key(NA_character_)
which.min.key(list())

```

write.csv.raw

*Fast data output to disk***Description**

A fast replacement of `write.csv` and `write.table` which saves the data as a raw vector rather than a character one.

**Usage**

```
write.csv.raw(x, file = "", append = FALSE, sep = ",", nsep="\t",
             col.names = !is.null(colnames(x)), fileEncoding = "")
```

```
write.table.raw(x, file = "", sep = " ", ...)
```

**Arguments**

<code>x</code>	object which is to be saved.
<code>file</code>	A connection object or a character string naming a file from which to save the output.
<code>append</code>	logical. Only used when <code>file</code> is a character string.
<code>sep</code>	field (column) separator.
<code>nsep</code>	index name separator (single character) or NA if no index names are included
<code>col.names</code>	logical. Should a row of column names be written.
<code>fileEncoding</code>	character string: if non-empty declares the encoding to be used on a file.
<code>...</code>	additional parameters to pass to <code>write.table.raw</code> .

**Details**

See [as.output](#) for the details of how various data types are converted to raw vectors (or character vectors when raw is not available).

**Author(s)**

Taylor Arnold and Simon Urbanek

# Index

## \*Topic **iterator**

`idstrsplit`, 13

`imstrsplit`, 14

## \*Topic **manip**

`.default.formatter`, 2

`as.output`, 3

`chunk`, 4

`chunk.apply`, 5

`chunk.map`, 6

`ctapply`, 7

`dstrfw`, 8

`dstrsplit`, 10

`fdrbind`, 12

`input.file`, 16

`line.merge`, 17

`mstrsplit`, 17

`output.file`, 19

`read.csv.raw`, 20

`which.min.key`, 22

`write.csv.raw`, 23

`.default.formatter`, 2

`as.output`, 2, 3, 6, 23

`chunk`, 4

`chunk.apply`, 5

`chunk.map`, 6

`chunk.reader`, 6

`chunk.tapply(chunk.apply)`, 5

`ctapply`, 7

`dstrfw`, 8

`dstrsplit`, 10, 21

`fdrbind`, 12

`idstrsplit`, 13

`imstrsplit`, 14

`input.file`, 16

`line.merge`, 17

`mstrsplit`, 2, 5, 17

`order`, 7

`output.file`, 19

`rbind`, 12

`read.chunk`, 6

`read.chunk(chunk)`, 4

`read.csv.raw`, 20

`read.delim.raw(read.csv.raw)`, 20

`readAsRaw`, 21

`rowindex(dstrsplit)`, 10

`sort`, 7

`tapply`, 8

`which.min`, 23

`which.min.key`, 22

`write.csv.raw`, 23

`write.table.raw(write.csv.raw)`, 23