

Package ‘VC2copula’

October 23, 2020

Title Extend the 'copula' Package with Families and Models from 'VineCopula'

Version 0.1.1

Description Provides new classes for (rotated) BB1, BB6, BB7, BB8, and Tawn copulas, extends the existing Gumbel and Clayton families with rotations, and allows to set up a vine copula model using the 'copula' API. Corresponding objects from the 'VineCopula' API can easily be converted.

License GPL-3

Encoding UTF-8

LazyData true

URL <https://github.com/tnagler/VC2copula>

BugReports <https://github.com/tnagler/VC2copula/issues>

Depends copula (>= 0.999-19.1)

Imports VineCopula (>= 2.3.0), methods

LinkingTo VineCopula

Suggests lattice, testthat (>= 2.1.0), spelling

RoxygenNote 7.1.1

Language en-US

NeedsCompilation yes

Author Thomas Nagler [aut, cre],
Benedikt Graeler [ctb]

Maintainer Thomas Nagler <mail@tnagler.com>

Repository CRAN

Date/Publication 2020-10-23 21:10:07 UTC

R topics documented:

BB1Copula	2
BB1Copula-class	3

BB6Copula	4
BB6Copula-class	5
BB7Copula	5
BB7Copula-class	6
BB8Copula	7
BB8Copula-class	8
BiCop2copula	9
ddCopula	10
joeBiCopula	11
joeBiCopula-class	12
surClaytonCopula	12
surClaytonCopula-class	13
surGumbelCopula	14
surGumbelCopula-class	14
tawnT1Copula	15
tawnT1Copula-class	16
tawnT2Copula	16
tawnT2Copula-class	17
vineCopula	18
vineCopula-class	19

Index	20
--------------	-----------

BB1Copula	<i>Constructors for BB1 copulas</i>
-----------	-------------------------------------

Description

Constructs an object of the [BB1Copula](#) (survival *sur*, 90 degree rotated *r90* and 270 degree rotated *r270*) family for given parameters.

Usage

```
BB1Copula(param = c(1, 1))
```

```
surBB1Copula(param = c(1, 1))
```

```
r90BB1Copula(param = c(-1, -1))
```

```
r270BB1Copula(param = c(-1, -1))
```

Arguments

`param` The parameter `param` defines the copula through `theta` and `delta`.

Value

One of the respective BB1 copula classes ([BB1Copula](#), [surBB1Copula](#), [r90BB1Copula](#), [r270BB1Copula](#)).

References

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

See Also

See also [BB6Copula\(\)](#), [BB7Copula\(\)](#), [BB8Copula\(\)](#) and [joeCopula\(\)](#) for further wrapper functions to the [VineCopula-package\(\)](#).

Examples

```
library(copula)

persp(BB1Copula(c(1, 1.5)), dCopula, zlim = c(0, 10))
persp(surBB1Copula(c(1, 1.5)), dCopula, zlim = c(0, 10))
persp(r90BB1Copula(c(-1, -1.5)), dCopula, zlim = c(0, 10))
persp(r270BB1Copula(c(-1, -1.5)), dCopula, zlim = c(0, 10))
```

BB1Copula-class

BB1 copula models

Description

Wrapper classes representing the BB1, survival BB1, 90 degree and 270 degree rotated BB1 copula families (Joe 1997) from [VineCopula-package\(\)](#).

Objects from the Classes

Objects can be created by calls of the form `new("BB1Copula", ...)`, `new("surBB1Copula", ...)`, `new("r90BB1Copula", ...)` and `new("r270BB1Copula", ...)` or by the functions [BB1Copula\(\)](#), [surBB1Copula\(\)](#), [r90BB1Copula\(\)](#) and [r270BB1Copula\(\)](#).

References

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

See Also

See also [BB6Copula](#), [BB7Copula](#), [BB8Copula](#) and [joeCopula](#) for further wrapper classes to the [VineCopula-package\(\)](#).

Examples

```
showClass("BB1Copula")
```

BB6Copula*Constructors for BB6 copulas*

Description

Constructs an object of the [BB6Copula](#) (survival `sur`, 90 degree rotated `r90` and 270 degree rotated `r270`) family for given parameters.

Usage

```
BB6Copula(param = c(1, 1))
```

```
surBB6Copula(param = c(1, 1))
```

```
r90BB6Copula(param = c(-1, -1))
```

```
r270BB6Copula(param = c(-1, -1))
```

Arguments

`param` The parameter `param` defines the copula through `theta` and `delta`.

Value

One of the respective BB6 copula classes ([BB6Copula](#), [surBB6Copula](#), [r90BB6Copula](#), [r270BB6Copula](#)).

References

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

See Also

See also [BB6Copula\(\)](#), [BB7Copula\(\)](#), [BB8Copula\(\)](#) and [joeCopula\(\)](#) for further wrapper functions to the [VineCopula-package\(\)](#).

Examples

```
library(copula)

persp(BB6Copula(c(1, 1.5)), dCopula, zlim = c(0, 10))
persp(surBB6Copula(c(1, 1.5)), dCopula, zlim = c(0, 10))
persp(r90BB6Copula(c(-1, -1.5)), dCopula, zlim = c(0, 10))
persp(r270BB6Copula(c(-1, -1.5)), dCopula, zlim = c(0, 10))
```

BB6Copula-class	<i>BB6 copula models</i>
-----------------	--------------------------

Description

Wrapper classes representing the BB6, survival BB6, 90 degree and 270 degree rotated BB6 copula families (Joe 1997) from [VineCopula-package\(\)](#).

Objects from the Classes

Objects can be created by calls of the form `new("BB6Copula", ...)`, `new("surBB6Copula", ...)`, `new("r90BB6Copula", ...)` and `new("r270BB6Copula", ...)` or by the functions [BB6Copula\(\)](#), [surBB6Copula\(\)](#), [r90BB6Copula\(\)](#) and [r270BB6Copula\(\)](#).

References

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

See Also

See also [BB6Copula](#), [BB7Copula](#), [BB8Copula](#) and [joeCopula](#) for further wrapper classes to the [VineCopula-package\(\)](#).

Examples

```
showClass("BB6Copula")
```

BB7Copula	<i>Constructors for BB7 copulas</i>
-----------	-------------------------------------

Description

Constructs an object of the [BB7Copula](#) (survival `sur`, 90 degree rotated `r90` and 270 degree rotated `r270`) family for given parameters.

Usage

```
BB7Copula(param = c(1, 1))
```

```
surBB7Copula(param = c(1, 1))
```

```
r90BB7Copula(param = c(-1, -1))
```

```
r270BB7Copula(param = c(-1, -1))
```

Arguments

param The parameter param defines the copula through theta and delta.

Value

One of the respective BB7 copula classes ([BB7Copula](#), [surBB7Copula](#), [r90BB7Copula](#), [r270BB7Copula](#)).

References

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

See Also

See also [BB6Copula\(\)](#), [BB7Copula\(\)](#), [BB8Copula\(\)](#) and [joeCopula\(\)](#) for further wrapper functions to the [VineCopula-package\(\)](#).

Examples

```
library(copula)

persp(BB7Copula(c(1, 1.5)), dCopula, zlim = c(0, 10))
persp(surBB7Copula(c(1, 1.5)), dCopula, zlim = c(0, 10))
persp(r90BB7Copula(c(-1, -1.5)), dCopula, zlim = c(0, 10))
persp(r270BB7Copula(c(-1, -1.5)), dCopula, zlim = c(0, 10))
```

BB7Copula-class

BB7 copula models

Description

Wrapper classes representing the BB7, survival BB7, 90 degree and 270 degree rotated BB7 copula families (Joe 1997) from [VineCopula-package\(\)](#).

Objects from the Classes

Objects can be created by calls of the form `new("BB7Copula", ...)`, `new("surBB7Copula", ...)`, `new("r90BB7Copula", ...)` and `new("r270BB7Copula", ...)` or by the functions [BB7Copula\(\)](#), [surBB7Copula\(\)](#), [r90BB7Copula\(\)](#) and [r270BB7Copula\(\)](#).

References

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

See Also

See also [BB7Copula](#), [BB7Copula](#), [BB8Copula](#) and [joeCopula](#) for further wrapper classes to the [VineCopula-package\(\)](#).

Examples

```
showClass("BB7Copula")
```

BB8Copula	<i>Constructors for BB8 copulas</i>
-----------	-------------------------------------

Description

Constructs an object of the [BB8Copula](#) (survival `sur`, 90 degree rotated `r90` and 270 degree rotated `r270`) family for given parameters.

Usage

```
BB8Copula(param = c(1, 1))
```

```
surBB8Copula(param = c(1, 1))
```

```
r90BB8Copula(param = c(-1, -1))
```

```
r270BB8Copula(param = c(-1, -1))
```

Arguments

`param` The parameter `param` defines the copula through `theta` and `delta`.

Value

One of the respective BB8 copula classes ([BB8Copula](#), [surBB8Copula](#), [r90BB8Copula](#), [r270BB8Copula](#)).

References

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

See Also

See also [BB6Copula\(\)](#), [BB7Copula\(\)](#), [BB8Copula\(\)](#) and [joeCopula\(\)](#) for further wrapper functions to the [VineCopula-package\(\)](#).

Examples

```
library(copula)

persp(BB8Copula(c(2, 0.9)), dCopula, zlim = c(0, 10))
persp(surBB8Copula(c(2, 0.9)), dCopula, zlim = c(0, 10))
persp(r90BB8Copula(c(-2, -0.9)), dCopula, zlim = c(0, 10))
persp(r270BB8Copula(c(-2, -0.9)), dCopula, zlim = c(0, 10))
```

BB8Copula-class

BB8 copula models

Description

Wrapper classes representing the BB8, survival BB8, 90 degree and 270 degree rotated BB8 copula families (Joe 1997) from [VineCopula-package\(\)](#).

Objects from the Classes

Objects can be created by calls of the form `new("BB8Copula", ...)`, `new("surBB8Copula", ...)`, `new("r90BB8Copula", ...)` and `new("r270BB8Copula", ...)` or by the functions [BB8Copula\(\)](#), [surBB8Copula\(\)](#), [r90BB8Copula\(\)](#) and [r270BB8Copula\(\)](#).

References

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

See Also

See also [BB8Copula](#), [BB8Copula](#), [BB8Copula](#) and [joeCopula](#) for further wrapper classes to the [VineCopula-package\(\)](#).

Examples

```
showClass("BB8Copula")
```


Description

A VineCopula family index along with its parameters is used to construct a corresponding [copula](#) object.

Usage

```
BiCop2copula(family, par, par2 = 0, obj = NULL)
```

```
copulaFromFamilyIndex(family, par, par2 = 0)
```

Arguments

family	a family index as defined in VineCopula-package() .
par	first parameter.
par2	second parameter.
obj	BiCop() object containing the family and parameter specification.

Details

If the family and parameter specification is stored in a [\[BiCop\(\)\]](#) object `obj`, the alternative version

```
BiCop2copula(u1, u2, obj)
```

can be used.

Value

An object inheriting [copula](#) corresponding to the specific family.

Examples

```
# normalCopula with parameter 0.5
BiCop2copula(1, 0.5)

# rotated Tawn T2 copula
BiCop2copula(224, -2, 0.5)
```

ddCopula

*Partial Derivatives of Copulas***Description**

Similar to `dCopula()` and `pCopula()` the function `dduCopula` evaluates the partial derivative $\frac{\partial}{\partial u} C(u, v)$ and the function `ddvCopula` evaluates the partial derivative $\frac{\partial}{\partial v} C(u, v)$ of the provided copula.

Usage

```
dduCopula(u, copula, ...)
```

Arguments

`u` Pairs of values for which the partial derivative should be evaluated.
`copula` The copula object representing the family member of interest.
`...` additional arguments can be passed on to the underlying functions.

Value

A vector of the evaluated partial derivatives of the same length as rows in `u`.

Examples

```
library(copula)

BB1Cop <- BB1Copula()
BB1CopSmpl <- rCopula(100, BB1Cop)

# conditional probabilities of a Gaussian copula given u
BB1GivenU <- dduCopula(BB1CopSmpl, BB1Cop)

# vs. conditional probabilities of a Gaussian copula given v
BB1GivenV <- ddvCopula(BB1CopSmpl[, c(2, 1)], BB1Cop)

plot(BB1GivenU, BB1GivenV)
abline(0, 1)
```

`joeBiCopula`*Constructors for Joe copulas*

Description

Constructs an object of the (survival `surJoeBiCopula`, 90 degree rotated `r90JoeBiCopula` and 270 degree rotated `r270JoeBiCopula`) family for a given parameter. Note that package [copula-package\(\)](#) provides a class [joeCopula](#) as well.

Usage

```
joeBiCopula(param = 2)

surJoeBiCopula(param = 2)

r90JoeBiCopula(param = -2)

r270JoeBiCopula(param = -2)
```

Arguments

`param` The parameter `param` defines the copula through `theta`.

Value

One of the respective Joe copula classes ([joeBiCopula](#), [surJoeBiCopula](#), [r90JoeBiCopula](#), [r270JoeBiCopula](#)).

References

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

See Also

See also [BB1Copula\(\)](#), [BB6Copula\(\)](#), [BB7Copula\(\)](#) and [BB8Copula\(\)](#) for further wrapper functions to the [VineCopula-package\(\)](#).

Examples

```
library(copula)

persp(surJoeBiCopula(1.5), dCopula, zlim = c(0, 10))
persp(r90JoeBiCopula(-1.5), dCopula, zlim = c(0, 10))
persp(r270JoeBiCopula(-1.5), dCopula, zlim = c(0, 10))
```

joeBiCopula-class *Joe copula models*

Description

Wrapper classes representing the bivariate Joe, survival Joe, 90 degree and 270 degree rotated Joe copula families (Joe 1997) from [VineCopula-package\(\)](#). Note that package [copula-package\(\)](#) provides a class [joeCopula](#) as well.

Objects from the Classes

Objects can be created by calls of the form `new("joeBiCopula", ...)`, `new("surJoeBiCopula", ...)`, `new("r90JoeBiCopula", ...)` and `new("r270JoeBiCopula", ...)` or by the functions [joeBiCopula\(\)](#), [surJoeBiCopula\(\)](#), [r90JoeBiCopula\(\)](#) and [r270JoeBiCopula\(\)](#).

References

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

See Also

See also [BB1Copula](#), [BB6Copula](#), [BB7Copula](#) and [BB8Copula](#) for further wrapper classes to the [VineCopula-package\(\)](#).

Examples

```
showClass("surJoeBiCopula")
```

surClaytonCopula *Constructors for survival and rotated Clayton Copulas*

Description

These are wrappers to functions from [VineCopula-package\(\)](#)

Usage

```
surClaytonCopula(param = 1)
```

```
r90ClaytonCopula(param = -1)
```

```
r270ClaytonCopula(param = -1)
```

Arguments

param A single parameter defining the Copula.

Value

An object of class [surClaytonCopula](#), [r90ClaytonCopula](#) or [r270ClaytonCopula](#) respectively.

Examples

```
library(copula)

persp(surClaytonCopula(1.5), dCopula, zlim = c(0, 10))
persp(r90ClaytonCopula(-1.5), dCopula, zlim = c(0, 10))
persp(r270ClaytonCopula(-1.5), dCopula, zlim = c(0, 10))
```

surClaytonCopula-class

Survival and rotated Clayton copula models

Description

A class representing rotated versions of the Clayton copula family (survival, 90 and 270 degree rotated).

Objects from the Class

Objects can be created by calls of the form `new("surClaytonCopula", ...)`, `new("r90ClaytonCopula", ...)` and `new("r270ClaytonCopula", ...)` or by the function [surClaytonCopula\(\)](#), [r90ClaytonCopula\(\)](#) and [r270ClaytonCopula\(\)](#) respectively.

See Also

[VineCopula-package\(\)](#)

Examples

```
library(copula)

persp(surClaytonCopula(.5), dCopula, zlim = c(0, 10))
persp(r90ClaytonCopula(-.5), dCopula, zlim = c(0, 10))
persp(r270ClaytonCopula(-.5), dCopula, zlim = c(0, 10))
```

surGumbelCopula *Constructors for survival and rotated Gumbel Copulas*

Description

These are wrappers to functions from [VineCopula-package\(\)](#)

Usage

```
surGumbelCopula(param = 1)
```

```
r90GumbelCopula(param = -1)
```

```
r270GumbelCopula(param = -1)
```

Arguments

param A single parameter defining the Copula.

Value

An object of class [surGumbelCopula](#), [r90GumbelCopula](#) or [r270GumbelCopula](#) respectively.

Examples

```
library(copula)

persp(surGumbelCopula(1.5), dCopula, zlim = c(0, 10))
persp(r90GumbelCopula(-1.5), dCopula, zlim = c(0, 10))
persp(r270GumbelCopula(-1.5), dCopula, zlim = c(0, 10))
```

surGumbelCopula-class *Survival and rotated Gumbel copula models*

Description

A class representing rotated versions of the Gumbel copula family (survival, 90 and 270 degree rotated).

Objects from the Class

Objects can be created by calls of the form `new("surGumbelCopula", ...)`, `new("r90GumbelCopula", ...)` and `new("r270GumbelCopula", ...)` or by the function [surGumbelCopula\(\)](#), [r90GumbelCopula\(\)](#) and [r270GumbelCopula\(\)](#) respectively.

See Also

[VineCopula-package\(\)](#)

Examples

```
library(copula)

persp(surGumbelCopula(5), dCopula, zlim = c(0, 10))
persp(r90GumbelCopula(-5), dCopula, zlim = c(0, 10))
persp(r270GumbelCopula(-5), dCopula, zlim = c(0, 10))
```

tawnT1Copula	<i>Constructor for Tawn copulas (type 1)</i>
--------------	--

Description

Constructs an object of the [tawnT1Copula](#) (survival sur, 90 degree rotated r90 and 270 degree rotated r270) family for given parameters.

Usage

```
tawnT1Copula(param = c(2, 0.5))

surTawnT1Copula(param = c(2, 0.5))

r90TawnT1Copula(param = c(-2, 0.5))

r270TawnT1Copula(param = c(-2, 0.5))
```

Arguments

param The parameter param defines the copula through param1 and param2.

Value

One of the Tawn type 1 copula classes ([tawnT1Copula](#), [surTawnT1Copula](#), [r90TawnT1Copula](#), [r270TawnT1Copula](#)).

See Also

[tawnT1Copula\(\)](#) and the package [VineCopula-package\(\)](#) for implementation details.

Examples

```
library(copula)

persp(tawnT1Copula(), dCopula, zlim = c(0, 10))
persp(surTawnT1Copula(), dCopula, zlim = c(0, 10))
persp(r90TawnT1Copula(), dCopula, zlim = c(0, 10))
persp(r270TawnT1Copula(), dCopula, zlim = c(0, 10))
```

tawnT1Copula-class	<i>Tawn copula models (type 1)</i>
--------------------	------------------------------------

Description

S4-class representation of the Tawn Copula family of type 1 and rotated versions there of.

Objects from the Class

Objects can be created by calls of the form `new("tawnT1Copula", ...)`, or through the explicit constructors `tawnT1Copula()`, `surTawnT1Copula()`, `r90TawnT1Copula()` and `r270TawnT1Copula()` respectively.

See Also

`tawnT1Copula` and the package `VineCopula-package()` for implementation details.

Examples

```
showClass("tawnT1Copula")
```

tawnT2Copula	<i>Constructor for Tawn copulas (type 2)</i>
--------------	--

Description

Constructs an object of the `tawnT2Copula` (survival `sur`, 90 degree rotated `r90` and 270 degree rotated `r270`) family for given parameters.

Usage

```
tawnT2Copula(param = c(2, 0.5))

surTawnT2Copula(param = c(2, 0.5))

r90TawnT2Copula(param = c(-2, 0.5))

r270TawnT2Copula(param = c(-2, 0.5))
```


Arguments

param The parameter param defines the copula through param1 and param2.

Value

One of the Tawn type 2 copula classes ([tawnT2Copula](#), [surTawnT2Copula](#), [r90TawnT2Copula](#), [r270TawnT2Copula](#)).

See Also

[tawnT2Copula\(\)](#) and the package [VineCopula-package\(\)](#) for implementation details.

Examples

```
library(copula)

persp(tawnT2Copula(), dCopula, zlim = c(0, 10))
persp(surTawnT2Copula(), dCopula, zlim = c(0, 10))
persp(r90TawnT2Copula(), dCopula, zlim = c(0, 10))
persp(r270TawnT2Copula(), dCopula, zlim = c(0, 10))
```

tawnT2Copula-class *Tawn copula models (type 2)*

Description

S4-class representation of the Tawn Copula family of type 2 and rotated versions there of.

Objects from the Class

Objects can be created by calls of the form `new("tawnT2Copula", ...)`, or through the explicit constructors [tawnT2Copula\(\)](#), [surTawnT2Copula\(\)](#), [r90TawnT2Copula\(\)](#) and [r270TawnT2Copula\(\)](#) respectively.

See Also

[tawnT2Copula](#) and the package [VineCopula-package\(\)](#) for implementation details.

Examples

```
showClass("tawnT2Copula")
```

`vineCopula`*Constructor of the Class `vineCopula`.*

Description

Constructs an instance of the `vineCopula` class.

Usage

```
vineCopula(RVM, type = "CVine")
```

Arguments

<code>RVM</code>	An object of class <code>RVineMatrix</code> generated from <code>RVineMatrix</code> in the package <code>VineCopula-package</code> or an integer (e.g. 4L) defining the dimension (an independent Gaussian C-vine of this dimension will be constructed).
<code>type</code>	A predefined type if only the dimension is provided and ignored otherwise, the default is a canonical vine

Value

An instance of the `vineCopula` class.

Author(s)

Benedikt Graeler

References

Aas, K., C. Czado, A. Frigessi, and H. Bakken (2009). Pair-copula constructions of multiple dependence Insurance: Mathematics and Economics 44 (2), 182-198.

Examples

```
# a C-vine of independent copulas
vine <- vineCopula(4L, "CVine")

library(copula)
library(lattice)

cloud(V1 ~ V2 + V3, as.data.frame(rCopula(500, vine)))
```

vineCopula-class	Class "vineCopula"
------------------	--------------------

Description

A class representing vine copulas in a object oriented implementations. Many functions go back to the package [VineCopula-package](#)

Objects from the Class

Objects can be created by calls of the form `new("vineCopula",...)` or through the function [vineCopula](#).

Author(s)

Benedikt Graeler

References

Aas, K., C. Czado, A. Frigessi, and H. Bakken (2009). Pair-copula constructions of multiple dependence Insurance: Mathematics and Economics 44 (2), 182-198.

See Also

[RVineMatrix](#) from package [VineCopula-package](#)

Examples

```
showClass("vineCopula")
```

Index

* classes

- BB1Copula-class, 3
- BB6Copula-class, 5
- BB7Copula-class, 6
- BB8Copula-class, 8
- joeBiCopula-class, 12
- surClaytonCopula-class, 13
- surGumbelCopula-class, 14
- tawnT1Copula-class, 16
- tawnT2Copula-class, 17
- vineCopula-class, 19

* conditional

- ddCopula, 10

* copula

- BB1Copula, 2
- surClaytonCopula, 12
- surGumbelCopula, 14
- tawnT1Copula, 15
- tawnT2Copula, 16

* derivative

- ddCopula, 10

* distribution

- BB1Copula, 2
- tawnT1Copula, 15
- tawnT2Copula, 16
- vineCopula, 18

* multivariate

- vineCopula, 18

* partial

- ddCopula, 10

* probabilities

- ddCopula, 10

- BB1Copula, 2, 2, 12
- BB1Copula(), 3, 11
- BB1Copula-class, 3
- BB6Copula, 3, 4, 4, 5, 12
- BB6Copula(), 3–7, 11
- BB6Copula-class, 5
- BB7Copula, 3, 5, 5, 6, 7, 12

- BB7Copula(), 3, 4, 6, 7, 11

- BB7Copula-class, 6

- BB8Copula, 3, 5, 7, 7, 8, 12

- BB8Copula(), 3, 4, 6–8, 11

- BB8Copula-class, 8

- BiCop(), 9

- BiCop2copula, 9

- copula, 9

- copulaFromFamilyIndex (BiCop2copula), 9

- dCopula(), 10

- ddCopula, 10

- dduCopula (ddCopula), 10

- dduCopula, matrix, BB1Copula-method (BB1Copula-class), 3

- dduCopula, matrix, BB6Copula-method (BB6Copula-class), 5

- dduCopula, matrix, BB7Copula-method (BB7Copula-class), 6

- dduCopula, matrix, BB8Copula-method (BB8Copula-class), 8

- dduCopula, matrix, joeBiCopula-method (joeBiCopula-class), 12

- dduCopula, matrix, r270BB1Copula-method (BB1Copula-class), 3

- dduCopula, matrix, r270BB6Copula-method (BB6Copula-class), 5

- dduCopula, matrix, r270BB7Copula-method (BB7Copula-class), 6

- dduCopula, matrix, r270BB8Copula-method (BB8Copula-class), 8

- dduCopula, matrix, r270ClaytonCopula-method (surClaytonCopula-class), 13

- dduCopula, matrix, r270GumbelCopula-method (surGumbelCopula-class), 14

- dduCopula, matrix, r270JoeBiCopula-method (joeBiCopula-class), 12

- dduCopula, matrix, r270TawnT1Copula-method (tawnT1Copula-class), 16

- dduCopula, matrix, r270TawnT2Copula-method (tawnT2Copula-class), 17
- dduCopula, matrix, r90BB1Copula-method (BB1Copula-class), 3
- dduCopula, matrix, r90BB6Copula-method (BB6Copula-class), 5
- dduCopula, matrix, r90BB7Copula-method (BB7Copula-class), 6
- dduCopula, matrix, r90BB8Copula-method (BB8Copula-class), 8
- dduCopula, matrix, r90ClaytonCopula-method (surClaytonCopula-class), 13
- dduCopula, matrix, r90GumbelCopula-method (surGumbelCopula-class), 14
- dduCopula, matrix, r90JoeBiCopula-method (joeBiCopula-class), 12
- dduCopula, matrix, r90TawnT1Copula-method (tawnT1Copula-class), 16
- dduCopula, matrix, r90TawnT2Copula-method (tawnT2Copula-class), 17
- dduCopula, matrix, surBB1Copula-method (BB1Copula-class), 3
- dduCopula, matrix, surBB6Copula-method (BB6Copula-class), 5
- dduCopula, matrix, surBB7Copula-method (BB7Copula-class), 6
- dduCopula, matrix, surBB8Copula-method (BB8Copula-class), 8
- dduCopula, matrix, surClaytonCopula-method (surClaytonCopula-class), 13
- dduCopula, matrix, surGumbelCopula-method (surGumbelCopula-class), 14
- dduCopula, matrix, surJoeBiCopula-method (joeBiCopula-class), 12
- dduCopula, matrix, surTawnT1Copula-method (tawnT1Copula-class), 16
- dduCopula, matrix, surTawnT2Copula-method (tawnT2Copula-class), 17
- dduCopula, matrix, tawnT1Copula-method (tawnT1Copula-class), 16
- dduCopula, matrix, tawnT2Copula-method (tawnT2Copula-class), 17
- dduCopula, numeric, BB1Copula-method (BB1Copula-class), 3
- dduCopula, numeric, BB6Copula-method (BB6Copula-class), 5
- dduCopula, numeric, BB7Copula-method (BB7Copula-class), 6
- dduCopula, numeric, BB8Copula-method (BB8Copula-class), 8
- dduCopula, numeric, joeBiCopula-method (joeBiCopula-class), 12
- dduCopula, numeric, r270BB1Copula-method (BB1Copula-class), 3
- dduCopula, numeric, r270BB6Copula-method (BB6Copula-class), 5
- dduCopula, numeric, r270BB7Copula-method (BB7Copula-class), 6
- dduCopula, numeric, r270BB8Copula-method (BB8Copula-class), 8
- dduCopula, numeric, r270ClaytonCopula-method (surClaytonCopula-class), 13
- dduCopula, numeric, r270GumbelCopula-method (surGumbelCopula-class), 14
- dduCopula, numeric, r270JoeBiCopula-method (joeBiCopula-class), 12
- dduCopula, numeric, r270TawnT1Copula-method (tawnT1Copula-class), 16
- dduCopula, numeric, r270TawnT2Copula-method (tawnT2Copula-class), 17
- dduCopula, numeric, r90BB1Copula-method (BB1Copula-class), 3
- dduCopula, numeric, r90BB6Copula-method (BB6Copula-class), 5
- dduCopula, numeric, r90BB7Copula-method (BB7Copula-class), 6
- dduCopula, numeric, r90BB8Copula-method (BB8Copula-class), 8
- dduCopula, numeric, r90ClaytonCopula-method (surClaytonCopula-class), 13
- dduCopula, numeric, r90GumbelCopula-method (surGumbelCopula-class), 14
- dduCopula, numeric, r90JoeBiCopula-method (joeBiCopula-class), 12
- dduCopula, numeric, r90TawnT1Copula-method (tawnT1Copula-class), 16
- dduCopula, numeric, r90TawnT2Copula-method (tawnT2Copula-class), 17
- dduCopula, numeric, surBB1Copula-method (BB1Copula-class), 3
- dduCopula, numeric, surBB6Copula-method (BB6Copula-class), 5
- dduCopula, numeric, surBB7Copula-method (BB7Copula-class), 6
- dduCopula, numeric, surBB8Copula-method (BB8Copula-class), 8

- (BB6Copula-class), 5
- ddvCopula, numeric, r270BB7Copula-method (BB7Copula-class), 6
- ddvCopula, numeric, r270BB8Copula-method (BB8Copula-class), 8
- ddvCopula, numeric, r270ClaytonCopula-method (surClaytonCopula-class), 13
- ddvCopula, numeric, r270GumbelCopula-method (surGumbelCopula-class), 14
- ddvCopula, numeric, r270JoeBiCopula-method (joeBiCopula-class), 12
- ddvCopula, numeric, r270TawnT1Copula-method (tawnT1Copula-class), 16
- ddvCopula, numeric, r270TawnT2Copula-method (tawnT2Copula-class), 17
- ddvCopula, numeric, r90BB1Copula-method (BB1Copula-class), 3
- ddvCopula, numeric, r90BB6Copula-method (BB6Copula-class), 5
- ddvCopula, numeric, r90BB7Copula-method (BB7Copula-class), 6
- ddvCopula, numeric, r90BB8Copula-method (BB8Copula-class), 8
- ddvCopula, numeric, r90ClaytonCopula-method (surClaytonCopula-class), 13
- ddvCopula, numeric, r90GumbelCopula-method (surGumbelCopula-class), 14
- ddvCopula, numeric, r90JoeBiCopula-method (joeBiCopula-class), 12
- ddvCopula, numeric, r90TawnT1Copula-method (tawnT1Copula-class), 16
- ddvCopula, numeric, r90TawnT2Copula-method (tawnT2Copula-class), 17
- ddvCopula, numeric, surBB1Copula-method (BB1Copula-class), 3
- ddvCopula, numeric, surBB6Copula-method (BB6Copula-class), 5
- ddvCopula, numeric, surBB7Copula-method (BB7Copula-class), 6
- ddvCopula, numeric, surBB8Copula-method (BB8Copula-class), 8
- ddvCopula, numeric, surClaytonCopula-method (surClaytonCopula-class), 13
- ddvCopula, numeric, surGumbelCopula-method (surGumbelCopula-class), 14
- ddvCopula, numeric, surJoeBiCopula-method (joeBiCopula-class), 12
- ddvCopula, numeric, surTawnT1Copula-method (tawnT1Copula-class), 16
- ddvCopula, numeric, surTawnT2Copula-method (tawnT2Copula-class), 17
- fitCopula, vineCopula-method (vineCopula-class), 19
- getKendallDistr, BB1Copula-method (BB1Copula-class), 3
- getKendallDistr, BB6Copula-method (BB6Copula-class), 5
- getKendallDistr, BB7Copula-method (BB7Copula-class), 6
- getKendallDistr, BB8Copula-method (BB8Copula-class), 8
- getKendallDistr, joeBiCopula-method (joeBiCopula-class), 12
- joeBiCopula, 11, 11
- joeBiCopula(), 12
- joeBiCopula-class, 12
- joeCopula, 3, 5, 7, 8, 11, 12
- joeCopula(), 3, 4, 6, 7
- kendallDistribution, BB1Copula-method (BB1Copula-class), 3
- kendallDistribution, BB6Copula-method (BB6Copula-class), 5
- kendallDistribution, BB7Copula-method (BB7Copula-class), 6
- kendallDistribution, BB8Copula-method (BB8Copula-class), 8
- kendallDistribution, joeBiCopula-method (joeBiCopula-class), 12
- pCopula(), 10
- r270BB1Copula, 2
- r270BB1Copula (BB1Copula), 2
- r270BB1Copula(), 3
- r270BB1Copula-class (BB1Copula-class), 3
- r270BB6Copula, 4
- r270BB6Copula (BB6Copula), 4
- r270BB6Copula(), 5
- r270BB6Copula-class (BB6Copula-class), 5
- r270BB7Copula, 6

- r270BB7Copula (BB7Copula), 5
- r270BB7Copula(), 6
- r270BB7Copula-class (BB7Copula-class), 6
- r270BB8Copula, 7
- r270BB8Copula (BB8Copula), 7
- r270BB8Copula(), 8
- r270BB8Copula-class (BB8Copula-class), 8
- r270ClaytonCopula, 13
- r270ClaytonCopula (surClaytonCopula), 12
- r270ClaytonCopula(), 13
- r270ClaytonCopula-class (surClaytonCopula-class), 13
- r270GumbelCopula, 14
- r270GumbelCopula (surGumbelCopula), 14
- r270GumbelCopula(), 14
- r270GumbelCopula-class (surGumbelCopula-class), 14
- r270JoeBiCopula, 11
- r270JoeBiCopula (joeBiCopula), 11
- r270JoeBiCopula(), 12
- r270JoeBiCopula-class (joeBiCopula-class), 12
- r270TawnT1Copula, 15
- r270TawnT1Copula (tawnT1Copula), 15
- r270TawnT1Copula(), 16
- r270TawnT1Copula-class (tawnT1Copula-class), 16
- r270TawnT2Copula, 17
- r270TawnT2Copula (tawnT2Copula), 16
- r270TawnT2Copula(), 17
- r270TawnT2Copula-class (tawnT2Copula-class), 17
- r90BB1Copula, 2
- r90BB1Copula (BB1Copula), 2
- r90BB1Copula(), 3
- r90BB1Copula-class (BB1Copula-class), 3
- r90BB6Copula, 4
- r90BB6Copula (BB6Copula), 4
- r90BB6Copula(), 5
- r90BB6Copula-class (BB6Copula-class), 5
- r90BB7Copula, 6
- r90BB7Copula (BB7Copula), 5
- r90BB7Copula(), 6
- r90BB7Copula-class (BB7Copula-class), 6
- r90BB8Copula, 7
- r90BB8Copula (BB8Copula), 7
- r90BB8Copula(), 8
- r90BB8Copula-class (BB8Copula-class), 8
- surClaytonCopula, 12, 13
- surClaytonCopula(), 13
- surClaytonCopula-class, 13
- surGumbelCopula, 14, 14
- surGumbelCopula(), 14
- surGumbelCopula-class, 14
- r90ClaytonCopula, 13
- r90ClaytonCopula (surClaytonCopula), 12
- r90ClaytonCopula(), 13
- r90ClaytonCopula-class (surClaytonCopula-class), 13
- r90GumbelCopula, 14
- r90GumbelCopula (surGumbelCopula), 14
- r90GumbelCopula(), 14
- r90GumbelCopula-class (surGumbelCopula-class), 14
- r90JoeBiCopula, 11
- r90JoeBiCopula (joeBiCopula), 11
- r90JoeBiCopula(), 12
- r90JoeBiCopula-class (joeBiCopula-class), 12
- r90TawnT1Copula, 15
- r90TawnT1Copula (tawnT1Copula), 15
- r90TawnT1Copula(), 16
- r90TawnT1Copula-class (tawnT1Copula-class), 16
- r90TawnT2Copula, 17
- r90TawnT2Copula (tawnT2Copula), 16
- r90TawnT2Copula(), 17
- r90TawnT2Copula-class (tawnT2Copula-class), 17
- RVineMatrix, 18, 19
- surBB1Copula, 2
- surBB1Copula (BB1Copula), 2
- surBB1Copula(), 3
- surBB1Copula-class (BB1Copula-class), 3
- surBB6Copula, 4
- surBB6Copula (BB6Copula), 4
- surBB6Copula(), 5
- surBB6Copula-class (BB6Copula-class), 5
- surBB7Copula, 6
- surBB7Copula (BB7Copula), 5
- surBB7Copula(), 6
- surBB7Copula-class (BB7Copula-class), 6
- surBB8Copula, 7
- surBB8Copula (BB8Copula), 7
- surBB8Copula(), 8
- surBB8Copula-class (BB8Copula-class), 8

surJoeBiCopula, [11](#)
surJoeBiCopula (joeBiCopula), [11](#)
surJoeBiCopula(), [12](#)
surJoeBiCopula-class
 (joeBiCopula-class), [12](#)
surTawnT1Copula, [15](#)
surTawnT1Copula (tawnT1Copula), [15](#)
surTawnT1Copula(), [16](#)
surTawnT1Copula-class
 (tawnT1Copula-class), [16](#)
surTawnT2Copula, [17](#)
surTawnT2Copula (tawnT2Copula), [16](#)
surTawnT2Copula(), [17](#)
surTawnT2Copula-class
 (tawnT2Copula-class), [17](#)

tawnT1Copula, [15](#), [15](#), [16](#)
tawnT1Copula(), [15](#), [16](#)
tawnT1Copula-class, [16](#)
tawnT2Copula, [16](#), [16](#), [17](#)
tawnT2Copula(), [17](#)
tawnT2Copula-class, [17](#)

vineCopula, [18](#), [18](#), [19](#)
vineCopula-class, [19](#)