

Package ‘aplot’

September 22, 2021

Title Decorate a 'ggplot' with Associated Information

Version 0.1.1

Description For many times, we are not just aligning plots as what 'cowplot' and 'patchwork' did. Users would like to align associated information that requires axes to be exactly matched in subplots, e.g. hierarchical clustering with a heatmap. This package provides utilities to align associated subplots to a main plot at different sides (left, right, top and bottom) with axes exactly matched.

Imports ggfun (>= 0.0.4), ggplot2, ggplotify, patchwork, magrittr, methods, utils, yulab.utils

Suggests ggtree

URL <https://github.com/YuLab-SMU/aplot>

License Artistic-2.0

Encoding UTF-8

RoxygenNote 7.1.1

NeedsCompilation no

Author Guangchuang Yu [aut, cre, cph]
(<https://orcid.org/0000-0002-6485-8781>)

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Repository CRAN

Date/Publication 2021-09-22 04:40:02 UTC

R topics documented:

insert_left	2
plot_list	3
xlim2	4
yrange	5
Index	6

insert_left	<i>plot-insertion</i>
-------------	-----------------------

Description

insert an associated plot to left, right, top and bottom of a main plot

Usage

```
insert_left(.data, plot, width = 1)
insert_right(.data, plot, width = 1)
insert_top(.data, plot, height = 1)
insert_bottom(.data, plot, height = 1)
```

Arguments

.data	an 'aplot' or 'gg' object
plot	a 'gg' plot to be inserted
width	relative width to the main plot
height	relative height to the main plot

Details

The first input serve as a main plot, and other plots can be progressively inserted to different sides on left, right, top and bottom.

Value

an 'aplot' object

Author(s)

Guangchuang Yu

Examples

```
library(ggplot2)
library(aplot)

p <- ggplot(mtcars, aes(mpg, disp)) + geom_point()
p2 <- ggplot(mtcars, aes(mpg)) +
  geom_density(fill='steelblue', alpha=.5) +
  ggtree::theme_dendrogram()
p3 <- ggplot(mtcars, aes(x=1, y=disp)) +
  geom_boxplot(fill='firebrick', alpha=.5) +
```

```
theme_void()
ap <- p %>%
  insert_top(p2, height=.3) %>%
  insert_right(p3, width=.1)
```

plot_list*plot a list of ggplot objects*

Description

plot a list of ggplot objects using patchwork, similar to ‘cowplot::plot_grid(plotlist)’

Usage

```
plot_list(
  ...,
  gglist = NULL,
  ncol = NULL,
  nrow = NULL,
  byrow = NULL,
  widths = NULL,
  heights = NULL,
  guides = NULL,
  labels = NULL,
  tag_levels = NULL,
  tag_size = 14,
  design = NULL
)
```

Arguments

...	list of plots to be arranged
gglist	(optional) list of plots
ncol	number of columns
nrow	number of rows
byrow	If "FALSE" the plots will be filled in in column-major order
widths	relative widths
heights	relative heights
guides	A string specifying how guides should be treated in the layout.
labels	manual specified labels to label plots
tag_levels	format to label plots, will be disable if 'labels' is not NULL
tag_size	size of tags
design	specification of the location of areas in the layout

Value

composite plot

Author(s)

Guangchuang Yu

xlim2

xlim2

Description

set axis limits (x or y) of a 'ggplot' object (left hand side of '+') based on the x ('xlim2') or y ('ylim2') limits of another 'ggplot' object (right hand side of '+'). This is useful for using 'cowplot' or 'patchwork' to align 'ggplot' objects.

Usage

```
xlim2(gg, limits = NULL)
```

```
ylim2(gg, limits = NULL)
```

Arguments

`gg` ggplot object

`limits` vector of limits. If NULL, determine from 'gg'.

Value

ggplot2 object with new limits

Author(s)

Guangchuang Yu

Examples

```
library(ggplot2)
library(aplot)
p1 <- ggplot(mtcars, aes(cyl)) + geom_bar()
p2 <- ggplot(subset(mtcars, cyl != 4), aes(cyl)) + geom_bar()
p2 + xlim2(p1)
```

yrange	<i>plot range of a ggplot object</i>
--------	--------------------------------------

Description

extract x or y ranges of a ggplot

Usage

yrange(gg)

xrange(gg)

Arguments

gg a ggplot object

Value

range of selected axis

Author(s)

Guangchuang Yu

Index

`insert_bottom (insert_left), 2`
`insert_left, 2`
`insert_right (insert_left), 2`
`insert_top (insert_left), 2`

`plot_list, 3`

`xlim2, 4`
`xrange (yrange), 5`

`ylim2 (xlim2), 4`
`yrange, 5`