

Package ‘incR’

May 8, 2026

Type Package

Title Analysis of Incubation Data

Version 2.1.1

Date 2025-09-11

Author Pablo Capilla-Lasheras [aut, cre]

Maintainer Pablo Capilla-Lasheras <pacapilla@gmail.com>

Description Suite of functions to study animal incubation.

At the core of incR

lies an algorithm that allows for the scoring of

incubation behaviour. Additionally, several functions

extract biologically relevant metrics of incubation such as off-bout number

and off-bout duration - for a review of avian incubation studies,

see Nests, Eggs, and Incubation: New ideas about avian reproduction (2015)

edited by D. Charles Deem-

ing and S. James Reynolds <[doi:10.1093/acprof:oso/9780198718666.001.0001](https://doi.org/10.1093/acprof:oso/9780198718666.001.0001)>.

License GPL-3

Depends R (>= 3.4.0), base, stats

Imports ggplot2, suncalc, lubridate, utils

Suggests codetools, knitr, rmarkdown

VignetteBuilder knitr

LazyData true

Encoding UTF-8

RoxygenNote 7.3.3

NeedsCompilation no

Repository CRAN

Date/Publication 2025-09-17 22:10:02 UTC

Contents

incR	2
incRact	3
incRatt	4
incRbouts	5
incRenv	6
incRenv_old	7
incRplot	9
incRprep	11
incRscan	12
incRscan_v2	14
incRscan_v3	15
incRt	17
incR_envdata	19
incR_procddata	20
incR_rawdata	21
Index	22

 incR

incR: Analysis of animal incubation

Description

This packages is formed by a suite of R functions that help the user to get useful biological information from raw time-series data of incubation temperatures. It is thought to be of interest for the study of uni-parental or intermittent incubating species.

Suggested workflow

Check the package vignettes to find a suggested workflow and calibrate the main function in incR.

incR functions

The current version of incR contains the following functions and three example data sets: [incRprep](#), [incRenv](#), [incRscan](#), [incRact](#), [incRatt](#) [incRbouts](#) and [incRt](#), along with three example data sets.

Author(s)

Maintainer: Pablo Capilla-Lasheras <pacapilla@gmail.com>

incRact	<i>Calculation of daily first incubation off-bout and last incubation on-bout</i>
---------	-----------------------------------------------------------------------------------

Description

Using a vector of incubation scores, *incRact* calculates onset of activity (first off-bout in the morning), and end of daily activity (last on-bout in the evening) per day. A column for dates, named "date" is needed in the data argument.

Usage

```
incRact(data, time_column, vector.incubation)
```

Arguments

data	data frame containing a numeric vector of 1's and 0's (incubation scores), where "1" means "incubating individual inside nest" and "0" means "incubating individual outside the nests". This vector, under the name of <code>incR_score</code> is provided by incRscan in the first object (<i>incRscan_data</i>) of the returned list. A column named "date" is needed to refer to daily calculations.
time_column	(character class) name of the column containing times.
vector.incubation	(character class) name of the vector containing incubation scores. incRscan produces this vector named "incR_score".

Value

a data frame containing fist off-bout and last on-bout per day in *data*.

Author(s)

Pablo Capilla-Lasheras

See Also

[incRprep](#) [incRscan](#)

Examples

```
## # loading example data
data(incR_procddata)
incRact (data=incR_procddata,
        time_column="time",
        vector.incubation="incR_score")
```

`incRatt`*Calculation of the percentage of daily time spent in nest*

Description

This function calculates percentage of day time spent inside nest based on the "inc.vector" variable produced by [incRscan](#) (or any other method). Current version do not discriminate day and night times.

Usage

```
incRatt(data, vector.incubation)
```

Arguments

`data` data frame containing a time-series vector of 1's and 0's, where "1" means "incubating individual inside nest" and "0" means "incubating individual outside nest". This vector, under the name of "inc.vector" is provided by [incRscan](#) in the first object of the returned list. A column named "date" is needed to refer to daily calculations.

`vector.incubation` name of the column (vector class) storing the information about the presence/absence of the incubating individual in the nest.

Details

The 'date' column must have a 'year-month-day' format for this function to run correctly.

Value

Daily percentage of time in nest, returned in a data frame with one day per row.

See Also

[incRprep](#) [incRscan](#) [incRact](#)

Examples

```
#! # loading example data
data(incR_procddata)
incRatt (data=incR_procddata,
        vector.incubation="incR_score")
```

`incRbouts`*Calculation of the number of daily on- and off-bouts*

Description

Calculation of number and duration of incubation on- and off-bouts.

Usage

```
incRbouts(data, vector.incubation, dec_time, temp, sampling.rate)
```

Arguments

<code>data</code>	data frame containing a time-series vector of 1's and 0's, where "1" means "incubating individual inside nest" and "0" means "incubating individual outside nest". This vector, under the name of "inc.vector", is provided by incRscan in the first object of the returned list. A column named "date" is needed to refer to daily calculations.
<code>vector.incubation</code>	name of the column (vector class) storing the information about the presence/absence of the incubating individual in the nest.
<code>dec_time</code>	(character class) name of the column with decimal time.
<code>temp</code>	(character class) name of the column with incubation temperatures.
<code>sampling.rate</code>	time difference between two consecutive recording points. Effectively, the rate at which data points were recorded (e.g. 1 data point per 50sec). The time units of the returned object will depend on the units of this argument.

Value

This function returns a list with two objects. The first object, named `total_bouts`, is a list of individual on- and off-bouts, giving information about their start time, duration, start nest temperature and final nest temperature. The second object, `day_bouts`, provides a summary of on- and off-bouts per day of observation. This second table shows number and mean duration of on- and off-bout per day. Mean times are shown in those time units you specify the argument *sampling.rate*.

Author(s)

Pablo Capilla-Lasheras

See Also

[incRprep](#) [incRscan](#) [incRact](#) [incRatt](#)

Examples

```
#' # loading example data
data(incR_procdata)
incRbouts (data=incR_procdata,
           vector.incubation="incR_score",
           dec_time="dec_time",
           temp="temperature",
           sampling.rate=240) # sampling rate in seconds.
```

incRenv

Matching environmental and nest temperatures

Description

This function takes a data frame with recordings of environmental temperature and another with nest temperatures and merges both by time. The user can do this work manually, however, [incRenv](#) is thought to automate data preparation (in combination with [incRprep](#)) to use [incRscan](#) after. Code to update and improve this function provided by Natalie van Dis.

Usage

```
incRenv(
  data.nest,
  data.env,
  env.temperature.name,
  env.date.name,
  env.date.format,
  env.timezone
)
```

Arguments

<code>data.nest</code>	data frame containing nest temperature recordings. It must have two compulsory columns 'date' and 'hour' displaying dates and the hour of each observation. These two columns are provided if the user uses incRprep before.
<code>data.env</code>	data frame containing environmental temperatures to be merged with nest temperature records. Please, provide date and time of each observation in one unique column as requested for incRprep .
<code>env.temperature.name</code>	name of the column containing temperature recordings in the <i>data.env</i> data frame.
<code>env.date.name</code>	name of the column containing date and time in the <i>data.env</i> data frame.
<code>env.date.format</code>	format of <i>env.date.name</i> . Similar to incRprep .
<code>env.timezone</code>	time zone of the environmental recordings. Similar to incRprep .

Details

This function is thought to be used after [incRprep](#) as it uses some of the additional variables created by [incRprep](#).

Value

The original *data.nest* with an additional column for hour-averaged environmental temperature. This new variable is thought to serve as *env_temp* in [incRscan](#).

Author(s)

Pablo Capilla-Lasheras

See Also

[incRprep](#) [incRscan](#)

Examples

```
data(incR_envdata) # environmental data
head (incR_envdata)

data(incR_rawdata) # loading nest data
head (incR_rawdata)

# the first step in to format the raw data using incRprep
new.data <- incRprep (data=incR_rawdata,
  date.name= "DATE",
  date.format= "%d/%m/%Y %H:%M",
  timezone="GMT",
  temperature.name="temperature")

# then use incRenv to merge environmental data
new.data2 <- incRenv (data.nest = new.data,
  data.env = incR_envdata,
  env.temperature.name = "env_temperature",
  env.date.name = "DATE",
  env.date.format = "%d/%m/%Y %H:%M",
  env.timezone = "GMT")

head (new.data2, 3)
```

Description

This function takes a data frame with recordings of environmental temperature and another with nest temperatures and merges both per unit of time. The user can do this work manually, however, [incRenv](#) is thought to automate data preparation (in combination with [incRprep](#)) to use [incRscan](#) after.

Usage

```
incRenv_old(  
  data.nest,  
  data.env,  
  env.temperature.name,  
  env.date.name,  
  env.date.format,  
  env.timezone  
)
```

Arguments

<code>data.nest</code>	data frame containing nest temperature recordings. It must have two compulsory columns 'date' and 'hour' displaying dates and the hour of each observation. These two columns are provided if the user uses incRprep before.
<code>data.env</code>	data frame containing environmental temperatures to be merged with nest temperature records. Please, provide date and time of each observation in one unique column as requested for incRprep .
<code>env.temperature.name</code>	name of the column containing temperature recordings in the <i>data.env</i> data frame.
<code>env.date.name</code>	name of the column containing date and time in the <i>data.env</i> data frame.
<code>env.date.format</code>	format of <i>env.date.name</i> . Similar to incRprep .
<code>env.timezone</code>	time zone of the environmental recordings. Similar to incRprep .

Details

This function is thought to be used after [incRprep](#) as it uses some of the additional variables created by [incRprep](#).

Value

The original *data.nest* with an additional column for hour-averaged environmental temperature. This new variable is thought to serve as *env_temp* in [incRscan](#).

Author(s)

Pablo Capilla-Lasheras

See Also

[incRprep](#) [incRscan](#)

Examples

```
data(incR_envdata) # environmental data
head (incR_envdata)

data(incR_rawdata) # loading nest data
head (incR_rawdata)

# the first step in to format the raw data using incRprep
new.data <- incRprep (data=incR_rawdata,
                     date.name= "DATE",
                     date.format= "%d/%m/%Y %H:%M",
                     timezone="GMT",
                     temperature.name="temperature")

# then use incRenv to merge environmental data
new.data2 <- incRenv_old (data.nest = new.data,
                        data.env = incR_envdata,
                        env.temperature.name = "env_temperature",
                        env.date.name = "DATE",
                        env.date.format = "%d/%m/%Y %H:%M",
                        env.timezone = "GMT")

head (new.data2, 3)
```

incRplot

Quick visualisation of incubation temperatures, on-bouts and off-bouts

Description

After [incRscan](#) has been used, [incRplot](#) provides a quick visualisation of the incubation temperature trace with coloured on- and off-bouts. Environmental temperatures can also be added to the plot

Usage

```
incRplot(
  data,
  time.var,
  day.var,
  inc.temperature.var,
  env.temperature.var = NULL,
  vector.incubation
)
```

Arguments

<code>data</code>	data table with incubation temperature data
<code>time.var</code>	Character string. Name of the variable with time of the day for temperature data. Please, have time in decimal hours. If <code>incRprep</code> has been previously used, "dec_time" can be used.
<code>day.var</code>	Character string. Name of the variable with date for temperature observation. No specific format is needed. If <code>incRprep</code> has been previously used, "date" can be used.
<code>inc.temperature.var</code>	Character string. Name of the variable with incubation temperatures.
<code>env.temperature.var</code>	Character string. Name of the variable with environmental temperatures. If no value is provided, a plot with no environmental temperatures is produced.
<code>vector.incubation</code>	name of the binary variable storing information about the presence/absence of the incubating individual in the nest. If <code>incRscan</code> has been used, "incR_score" can be used.

Value

Plot of incubation temperature, on-bouts and off-bouts with (optional) environmental temperatures. The plot is generated using `ggplot2::ggplot()`. The user can customised the appearance of the plot using tools within `ggplot2::ggplot()` (see example)

See Also

[incRscan](#)

Examples

```
# loading example data
data(incR_procddata)
my_plot <- incRplot(data = incR_procddata[complete.cases(incR_procddata$temperature),],
                  time.var = "dec_time",
                  day.var = "date",
                  inc.temperature.var = "temperature",
                  env.temperature.var = "env_temp",
                  vector.incubation = "incR_score")

# see your plot
my_plot

# add new labels (ggplot2 required)
my_plot + ggplot2::labs(x = "New X label", y = "New Y label")
```

`incRprep`*Data preparation for incubation analysis in incR*

Description

Preparing incubation time series for further analysis. This function takes a data file containing a temporal series of temperature recordings and adds some the extra variables needed to use further functions embedded in the incR package. It simply accommodates a raw data frame, reformatting date and time columns automatically.

Usage

```
incRprep(data, date.name, date.format, timezone, temperature.name)
```

Arguments

<code>data</code>	raw data from incubation time series. It must contain a column with date and time information for each observation (e.g. "2017-05-01 21:01"). The function is written to handle date and time concatenated in one unique column (see example below).
<code>date.name</code>	name of the date and time column
<code>date.format</code>	format for date and time column. It must be a character object as specified in the function <code>base::strptime()</code> . <code>incRprep</code> assumes that the date and time column contains date and time, If date and time are in different columns, please, concatenate them in one column before running the function.
<code>timezone</code>	time zone for time calculations. See <code>base::strptime()</code> documentation for more details.
<code>temperature.name</code>	name of the column storing temperature information.

Value

The original data frame with additional columns for:

1. `index`: a running number identifying every row in the data set.
2. `time`: in ' '
3. `hour`: in 'H' format.
4. `minute`: in 'M' format.
5. `second`: in 'S' format.
6. `date`: in 'Y-m-d' format.
7. `dec_time`: time in decimal hours (e.g. "22:30" becomes 22.5).
8. `temp1`: difference between the i th temperature value and the $i-1$ one.

Author(s)

Pablo Capilla-Lasheras

Examples

```
# loading example data
data(incR_rawdata)
new.data <- incRprep (data=incR_rawdata,
                     date.name= "DATE",
                     date.format= "%d/%m/%Y %H:%M",
                     timezone="GMT",
                     temperature.name="temperature")

head (new.data, 3)
```

incRscan

*Automated scoring of incubation***Description**

This is the core algorithm of incR and classifies time points as 1's or 0's depending on whether or not the incubating individual is considered to be on the eggs. The algorithm uses night variation to daily calibrate itself to temperature variation when the incubating individual is assumed to be on the eggs. A major assumption of this algorithm is that there is a period of time in which temperature can be assumed to be constant or representative of time windows of constant incubation. This time window is defined by two arguments: `lower.time` and `upper.time`. The function is optimised to work using a data frame produced by [incRprep](#).

Usage

```
incRscan(
  data,
  temp.name,
  lower.time,
  upper.time,
  sensitivity,
  temp.diff,
  temp.diff.threshold,
  maxNightVariation,
  env.temp
)
```

Arguments

`data` data frame for analysis. It must contained four columns named as follow: `date`, `temp1`, `dec_time` and `index`, where `temp1` is the difference between the *ith* and *i-1th* temperature recordings; `dec_time` is time in decimal hours; and `index` is a running number from 1 to *N*, *N* being the total number of observations. [incRprep](#) returns a data frame with these variables and the correct names, ready to be passed through `incRscan`.

<code>temp.name</code>	(character object) name of the column containing temperature data in <code>data</code> .
<code>lower.time</code>	lower limit of time window for calibration (numeric).
<code>upper.time</code>	upper limit of time window for calibration (numeric).
<code>sensitivity</code>	ratio of reduction in temperature threshold. When nest temperature does not drop close to environmental temperatures, this value can be kept to 1. If nest temperature follows environmental temperature at any point, then adjustment of this value may be required to detect short on/off-bouts at lower nest temperatures (see details).
<code>temp.diff</code>	deprecated. Use <code>temp.diff.threshold</code> .
<code>temp.diff.threshold</code>	threshold for temperature difference between <code>env.temp</code> and an observation which triggers the sensitivity parameter.
<code>maxNightVariation</code>	maximum temperature variation between two consecutive points within the calibrating window that is considered normal of this period. If this variation value is surpassed, the calibrating window is discarded and a previous night is used for calibration.
<code>env.temp</code>	name of a column containing environmental temperatures.

Value

The function returns a list with two objects. The first object, named `incRscan_data`, is the original data frame with an extra column named `'incR_score'`. This variable is formed by 1's and 0's, representing whether the incubating individual is inside (1) or outside the nest (0).

The second object, named `incRscan_threshold`, is a data frame with one day per row. Four columns tell the user the thresholds employed to calculate the `'incR_score'` column. A fifth column accounts for the ratio between temperature variation in the calibrating window and the variation in temperature between 11am and 3pm for each day morning. The lower this value the more clear the pattern between night and day variation and, therefore, stronger the signal in the data. This value may serve the user as an indication of the signal / noise ratio in the analysed data set.

Details

For further details about the calculation performed by `incRscan`, consult the package vignettes and the associated publications.

Author(s)

Pablo Capilla-Lasheras

See Also

[incRprep](#) [incRenv](#)

Examples

```
# incR_procddata is a dataframe processed by incRprep and incRenv.
# it contains suitable information to run incRscan
data(incR_procddata)

incubation.analysis <- incRscan (data=incR_procddata,
                                temp.name="temperature",
                                lower.time=22,
                                upper.time=3,
                                sensitivity=0.15,
                                temp.diff.threshold=5,
                                maxNightVariation=2,
                                env.temp="env_temp")

inc.data <- incubation.analysis[[1]]
inc.thresholds <- incubation.analysis[[2]]
```

 incRscan_v2

Scoring of incubation based on a fixed temperature threshold

Description

Modified version of incRscan. Data points are assigned to incubation on/off-bout based on a fixed temperature threshold for the difference in nest temperature expected when an off-bout starts.

Usage

```
incRscan_v2(
  data,
  temp.name,
  sensitivity,
  temperature_threshold,
  temp.diff.threshold,
  env.temp
)
```

Arguments

data	data frame for analysis. It must contained four columns named as follow: date, temp1, dec_time and index, where temp1 is the difference between the <i>i</i> th and <i>i-1</i> th temperature recordings; dec_time is time in decimal hours; and index is a running number from 1 to <i>N</i> , <i>N</i> being the total number of observations. incRprep returns a data frame with these variables and the correct names, ready to be passed through incRscan.
temp.name	(character object) name of the column containing temperature data in data.
sensitivity	percentage of reduction in temperature threshold. When nest temperature does not drop close to environmental temperature, this value can be kept to 1. If nest temperature follows environmental temperature at any point, then, adjustment of

	this value may be required to detect short on/off-bouts at lower nest temperatures (see details).
temperature_threshold	Maximum temperature difference between two consecutive nest temperature recordings allowed for an on-bout. When the difference in nest temperature between two consecutive recordings is higher than this value, an off-bout is detected.
temp.diff.threshold	threshold for temperature difference between env.temp and an observation which triggers application of the sensitivity parameter.
env.temp	name of a column containing environmental temperatures.

Value

The function returns the original data frame with a new column named 'incR_score'. This new variable is formed by 1's and 0's, representing whether the incubating individual is inside ("1") or outside the nest ("0"). # @section Details: See [incRenv](#) for more details

Author(s)

Pablo Capilla-Lasheras

See Also

[incRprep](#) [incRenv](#) [incRscan](#)

Examples

```
# incR_procddata is a data frame processed by incRprep and incRenv.
# It contains suitable information to run incRscan
data(incR_procddata)

incubation.analysis <- incRscan_v2 (data=incR_procddata,
                                   temp.name="temperature",
                                   temperature_threshold = 0.75,
                                   sensitivity=0.15,
                                   temp.diff.threshold=5,
                                   env.temp="env_temp")
```

incRscan_v3

Scoring of incubation based on combination of dynamic (as in [incRscan](#)) and fixed temperature thresholds (as in [incRscan_v2](#))

Description

Modified version of [incRscan](#). It combines the assignment of incubation on/off-bout implemented in [incRscan](#) and [incRscan_v2](#).

Usage

```
incRscan_v3(
  data,
  temp.name,
  temperature_threshold,
  lower.time,
  upper.time,
  sensitivity,
  temp.diff,
  temp.diff.threshold,
  maxNightVariation,
  env.temp
)
```

Arguments

<code>data</code>	data frame for analysis. It must contained four columns named as follow: <code>date</code> , <code>temp1</code> , <code>dec_time</code> and <code>index</code> , where <code>temp1</code> is the difference between the <i>i</i> th and <i>i-1</i> th temperature recordings; <code>dec_time</code> is time in decimal hours; and <code>index</code> is a running number from 1 to <i>N</i> , <i>N</i> being the total number of observations. incRprep returns a data frame with these variables and the correct names, ready to be passed through <code>incRscan</code> .
<code>temp.name</code>	(character object) name of the column containing temperature data in <code>data</code> .
<code>temperature_threshold</code>	Maximum temperature difference between two consecutive nest temperature recordings allowed for an on-bout. When the difference in nest temperature between two consecutive recordings is higher than this value, an off-bout is detected. Only applies for days when a calibration window is not available or <code>temp.diff.threshold</code> is exceeded.
<code>lower.time</code>	lower limit of time window for calibration (numeric).
<code>upper.time</code>	upper limit of time window for calibration (numeric).
<code>sensitivity</code>	percentage of reduction in temperature threshold. When nest temperature does not drop close to environmental temperature, this value can be kept to 1. If nest temperature follows environmental temperature at any point, then, adjustment of this value may be required to detect short on/off-bouts at lower nest temperatures (see details).
<code>temp.diff</code>	deprecated. Use <code>temp.diff.threshold</code> .
<code>temp.diff.threshold</code>	threshold for temperature difference between <code>env.temp</code> and an observation which triggers application of the sensitivity parameter.
<code>maxNightVariation</code>	maximum temperature variation between two consecutive points within the calibrating window that is considered normal of this period. If this variation value is surpassed, the calibrating window is discarded and a previous night is used for calibration.
<code>env.temp</code>	name of a column containing environmental temperatures.

Value

The function returns the original data frame with a new column named 'incR_score'. This new variable is formed by 1's and 0's, representing whether the incubating individual is inside ("1") or outside the nest ("0"). #' @section Details: See [incRenv](#) for more details

Author(s)

Pablo Capilla-Lasheras

See Also

[incRscan](#) [incRscan_v2](#)

incRt	<i>Calculation of temperature average and variance for customised time windows</i>
-------	------------------------------------------------------------------------------------

Description

Calculation of temperature average and variation between two customised time periods per day. Time windows can be defined by the user using the `limits` argument, defined by bird activity time (using the `activity.times` parameter) or set according to twilight times if coordinates are provided (`coord`).

Usage

```
incRt(
  data,
  temp.name,
  limits = NULL,
  coord = NULL,
  activity.times = FALSE,
  civil.twilight = FALSE,
  time.zone = NULL,
  ...
)
```

Arguments

<code>data</code>	data frame containing a time-series vector of 1's and 0's (incubation scores), where "1" means "incubating individual inside nest" and "0" means "incubating individual outside the nests". This vector, under the name of <code>incR_score</code> , is provided by incRscan in the first object of the returned list. A column named "date" is needed to refer to daily calculations.
<code>temp.name</code>	(character object) name of the column containing temperature data in <code>data</code> .

limits	vector of length 2 giving the time limits for calculations. For example, 'c(6,20)' would calculate temperature averages and variances for two time periods, from 6 to 20 and from 20 to 6 of the next day. 'civil.twilight' and 'activity.times' must be FALSE to allow the use of 'limits'.
coor	coordinates for the location where temperature was recorded, formatted as decimal degrees N/S, decimal degrees E/W. When 'civil.twilight' is TRUE, 'coor' allows the user to define sunrise and sunset times based on the suncalc::getSunlightTimes() function (in suncalc package).
activity.times	TRUE or FALSE. Set as TRUE when time periods for calculation are defined by incRact . Data must contain a column named 'incR_score' for the use of incRact .
civil.twilight	TRUE or FALSE. Set as TRUE when time periods for calculation are to be defined by civil twilight times - calculated using suncalc::getSunlightTimes() . If 'civil.twilight = TRUE', 'coor' and 'time.zone' need to be specified.
time.zone	time zone for suncalc::getSunlightTimes() dawn and dusk calculations.
...	use parameters in incRact if <i>activity.times</i> = TRUE.

Value

a data frame containing temperature means and variance for the defined time window.

Author(s)

Pablo Capilla-Lasheras

See Also

[incRprep](#) [incRscan](#) [incRact](#) [suncalc::getSunlightTimes\(\)](#)

Examples

```
# loading example data
data(incR_procddata)

# calculation based on chosen times from 6am to 7pm and 7pm to 6am
incRt (data=incR_procddata,
      temp.name="temperature",
      limits=c(6,19),
      coor=NULL,
      civil.twilight=FALSE,
      activity.times=FALSE,
      time.zone=NULL)

# calculation based on activity times
incRt (data=incR_procddata,
      temp.name="temperature",
      limits=NULL,
      coor=NULL,
      civil.twilight=FALSE,
```

```

        activity.times=TRUE,
        time.zone=NULL,
        time_column="time",          # extra argument needed for incRact
        vector.incubation="incR_score") # extra argument needed for incRact

# calculation based on civil twilight
incRt (data=incR_procddata,
       temp.name="temperature",
       limits=NULL,
       coor=c(42,0.89),
       civil.twilight=TRUE,
       activity.times=FALSE,
       time.zone="GMT")

```

incR_envdata	<i>An example data set of environmental temperatures to test the use of link{incRenv}.</i>
--------------	--------------------------------------------------------------------------------------------

Description

A dataset containing environmental temperatures for the study area where the data in [incR_rawdata](#) were collected. This raw data set was produced by an iButton device (Maxim Integrated).

Usage

```
incR_envdata
```

Format

A data frame with 1570 rows and two variables, representing two days of environmental temperature recordings at two different locations in one study site.

DATE a date-time column. Both elements, date and time, are concatenated in one column.

env_temperature environmental temperature recordings.

Details

use this data set to try out `link{incRenv}` after the very first application of `incRprep` using `incR_rawdata`.

incR_procdata	<i>An example of incubation temperature time-series after the use of incRprep and incRenv.</i>
---------------	--------------------------------------------------------------------------------------------------------------------------------

Description

A dataset containing temperatures, time and date for a blue tit nest. It also includes variables added by [incRprep](#) and [incRenv](#). The raw data set [incR_rawdata](#) was produced by an iButton device (Maxim) and represents raw data to start the analysis of incubation behaviour

Usage

```
incR_procdata
```

Format

A data frame with 954 rows and 11 variables, representing two days of nest temperatures.

DATE a date-time column. Both elements, date and time, are concatenated in one column.

temperature nest temperature recordings.

index running number from first to last observation.

time

hour

minute

second

date

dec_time time in decimal hours.

temp1 difference between the *ith* and the *ith-1* nest temperature recording.

env_temp environmental temperature, calculated per as hour average using [incRenv](#).

incR_score Incubation scores (0/1) as calculated by [incRscan](#)

Details

see [incRprep](#) and [incRenv](#) for more details on the variables of this data set and how it was produced.

`incR_rawdata`*An example of incubation temperature time-series*

Description

A dataset containing date, time and temperatures for a blue tit nest. This data set was produced by an iButton device (Maxim Integrated) and represents raw data to start the analysis of incubation behaviour.

Usage`incR_rawdata`**Format**

A data frame with 954 rows and 2 variables, representing three days of nest temperatures.

DATE a date-time column. Both elements, date and time, are concatenated in one column

temperature temperature recordings in Celsius

Index

* datasets

- incR_envdata, [19](#)
- incR_procddata, [20](#)
- incR_rawdata, [21](#)

base::strptime(), [11](#)

ggplot2::ggplot(), [10](#)

incR, [2](#)

incR-package (incR), [2](#)

incR_envdata, [19](#)

incR_procddata, [20](#)

incR_rawdata, [19](#), [20](#), [21](#)

incRact, [2](#), [3](#), [4](#), [5](#), [18](#)

incRatt, [2](#), [4](#), [5](#)

incRbouts, [2](#), [5](#)

incRenv, [2](#), [6](#), [6](#), [8](#), [13](#), [15](#), [17](#), [20](#)

incRenv_old, [7](#)

incRplot, [9](#), [9](#)

incRprep, [2–11](#), [11](#), [12–16](#), [18–20](#)

incRscan, [2–10](#), [12](#), [13](#), [15](#), [17](#), [18](#), [20](#)

incRscan_v2, [14](#), [15](#), [17](#)

incRscan_v3, [15](#)

incRt, [2](#), [17](#)

suncalc::getSunlightTimes(), [18](#)