

# Package ‘rdwd’

April 15, 2023

**Title** Select and Download Climate Data from 'DWD' (German Weather Service)

**Version** 1.7.1

**Date** 2023-04-15

**Depends** R(>= 2.10)

**Imports** berryFunctions (>= 1.21.11), pbapply

**Suggests** RCurl, leaflet, knitr, rmarkdown, testthat, roxygen2, devtools, remotes, bit64, data.table, OSMscale, raster, R.utils, ncdf4, readr, dwdradar, XML, sp, rgdal, terra, stars, shiny, gsheets

**Author** Berry Boessenkool

**Maintainer** Berry Boessenkool <berry-b@gmx.de>

**Description** Handle climate data from the 'DWD' ('Deutscher Wetterdienst', see <[https://www.dwd.de/EN/climate\\_environment/cdc/cdc\\_node\\_en.html](https://www.dwd.de/EN/climate_environment/cdc/cdc_node_en.html)> for more information). Choose observational time series from meteorological stations with 'selectDWD()'. Find raster data from radar and interpolation according to <<https://bookdown.org/brry/rdwd/raster-data.html>>. Download (multiple) data sets with progress bars and no re-downloads through 'dataDWD()'. Read both tabular observational data and binary gridded datasets with 'readDWD()'.

**License** GPL (>= 2)

**Encoding** UTF-8

**URL** <https://github.com/brry/rdwd>

**RoxygenNote** 7.2.3

**BugReports** <https://github.com/brry/rdwd/issues>

**VignetteBuilder** knitr

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2023-04-15 07:40:02 UTC

**R topics documented:**

addBorders	3
app	4
checkIndex	4
checkSuggestedPackage	5
createIndex	6
dataDWD	8
DEU	10
dirDWD	11
dwdbase	12
dwdparams	13
EUR	13
fileType	14
findID	16
index	17
indexFTP	18
lldist	21
locdir	22
metaInfo	23
nearbyStations	23
newColumnNames	25
plotDWD	26
plotRadar	27
projectRasterDWD	29
rdwd	31
rdwdquiet	32
readDWD	32
readDWD.asc	34
readDWD.binary	36
readDWD.data	37
readDWD.deriv	39
readDWD.grib2	40
readDWD.meta	41
readDWD.multia	42
readDWD.nc	44
readDWD.pdf	45
readDWD.radar	47
readDWD.raster	48
readDWD.rklim	49
readDWD.stand	51
readMeta	53
readVars	54
rowDisplay	55
runLocalTests	55
selectDWD	56
updateRdwd	59
validFileTypes	60

---

addBorders	<i>add country and Bundesland borders to a map</i>
------------	--

---

### Description

add country and Bundesland borders to a map

### Usage

```
addBorders(de = "grey80", eu = "black", add = TRUE, ...)
```

### Arguments

de	Color for Bundeslaender line ( <a href="#">DEU</a> ). NA to suppress. DEFAULT: "grey80"
eu	Color for countries line ( <a href="#">EUR</a> ). NA to suppress. DEFAULT: "black"
add	Logical: add to existing plot? DEFAULT: TRUE
...	Further arguments passed to <a href="#">raster::plot()</a>

### Value

invisible list with DEU and EUR

### Author(s)

Berry Boessenkool, <[berry-b@gmx.de](mailto:berry-b@gmx.de)>, Aug 2019

### See Also

[plotRadar](#), [DEU](#), [EUR](#), [website raster chapter](#)

### Examples

```
if(requireNamespace("raster", quietly=TRUE)){
  plot(1, xlim=c(2,16), ylim=c(47,55))
  addBorders()
  plot(1, xlim=c(2,16), ylim=c(47,55))
  addBorders(de="orange", eu=NA)
}
```

---

app	<i>Launch interactive weather analysis app</i>
-----	--

---

### Description

Launch interactive analysis of weather period comparison for different RDWD stations. The R session is blocked during usage, close the app to re-enable console usage.

### Usage

```
app(...)
```

### Arguments

... Arguments passed to [shiny::runApp\(\)](#)

### Author(s)

Berry Boessenkool, <berry-b@gmx.de>, July 2018 + April 2023

### See Also

[shiny::runApp\(\)](#), [rdwd](#)

### Examples

```
# app()
```

---

checkIndex	<i>check indexes</i>
------------	----------------------

---

### Description

check indexes. Mainly for internal usage in [createIndex\(\)](#). Not exported, so call it as `rdwd:::checkIndex()` if you want to run tests yourself. Further test suggestions are welcome!

### Usage

```
checkIndex(  
  findex = NULL,  
  mindex = NULL,  
  gindex = NULL,  
  excludefp = TRUE,  
  fast = FALSE,  
  warn = !quiet,  
  logfile = berryFunctions::packagePath(file = "misc/ExampleTests/warnings.txt"),  
  quiet = rdwdquiet()  
)
```

**Arguments**

findex	<a href="#">fileIndex</a> . DEFAULT: NULL
mindex	<a href="#">metaIndex</a> . DEFAULT: NULL
gindex	<a href="#">geoIndex</a> . DEFAULT: NULL
excludefp	Exclude false positives from <a href="#">geoIndex</a> coordinate check results? DEFAULT: TRUE
fast	Exclude the 3-minute location per ID check? DEFAULT: FALSE
warn	Warn about issues? DEFAULT: !quiet (TRUE)
logfile	File to copy log to, appended to existing content. NULL to suppress. DEFAULT: "misc/ExampleTests/warnings.txt"
quiet	Logical: Suppress progress messages? DEFAULT: FALSE through <a href="#">rdwdquiet()</a>

**Value**

Charstring with issues (if any) to be printed with [cat\(\)](#).

**Author(s)**

Berry Boessenkool, <[berry-b@gmx.de](mailto:berry-b@gmx.de)>, May 2019

**See Also**

[createIndex](#)

**Examples**

```
data(fileIndex) ; data(metaIndex) ; data(geoIndex)
# ci <- rdwd:::checkIndex(findex=fileIndex, mindex=metaIndex, gindex=geoIndex)
# cat(ci)
```

---

checkSuggestedPackage *check suggested package for availability*

---

**Description**

check suggested package for availability, yielding an instructive error message if not

**Usage**

```
checkSuggestedPackage(package, functionname)
```

**Arguments**

package	Charstring: package to be checked for loadability
functionname	Charstring: function name to be used in the message

**Value**

invisible success logical value from [requireNamespace\(\)](#)

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Aug 2019

**See Also**

[requireNamespace\(\)](#)

---

createIndex

*Create file and meta index of the DWD CDC FTP Server*

---

**Description**

This is mainly an internal function. Create data.frames out of the vector index returned by [indexFTP\(\)](#). For [fileIndex](#) (the first output element) createIndex tries to obtain res, var, per, file, id, start and end from the paths. If meta=TRUE, [metaIndex](#) and [geoIndex](#) are also created. They combine all Beschreibung files into a single data.frame.

If you create your own index as suggested in selectDWD (argument findex), you can read the produced file as shown in the example section.

**Usage**

```
createIndex(
  paths,
  base = dwdbase,
  dir = "DWDdata",
  fname = "fileIndex.txt",
  meta = FALSE,
  metadir = "meta",
  mname = "metaIndex.txt",
  gname = "geoIndex.txt",
  overwrite = FALSE,
  checkwarn = TRUE,
  checklog = tempfile(),
  quiet = rdwdquiet(),
  ...
)
```

**Arguments**

paths	Char: vector of DWD paths returned by <a href="#">indexFTP()</a> called with the same base value as this function
base	Main directory of DWD ftp server, defaulting to observed climatic records. DEFAULT: <a href="#">dwdbase</a>

dir	Char: writeable directory name where to save the main output(s). Created if not existent. DEFAULT: "DWDdata" at current <code>getwd()</code>
fname	Char: Name of file in dir in which to write <code>fileIndex</code> . Use <code>fname=""</code> to suppress writing. DEFAULT: "fileIndex.txt"
meta	Logical: should metaIndex also be created from fileIndex? Uses <code>dataDWD()</code> to download files if not present. DEFAULT: FALSE
metadir	Char: Directory (subfolder of dir) where original description files are downloaded to if meta=TRUE. Passed to <code>dataDWD()</code> . "" to write in dir. DEFAULT: "meta"
mname	Char: Name of file in dir (not metadir) in which to write <code>metaIndex</code> . Use <code>mname=""</code> to suppress writing. DEFAULT: "metaIndex.txt"
gname	Filename for <code>geoIndex</code> . DEFAULT: "geoIndex.txt"
overwrite	Logical: Overwrite existing fname / mname / gname files? If not, "_n" is added to the filenames, see <code>berryFunctions::newFilename()</code> . DEFAULT: FALSE
checkwarn	Logical: warn about <code>checkIndex()</code> issues? DEFAULT: TRUE
checklog	Logfile for <code>checkIndex()</code> . DEFAULT: <code>tempfile()</code>
quiet	Logical: Suppress messages about progress and filenames? DEFAULT: FALSE through <code>rdwdquiet()</code>
...	Further arguments passed to <code>dataDWD()</code> for the meta part.

### Value

invisible data.frame (or if meta=TRUE, list with two data.frames) with a number of columns inferred from the paths. Each is also written to disc.

### Author(s)

Berry Boessenkool, <berry-b@gmx.de>, Oct-Nov 2016, June 2017

### See Also

[indexFTP\(\)](#), [updateIndexes\(\)](#), [index](#), [selectDWD\(\)](#), [website index chapter](#)

### Examples

```
## Not run: # Not tested with R CMD check because of file writing
link <- "daily/kl/historical/tageswerte_KL_00699_19490101_19580630_hist.zip"
ind <- createIndex(link, dir=tempdir())
ind
# res var      per id      start      end ismeta
# daily kl historical 699 1949-01-01 1958-06-30 FALSE
link2 <- "daily/kl/historical/KL_Tageswerte_Beschreibung_Stationen.txt"
link3 <- "daily/kl/recent/KL_Tageswerte_Beschreibung_Stationen.txt"
ind2 <- createIndex(c(link,link2,link3), dir=tempdir(), meta=TRUE, checkwarn=FALSE)
lapply(ind2, head)
link4 <- "1_minute/precipitation/meta_data/Meta_Daten_ein_min_rr_00755.zip"
ind <- createIndex(link4, dir=tempdir())
```

```
ind
## End(Not run)
```

---

 dataDWD

---

*Download data from the DWD CDC FTP Server*


---

## Description

Get climate data from the German Weather Service (DWD) FTP-server. The desired dataset is downloaded into `dir`. If `read=TRUE`, it is also read and processed. `dataDWD` handles vectors of URLs, displays progress bars (if the package `pbapply` is available) and by default does not re-download data already in `dir` (but see argument `force` to update files). To solve "errors in download.file: cannot open URL", see <https://bookdown.org/brry/rdwd/fileindex.html>.

## Usage

```
dataDWD(
  url,
  base = dwdbase,
  joinbf = FALSE,
  dir = locdir(),
  force = FALSE,
  overwrite = !isFALSE(force),
  read = TRUE,
  dbin = TRUE,
  method = getOption("download.file.method"),
  dfargs = NULL,
  sleep = 0,
  progbar = !quiet,
  browse = FALSE,
  ntrunc = 2,
  file = NULL,
  quiet = rdwdquiet(),
  ...
)
```

## Arguments

<code>url</code>	Char (vector): complete file URL(s) (including base and filename.zip) as returned by <code>selectDWD()</code> . Can be a vector with several FTP URLs.
<code>base</code>	Single char: base URL that will be removed from output file names. DEFAULT: <code>dwdbase</code>



joinbf	Logical: paste base and file url together? Needed mostly for data at <a href="#">gridbase</a> . DEFAULT: FALSE (selectDWD returns complete URLs already)
dir	Char: Writeable directory name where to save the downloaded file. Created if not existent. DEFAULT: <a href="#">locdir()</a>
force	Logical (vector): always download, even if the file already exists in dir? Use NA to force re-downloading files older than 24 hours. Use a numerical value to force after that amount of hours. Use something like <code>c(Inf, 24)</code> or <code>force=c(24*365, 6)</code> , for <code>per="hr"</code> . Note: if force is not FALSE, the overwrite default is TRUE. DEFAULT: FALSE
overwrite	Logical (vector): if force=TRUE, overwrite the existing file rather than append "_1"/"_2" etc to the filename? DEFAULT: <code>!isFALSE(force)</code> , i.e. true when force is specified.
read	Logical: read the file(s) with <a href="#">readDWD()</a> ? If FALSE, only download is performed and the filename(s) returned. DEFAULT: TRUE
dbin	Logical: Download binary file, i.e. add mode="wb" to the <a href="#">download.file()</a> call? See <a href="#">Website</a> for details. DEFAULT: TRUE
method	<a href="#">download.file</a> method. Introduced in version 1.5.25 (2022-05-12) as triggered by <a href="https://github.com/brry/rdwd/issues/34">https://github.com/brry/rdwd/issues/34</a> . DEFAULT: <code>getOption("download.file.method")</code>
dfargs	Named list of additional arguments passed to <a href="#">download.file()</a> Note that mode="wb" is already passed if dbin=TRUE
sleep	Number. If not 0, a random number of seconds between 0 and sleep is passed to <a href="#">Sys.sleep()</a> after each download to avoid getting kicked off the FTP-Server, see note in <a href="#">indexFTP()</a> . DEFAULT: 0
progbar	Logical: present a progress bar with estimated remaining time? If missing and <code>length(file)==1</code> , progbar is internally set to FALSE. Only works if the R package <code>pbapply</code> is available. DEFAULT: TRUE (!quiet)
browse	Logical: open repository via <a href="#">browseURL()</a> and return URL folder path? If TRUE, no data is downloaded. If file has several values, only unique folders will be opened. DEFAULT: FALSE
ntrunc	Single integer: number of filenames printed in messages before they get truncated with message "(and xx more)". DEFAULT: 2
file	Deprecated since rdwd version 1.3.34, 2020-07-28.
quiet	Logical: suppress message about directory / filenames? DEFAULT: FALSE through <a href="#">rdwdquiet()</a>
...	Further arguments passed to <a href="#">readDWD()</a> , like <code>fread</code> , <code>varnames</code> , <code>hr</code> , etc.

### Value

Presuming downloading and processing were successful: if `read=TRUE`, the desired dataset (as returned by [readDWD\(\)](#)), otherwise the filename as saved on disc (may have "\_n" appended in name, see [newFilename\(\)](#)).

If `length(file)>1`, the output is a list of outputs / vector of filenames.

The output is always invisible.

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Jun-Oct 2016

**See Also**

[selectDWD\(\). readDWD\(\), download.file\(\)](#).

<https://bookdown.org/brry/rdwd>

Helpful for plotting: [berryFunctions::monthAxis\(\)](#), see also [berryFunctions::climateGraph\(\)](#)

**Examples**

```
## Not run: ## requires internet connection
# find FTP files for a given station name and file path:
link <- selectDWD("Fuerstenzell", res="hourly", var="wind", per="recent")
# download file:
fname <- dataDWD(link, dir=locdir(), read=FALSE) ; fname
# dir="DWDdata" is the default directory to store files
# unless force=TRUE, already obtained files will not be downloaded again

# read and plot file:
wind <- readDWD(fname, varnames=TRUE) ; head(wind)
metafiles <- readMeta(fname) ; str(metafiles, max.level=1)
column_names <- readVars(fname) ; head(column_names)

plot(wind$MESS_DATUM, wind$F, main="DWD hourly wind Fuerstenzell", col="blue",
     xaxt="n", las=1, type="l", xlab="Date", ylab="Hourly Wind speed [m/s]")
berryFunctions::monthAxis(1)

# current and historical files, keep historical in the overlap time period:
link <- selectDWD("Potsdam", res="daily", var="kl", per="hr"); link
potsdam <- dataDWD(link, dir=locdir(), hr=4)
plot(TMK~MESS_DATUM, data=tail(potsdam,1500), type="l")

# With many files (>>50), use sleep to avoid getting kicked off the FTP server
#links <- selectDWD(res="daily", var="solar")
#sol <- dataDWD(links, sleep=20) # random waiting time after download (0 to 20 secs)

# Real life examples can be found in the use cases section of the vignette:
# browseURL("https://bookdown.org/brry/rdwd")

## End(Not run)
```

**Description**

Map of German states (Bundeslaender) from GADM through the raster package

**Format**

Formal class 'SpatialPolygons' (package "sp") with 4 slots

**Details**

Use directly with:

```
load(system.file("extdata/DEU.rda", package="rdwd"))
```

Obtained with the code:

```
url <- "https://gisco-services.ec.europa.eu/distribution/v2/nuts/shp/NUTS_RG_03M_2021_4326_LEVEL_1.shp"
tf <- tempfile(fileext=".zip")
download.file(url, tf) # 0.9 MB
unzip(tf, exdir="misc/vign") ; rm(url, tf)

DEU <- raster::shapefile("misc/vign/NUTS_RG_03M_2021_4326_LEVEL_1.shp")
DEU <- DEU[DEU$CNTR_CODE=="DE", "NUTS_NAME"]
raster::plot(DEU) ; axis(1, line=-1) ; axis(2, line=-1)

save(DEU, file="inst/extdata/DEU.rda", version=2)
tools::resaveRdaFiles("inst/extdata/DEU.rda", version=2)
```

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, May 2018

**See Also**

[addBorders](#), [EUR](#)

---

dirDWD

*directory management for rdwd*

---

**Description**

Manage directories with useful messages in the rdwd package.

**Usage**

```
dirDWD(dir = "DWDdata", quiet = rdwdquiet())
```

**Arguments**

dir	Char for dirDWD: writeable directory name. Created if not existent. DEFAULT: "DWDdata" at current <a href="#">getwd()</a>
quiet	Logical: Suppress messages about creating dir? DEFAULT: FALSE through <a href="#">rdwdquiet()</a>

**Value**

dirDWD invisibly returns the prior working directory as per [setwd\(\)](#).

**Author(s)**

Berry Boessenkool, <[berry-b@gmx.de](mailto:berry-b@gmx.de)>, Oct 2016

**See Also**

[dataDWD\(\)](#)

**Examples**

```
# see source code of dataDWD and metaDWD
```

---

dwdbase	<i>DWD FTP Server base URL</i>
---------	--------------------------------

---

**Description**

base URLs to the DWD FTP Server

dwdbase: observed climatic records at ftp:// variant of [https://opendata.dwd.de/climate\\_environment/CDC/observations\\_germany/climate/](https://opendata.dwd.de/climate_environment/CDC/observations_germany/climate/)  
See [overview of available datasets](#) and [usage suggestions](#).

gridbase: spatially interpolated gridded data at ftp:// variant of [https://opendata.dwd.de/climate\\_environment/CDC/grids\\_germany/](https://opendata.dwd.de/climate_environment/CDC/grids_germany/)  
See [usage suggestions](#)

**Usage**

```
dwdbase
```

**Format**

An object of class character of length 1.

---

`dwdparams`*DWD parameter explanations*

---

**Description**

Short German parameter explanations for the DWD abbreviations on the CDC FTP server. These are manually created by me and might need to be expanded if the DWD adds more abbreviations.

`readVars()` maps them to the variable abbreviations in the "Metadaten\_Parameter.\*txt" file in any given zip folder and will warn about missing entries.

**Usage**

```
dwdparams
```

**Format**

An object of class `data.frame` with 176 rows and 2 columns.

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Jun 2018

**See Also**

`readVars()`, `readDWD()`

**Examples**

```
head(dwdparams)
```

---

`EUR`*Map of Western European countries through the rworldmap package*

---

**Description**

Map of Western European countries through the `rworldmap` package

**Format**

`SpatialPolygonsDataFrame` (package "sp") with 32 rows

**Details**

Use directly with:

```
load(system.file("extdata/EUR.rda", package="rdwd"))
```

Obtained with the code:

```
EUR <- rworldmap::getMap("low")
EUR <- raster::crop(EUR, c(-11,25, 40,60))
raster::crs(EUR) <- raster::crs(DEU)
raster::plot(EUR)
save(EUR, file="inst/extdata/EUR.rda", version=2)
tools::resaveRdaFiles("inst/extdata/EUR.rda", version=2)
```

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Aug 2019

**See Also**

[addBorders](#), [DEU](#)

---

fileType	<i>determine DWD file type</i>
----------	--------------------------------

---

**Description**

determine which subfunction to call in [readDWD\(\)](#) from the file extension (ext).

The first block is for **observational data** ([overview](#)), the second for **gridded data** ([overview](#)).

Click on the type for the subfunction documentation, e.g. [data](#) for [readDWD.data\(\)](#).

type	ext	notes
<a href="#">data</a>	.zip	For regular data at <a href="#">dwdbase</a> .
<a href="#">meta</a>	.txt	For Beschreibung.txt files. For zip files containing station meta information, see <a href="#">readMeta()</a> .
<a href="#">multia</a>	[SO]	[SO]: file ends with "Standort.txt" or contains multi_annual. Overrides meta.
<a href="#">stand</a>	[SF]	[SF]: file contains "standard_format". For subdaily/standard_format files.
<a href="#">data</a>	.txt.gz	For data at /CDC/derived_germany/.
<a href="#">pdf</a>	.pdf	only opens file in default viewer.

---

<code>radar</code>	<code>.gz</code>	For when the file contains a single binary file.
<code>binary</code>	<code>.tar.gz</code>	The common radolan format, as far as I can tell.
<code>raster</code>	<code>.asc.gz</code>	E.g. for seasonal data at <a href="#">gridbase</a> .
<code>nc</code>	<code>.nc.gz</code>	For netcdf files.
<code>asc</code>	<code>.tar</code>	For a file containing asc files.
<code>rklim</code>	<code>YW*.tar</code>	For a file containing bin files.
<code>grib2</code>	<code>.grib2.bz2</code>	For an nwp forecast file.

**Usage**

```
fileType(file)
```

**Arguments**

`file`                      Filename(s) with extension.

**Value**

Character (vector)

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Jul 2020

**See Also**

[readDWD\(\)](#)

**Examples**

```
ft <- read.table(header=TRUE, stringsAsFactors=FALSE, text="
type  filename
data  daily_kl_recent_tageswerte_KL_03987_akt.zip
meta  daily_kl_recent_KL_Tageswerte_Beschreibung_Stationen.txt
multia multi_annual_mean_81-10_Temperatur_1981-2010_aktStandort.txt
multia multi_annual_mean_81-10_Temperatur_1981-2010.txt
stand subdaily_standard_format_kl_10381_00_akt.txt
deriv derived_germany_soil_daily_historical_3987.txt.gz
pdf   DESCRIPTION_obsgermany_climate_monthly_kl_historical_en.pdf

radar  radolan_recent_bin_raa01-rw_10000-1802020250-dwd---bin.gz
binary daily_radolan_historical_bin_2017_SF201712.tar.gz
raster 16_DJF_grids_germany_seasonal_air_temp_mean_188216.asc.gz
```

```

nc      daily_Project_TRY_humidity_RH_199509_daymean.nc.gz
asc     radolan_historical_asc_2018_RW-201809.tar
rklim   5_minutes_radolan_reproc_2017_002_bin_2020_YW2017.002_202006.tar
grib2   ftp_weather_nwp_cosmo-d2_005_T_2M.grib2.bz2
")
fileType(ft$filename)

stopifnot(fileType(ft$filename)==ft$type)
berryFunctions::is.error(fileType("random_stuff.odt"), force=TRUE)

stopifnot(validFileTypes %in% ft$type)
stopifnot(ft$type %in% validFileTypes)

```

---

findID	<i>find DWD weather station ID from name</i>
--------	--

---

## Description

Identify DWD weather station ID from station name

## Usage

```

findID(
  name = "",
  exactmatch = TRUE,
  mindex = metaIndex,
  failempty = FALSE,
  quiet = rdwdquiet()
)

```

## Arguments

name	Char: station name(s) that will be matched in mindex to obtain <b>id</b> . DEFAULT: ""
exactmatch	Logical: Should name match an entry in mindex exactly (be ==)? If FALSE, name may be a part of mindex\$Stationsname, as checked with <a href="#">grepl()</a> . This is useful e.g. to get all stations starting with a name (e.g. 42 IDs for Berlin). DEFAULT: TRUE
mindex	Single object: Index used to select id if name is given. DEFAULT: <a href="#">metaIndex</a>
failempty	Logical: fail if no matching names are found (instead of returning NA with a warning)? With the latter, <a href="#">selectDWD()</a> returns all files at a res/var/per folder. This may be especially unwanted with per="hr". DEFAULT: FALSE
quiet	Logical: suppress length warnings? DEFAULT: FALSE through <a href="#">rdwdquiet()</a>

## Value

Character string (vector) with ID(s)



**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Oct-Nov 2016

**See Also**

used in [selectDWD\(\)](#), [metaInfo\(\)](#)

**Examples**

```
# Give weather station name (must be existing in metaIndex):
findID("Potsdam")
findID("potsDam") # capitalization is ignored
# all names containing "Hamburg":
findID("Hamburg", exactmatch=FALSE)
findID("Potsdam", exactmatch=FALSE)

# vectorized:
findID(c("Potsdam", "Berlin-Buch"))

# German Umlauts are changed to ue, ae, oe, ss
findID("Muenchen", FALSE)
berryFunctions::convertUmlaut("M?nchen") # use this to convert umlauts in lists
```

---

index

*Indexes of files and metadata on the DWD CDC FTP server*


---

**Description**

Created with [indexFTP\(\)](#) and [createIndex\(\)](#) used in [updateIndexes\(\)](#).

In functions, you can access them with `rdwd:::fileIndex` etc.

**fileIndex**: A data.frame with the filenames (and derived information) at the default base value [dwdbase](#).

**metaIndex**: A data.frame with the contents of all the station description files (...\_Beschreibung\_Stationen.txt) under [dwdbase](#).

**geoIndex**: metaIndex distilled to geographic locations.

**gridIndex**: Vector of file paths at [gridbase](#).

**formatIndex**: (modified) table from [https://opendata.dwd.de/climate\\_environment/CDC/observations\\_germany/climate/subdaily/standard\\_format/formate\\_kl.html](https://opendata.dwd.de/climate_environment/CDC/observations_germany/climate/subdaily/standard_format/formate_kl.html)

**Format**

**fileIndex**: data.frame with character strings. ca 260k rows x 8 columns:

res, var, per (see [selectDWD\(\)](#)), station id, time series start and end, and ismeta information, all according to path.

**metaIndex**: data.frame with ca 97k rows for 12 columns:

Stations\_id, von\_datum, bis\_datum, Stationshoehe, geoBreite, geoLaenge, Stationsname, Bundesland, res,

**geoIndex:** data.frame with ca 6k rows for 11 columns:

id, name, state, lat, lon, ele, nfiles, nonpublic, recentfile, display, col

**gridIndex:** Vector with ca 50k file paths at [gridbase](#)

**formatIndex:** data.frame with 140 rows for 12 columns:

Ke\_Ind, Kennung, Label, Beschreibung, Einheit, Code-Tabellen, Zusatzinfo, Typ, Pos, Erlaubt, Fehlk, div

### Author(s)

Berry Boessenkool, <berry-b@gmx.de>, June-Nov 2016, June 2017, Oct 2019

### Source

Deutscher WetterDienst / Climate Data Center FTP Server

### See Also

[createIndex\(\)](#), [indexFTP\(\)](#), [selectDWD\(\)](#), [findID\(\)](#), [metaInfo\(\)](#), [website index chapter](#)

### Examples

```
data(fileIndex)
data(metaIndex)
data(geoIndex)
head(fileIndex)
head(metaIndex)
head(geoIndex)

# in functions, you can use head(rdwd::fileIndex) etc, but I don't export them
# because Hadley says 'Never @export a data set' in
# browseURL("http://r-pkgs.had.co.nz/data.html#data-data")

# To use a custom index, see
# browseURL("https://bookdown.org/brry/rdwd/fileindex.html")
```

---

indexFTP

*Create a recursive index of an FTP Server*

---

### Description

Create a list of all the files (in all subfolders) of an FTP server. Defaults to the German Weather Service (DWD, Deutscher WetterDienst) OpenData server at [https://opendata.dwd.de/climate\\_environment/CDC/observations\\_germany/climate/](https://opendata.dwd.de/climate_environment/CDC/observations_germany/climate/).

The R package RCur1 must be available to do this.

It's not suggested to run this for all folders, as it can take quite some time and you may get kicked off the FTP-Server. This package contains an index of the climatic observations at weather stations ([fileIndex](#)) and gridded datasets ([gridIndex](#)). If they are out of date, please let me know!

### Getting banned from the FTP Server

Normally, this shouldn't happen anymore: since Version 0.10.10 (2018-11-26), a single RCurl handle is used for all FTP requests and since version 1.0.17 (2019-05-14), the file tree provided by the DWD is used to obtain all folders first, eliminating the recursive calls.

There's a provision if the FTP server detects bot requests and denies access. If `RCurl::getURL()` fails, there will still be an output which you can pass in a second run via `folder` to extract the remaining dirs. You might need to wait a bit and set `sleep` to a higher value in that case. Here's an example:

```
gridindex <- indexFTP("", gridbase)
gridindex <- indexFTP(gridindex, gridbase, sleep=15)
```

Of course, with a higher sleep value, the execution will take longer!

### Usage

```
indexFTP(
  folder = "currentfindex",
  base = dwdbase,
  is.file.if.has.dot = TRUE,
  exclude.latest.bin = TRUE,
  fast = TRUE,
  sleep = 0,
  dir = "DWDdata",
  filename = folder[1],
  overwrite = FALSE,
  quiet = rdwdquiet(),
  progbar = !quiet,
  verbose = FALSE
)
```

### Arguments

<code>folder</code>	Folder(s) to be indexed recursively, e.g. <code>"/hourly/wind/"</code> . Leading slashes will be removed. Use <code>folder=""</code> to search at the location of base itself. If folder is "currentfindex" (the default) and base is the default, folder is changed to all observational folders listed in the current tree file at <a href="https://opendata.dwd.de/weather/tree.html">https://opendata.dwd.de/weather/tree.html</a> . With "currentgindex" and <code>gridbase</code> , the grid folders in the tree are used. DEFAULT: "currentfindex"
<code>base</code>	Main directory of FTP server. Trailing slashes will be removed. DEFAULT: <a href="#">dwdbase</a>
<code>is.file.if.has.dot</code>	Logical: if some of the input paths contain a dot, treat those as files, i.e. do not try to read those as if they were a folder. Only set this to FALSE if you know what you're doing. DEFAULT: TRUE

exclude.latest.bin	Exclude latest file at <code>opendata.dwd.de/weather/radar/radolan?</code> <code>RCurl::getURL</code> indicates this is a pointer to the last regularly named file. DEFAULT: TRUE
fast	Read tree file with <code>data.table::fread()</code> (1 sec) instead of <code>readLines()</code> (10 secs)? DEFAULT: TRUE
sleep	If not 0, a random number of seconds between 0 and <code>sleep</code> is passed to <code>Sys.sleep()</code> after each read folder to avoid getting kicked off the FTP-Server, see note above. DEFAULT: 0
dir	Writeable directory name where to save the downloaded file. Created if not existent. DEFAULT: "DWDdata" at current <code>getwd()</code>
filename	Character: Part of output filename. "INDEX_of_DWD_" is prepended, "/" replaced with "_", ".txt" appended. DEFAULT: <code>folder[1]</code>
overwrite	Logical: Overwrite existing file? If not, "_n" is added to the filename, see <code>berryFunctions::newFilename()</code> . DEFAULT: FALSE
quiet	Suppress progbars and message about directory/files? DEFAULT: FALSE through <code>rdwdquiet()</code>
progressbar	Logical: present a progress bar in each level? DEFAULT: TRUE
verbose	Logical: write a lot of messages from <code>RCurl::getURL()</code> ? DEFAULT: FALSE (usually, you dont need all the curl information)

**Value**

a vector with file paths

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Oct 2016

**See Also**

[createIndex\(\)](#), [updateIndexes\(\)](#), [website index chapter](#)

**Examples**

```
## Not run: ## Needs internet connection
sol <- indexFTP(folder="/daily/solar", dir=tempdir())
head(sol)

# mon <- indexFTP(folder="/monthly/kl", dir=tempdir(), verbose=TRUE)

## End(Not run)
```

---

lldist	<i>distance between lat-long coordinates</i>
--------	--

---

### Description

Great-circle distance between points at lat-long coordinates. Mostly a copy of `OSMscale::earthDist` Version 0.5.3 (2017-04-19). <https://github.com/brry/OSMscale/blob/master/R/earthDist.R#L57-L102>. Copied manually to avoid dependency hell. Does not check coordinates. Not exported.

### Usage

```
lldist(lat, long, data, r = 6371, i = 1L)
maxlldist(lat, long, data, r = 6371, fun = max, each = TRUE, ...)
```

### Arguments

lat, long	Latitude (North/South) and longitude (East/West) coordinates in decimal degrees
data	Optional: data.frame with the columns lat and long
r	radius of the earth. Could be given in miles. DEFAULT: 6371 (km)
i	Integer: Index element against which all coordinate pairs are computed. DEFAULT: 1
fun	Function to be applied. DEFAULT: <code>max()</code>
each	Logical: give max dist to all other points for each point separately? If FALSE, will return the maximum of the complete distance matrix, as if <code>max(maxlldist(y, x))</code> . For examples, see <code>OSMscale::maxEarthDist</code> DEFAULT: TRUE
...	Further arguments passed to fun, like <code>na.rm=TRUE</code>

### Value

Vector with distance(s) in km (or units of r, if r is changed)

### Author(s)

Berry Boessenkool, <brry-b@gmx.de>, Aug 2016 + Jan 2017. Angle formula from Diercke Weltatlas 1996, Page 245

---

locdir	<i>local data directory</i>
--------	-----------------------------

---

### Description

This can be used to set a directory for DWD data across projects, thus avoiding multiple downloads of the same file.

Set the default for all subsequent calls with `options(rdwdlocdir="YOUR/PATH")`.

Currently, the `dataDWD()` dir defaults to a project specific folder at `getwd`. In the future, this may change to `locdir()`.

`locdir()` is used especially for the website, local tests and examples.

### Usage

```
locdir(dir = getOption("rdwdlocdir"), file = NULL, quiet = rdwdquiet())
```

### Arguments

dir	Path to data directory. If dir does not exist, <code>tempdir()</code> is used instead (with a warning, unless <code>quiet=TRUE</code> ). If dir is NULL, locdir tries "C:/DWDdata", then "~/DWDdata". dir can also be set with <code>options(rdwdlocdir="YOUR/PATH")</code> thanks to the DEFAULT: <code>getOption("rdwdlocdir")</code>
file	Optional: path(s) at dir. DEFAULT: NULL
quiet	Logical: suppress tempdir warning? DEFAULT: FALSE through <code>rdwdquiet()</code>

### Value

charstring (directory)

### Author(s)

Berry Boessenkool, <berry-b@gmx.de>, Apr 2019, Jun 2021

### See Also

[runLocalTests\(\)](#)

### Examples

```
locdir()
oldopt <- options(rdwdlocdir="~")
locdir()
stopifnot(locdir() == path.expand("~"))
options(oldopt) ; rm(oldopt)
```

---

`metaInfo`*Information for a station ID on the DWD CDC FTP server*

---

**Description**

Information for a station ID on the DWD CDC FTP server

**Usage**

```
metaInfo(id, mindex = metaIndex, hasfileonly = TRUE)
```

**Arguments**

<code>id</code>	Station ID (integer number or convertible to one)
<code>mindex</code>	Index dataframe with metadata. DEFAULT: <a href="#">metaIndex</a>
<code>hasfileonly</code>	Logical: Only show entries that have files? DEFAULT: TRUE

**Value**

invisible data.frame. Also [prints](#) the output nicely formatted.

**Author(s)**

Berry Boessenkool, <[berry-b@gmx.de](mailto:berry-b@gmx.de)>, Nov 2016

**See Also**

[metaIndex](#)

**Examples**

```
metaInfo(2849)
```

---

`nearbyStations`*Find DWD stations close to given coordinates*

---

**Description**

Select DWD stations within a given radius around a set of coordinates

**Usage**

```

nearbyStations(
  lat,
  lon,
  radius,
  res = NA,
  var = NA,
  per = NA,
  mindate = NA,
  hasfileonly = TRUE,
  statname = "nearbyStations target location",
  quiet = rdwdquiet(),
  ...
)

```

**Arguments**

lat	Coordinates y component [degrees N/S, range 47:55]
lon	Coordinates x component [degrees E/W, range 6:15]
radius	Maximum distance [km] within which stations will be selected
res, var, per	Restrictions for dataset type as documented in <a href="#">selectDWD()</a> . Each can be a vector of entries. DEFAULTS: NA (ignored)
mindate	Minimum dataset ending date (as per metadata). DEFAULT: NA
hasfileonly	Logical: only return entries for which there is an open-access file available? DEFAULT: TRUE
statname	Character: name for target location. DEFAULT: "nearbyStations target location"
quiet	Logical: suppress progress messages? DEFAULT: FALSE through <a href="#">rdwdquiet()</a>
...	Further arguments passed to <a href="#">selectDWD()</a>

**Value**

[metaIndex](#) subset with additional columns "dist" and "url"

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Mar 2017

**See Also**

[selectDWD\(\)](#), [metaIndex](#), [website use case with nearbyStations](#)

**Examples**

```

m <- nearbyStations(49.211784, 9.812475, radius=30,
  res=c("daily","hourly"), var= c("precipitation","more_precip","kl") ,
  mindate=as.Date("2016-05-30"), statname="Braunsbach catchment center")

```



```
# View(m)

# for a continued example of this, see the vignette in chapter
# use case: plot all rainfall values around a given point
# browseURL("https://bookdown.org/brry/rdwd")
```

---

newColumnNames	<i>Enhance readDWD column names</i>
----------------	-------------------------------------

---

### Description

Add short German parameter descriptions to the DWD abbreviations. This uses `dwdparams()` to create column names like "TT\_TU.Lufttemperatur" and "RSK.Niederschlagshoehe." Column names not in the abbreviation list will be left untouched.

### Usage

```
newColumnNames(dataframe, variables = dwdparams, separator = ".")
```

### Arguments

dataframe	Dataframe as returned by <code>readDWD.data()</code>
variables	Dataframe as returned by <code>readVars()</code> for a single file. Rownames must be variable abbreviations. There must be a "Kurz" column. DEFAULT: <code>dwdparams</code>
separator	Separator between abbreviation and long name. DEFAULT: "."

### Value

The dataframe with new column names

### Author(s)

Berry Boessenkool, <berry-b@gmx.de>, Apr 2019

### See Also

`dwdparams`, `readVars()`, `readDWD()` argument `varnames`, `newColumnNames()`

### Examples

```
# mainly for internal usage
```

plotDWD

*Quickly plot time series***Description**

plot rdwd time series from data.frames

**Usage**

```
plotDWD(
  x,
  cn,
  monthaxis = TRUE,
  line0 = FALSE,
  xlab = "",
  ylab = cn,
  main = "",
  type = "l",
  lwd = 3,
  col = "blue",
  las = 1,
  mar = c(2.6, 3.1, 2.5, 0.5),
  mgp = c(1.9, 0.7, 0),
  keeppar = TRUE,
  ...
)
```

**Arguments**

x	Data.frame, e.g. from <a href="#">readDWD.data</a>
cn	Column name (charstring)
monthaxis	Draw nice axis? DEFAULT: TRUE
line0	Draw horizontal line at 0? DEFAULT: FALSE
xlab	X axis label. DEFAULT: ""
ylab	Y axis label. DEFAULT: cn
main	Plot title. DEFAULT: ""
type	<a href="#">graphics::plot</a> type. DEFAULT: "l"
lwd	Line width. DEFAULT: 3
col	Line color. DEFAULT: "blue"
las	Label axis style. DEFAULT: 1 (all upright)
mar	Plot margins. DEFAULT: c(2.6, 3.1, 2.5, 0.5)
mgp	Margin placement. DEFAULT: c(1.9, 0.7, 0)
keeppar	Keep las, mar and mgp as set with <a href="#">par</a> , so later points are added in the right location? DEFAULT: TRUE
...	Further arguments passed to <a href="#">graphics::plot</a>

**Value**

Nothing

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Sep 2021

**See Also**

[readDWD\(\)](#)

**Examples**

```
link <- selectDWD("Potsdam", res="daily", var="kl", per="r")
clim <- dataDWD(link, dir=locdir(), varnames=TRUE)
plotDWD(clim, "TMK.Lufttemperatur", line0=TRUE, main="Potsdam")
```

---

plotRadar

*plot radar products on a pretty map*

---

**Description**

Convenience function to plot radar products on a pretty map. Creates a separate plot for each layer, a selection is possible.

**Usage**

```
plotRadar(
  x,
  layer = NULL,
  main = x@title,
  land = "gray80",
  sea = "cadetblue1",
  de = "grey80",
  eu = "black",
  col = berryFunctions::seqPal(),
  xlim = NULL,
  ylim = NULL,
  zlim = NULL,
  axes = TRUE,
  las = 1,
  mar = c(2.5, 3.5, 2.5, 5),
  keeppar = TRUE,
  project = TRUE,
  proj = "radolan",
  extent = "radolan",
```

```

adjust05 = FALSE,
targetproj = "ll",
quiet = rdwdquiet(),
...
)

```

## Arguments

x	raster object, e.g. 'dat' element of object returned by <code>readDWD()</code> .
layer	Optional: selected layer(s) to be plotted. DEFAULT: NULL
main	Graph title(s). Use "" to suppress. Note <code>output@title</code> is set to main! DEFAULT: x@title
land	Color of land areas in the map. DEFAULT: "gray80"
sea	Color of sea areas in the map. DEFAULT: "cadetblue1"
de	Color of Deutschland Bundesland borders (DEU). DEFAULT: "grey80"
eu	Color of Europe country borders (EUR). DEFAULT: "black"
col	Color palette for the data itself. DEFAULT: <code>berryFunctions::seqPal()</code>
xlim	xlim. DEFAULT: NULL, i.e. taken from x extent (after reprojection if <code>project=TRUE</code> )
ylim	ylim. DEFAULT: NULL, i.e. taken from y extent (after reprojection if <code>project=TRUE</code> )
zlim	zlim. 3 Options: two-number vector, <code>zlim="ind"</code> for individual zlim per layer, or NULL for range of selected layer(s). DEFAULT: NULL
axes	Draw axes? DEFAULT: TRUE
las	LabelAxisStyle for axes. DEFAULT: 1 (all upright)
mar	Vector with plot margins. DEFAULT: <code>c(2.5, 3.5, 2.5, 5)</code>
keeppar	Logical: keep the margins set with par, so later points etc are added in the right location? DEFAULT: TRUE, opposite to <code>sf::plot</code> with <code>reset=TRUE</code> , see <a href="https://github.com/cran/sf/blob/master/R/plot.R">https://github.com/cran/sf/blob/master/R/plot.R</a>
project	Project the data before plotting? Not needed if <code>projectRasterDWD()</code> has already been called. DEFAULT: TRUE
proj	current projection, see <code>projectRasterDWD()</code> , used only if <code>project=TRUE</code> . DEFAULT: "radolan"
extent	current extent, see <code>projectRasterDWD()</code> , used only if <code>project=TRUE</code> . DEFAULT: "radolan"
adjust05	Logical: Adjust extent by 0.5m to match edges? DEFAULT: FALSE
targetproj	target projection, see <code>projectRasterDWD()</code> , used only if <code>project=TRUE</code> . DEFAULT: "ll"
quiet	suppress progress messages? DEFAULT: FALSE through <code>rdwdquiet()</code>
...	Further arguments passed to <code>raster::plot()</code>

## Value

raster object, projected (if `project=TRUE`). If `length(layer)==1`, only that selected layer is returned. `output@title` is set to main.

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Feb 2020

**See Also**

[projectRasterDWD\(\)](#), [addBorders\(\)](#), [readDWD\(\)](#), [website raster chapter](#)

**Examples**

```
# See homepage in the section 'See Also'
## Not run: ## Excluded from CRAN checks: requires internet connection
link <- "seasonal/air_temperature_mean/16_DJF/grids_germany_seasonal_air_temp_mean_188216.asc.gz"
rad <- dataDWD(link, base=gridbase, joinbf=TRUE, dir=locdir())
radp <- plotRadar(rad, proj="seasonal", extent=rad@extent, main="plotRadar ex")
plotRadar(radp, ylim=c(52,54), project=FALSE) # reuses main

# plotRadar equivalent, map only country borders:
radpm <- projectRasterDWD(rad[[1]], proj="seasonal", extent=rad@extent)
raster::plot(radpm)
addBorders()

# several layers
url <- "daily/Project_TRY/pressure/PRED_199606_daymean.nc.gz" # 5 MB
nc <- dataDWD(url, base=gridbase, joinbf=TRUE, dir=locdir())

ncp3 <- plotRadar(nc, main=paste(nc@title, nc@z[[1]]), layer=1:3,
                 col=terrain.colors(100), proj="nc", extent="nc")
plotRadar(ncp3, layer=3:4, project=FALSE) # still has all layers
plotRadar(ncp3, layer=4:5, project=FALSE, zlim="ind") # individual zlims per layer
plotRadar(ncp3, layer=1, project=FALSE, zlim=c(1016,1020))

ncp1 <- plotRadar(nc, layer=1, proj="nc", extent="nc") # much faster projection
# no longer has layers 2-4:
berryFunctions::is.error(plotRadar(ncp1, layer=1:4, project=FALSE), TRUE, TRUE)

## End(Not run)
```

---

projectRasterDWD

*project DWD raster data*

---

**Description**

Set projection and extent for DWD raster data. Optionally (and per default) also reprojects to latlon data.

**WARNING:** reprojection to latlon changes values slightly. For the tested RX product, this change is significant, see: <https://github.com/brry/rdwd/blob/master/misc/ExampleTests/Radartests.pdf>

In raster::plot, use **zlim with the original range** if needed.

**Usage**

```
projectRasterDWD(
  r,
  proj = "radolan",
  extent = "radolan",
  adjust05 = FALSE,
  targetproj = "ll",
  quiet = rdwdquiet()
)
```

**Arguments**

r	Raster object
proj	Current projection to be given to r. Can be <ul style="list-style-type: none"> <li>- a <code>raster::crs()</code> input (e.g. a projection character string),</li> <li>- NULL to not set proj+extent (but still consider targetproj),</li> <li>- or a special charstring for internal defaults, namely: "radolan" (readDWD.binary + .asc + .radar), "seasonal" (.raster) or "nc" (.nc).</li> </ul> DEFAULT: "radolan"
extent	Current <code>raster::extent()</code> to be given to r. Ignored if proj=NULL. Can be an extent object, a vector with 4 numbers, or "radolan" / "rw" / "seasonal" / "nc" with internal defaults. DEFAULT: "radolan"
adjust05	Logical: Adjust extent by 0.5m to match edges? DEFAULT: FALSE
targetproj	r is reprojected to this <code>raster::crs()</code> . Use NULL to not reproject (i.e. only set proj and extent). DEFAULT: "ll" with internal default for lat-lon.
quiet	Logical: suppress progress messages? DEFAULT: FALSE through <code>rdwdquiet()</code>

**Details**

The internal defaults are extracted from the Kompositformatbeschreibung at <https://www.dwd.de/DE/leistungen/radolan/radolan.html>, as provided 2019-04 by Antonia Hengst. The nc extent was obtained by projecting Germanys bbox to EPSG 3034 (specified in the DWD documentation). Using that as a starting point, I then refined the extent to a visual match, see [developmentNotes.R](#)

**Value**

Raster object with projection and extent, invisible

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, May 2019

**See Also**

`plotRadar()`  
`raster::crs / extent / projectRaster`  
`readDWD.binary / raster / asc / radar / nc`  
[website raster chapter](#)

**Examples**

```
# To be used after readDWD.binary etc
```

---

rdwd

*Handle Climate Data from DWD (German Weather Service)*

---

**Description**

- find, select, download + read data from the German weather service DWD
- vectorized, progress bars, no re-downloads
- index of files + meta data
- observational time series from 6k meteorological recording stations (2.5k active)  
-> rain, temperature, wind, sunshine, pressure, cloudiness, humidity, snow, ...
- gridded raster data from radar + interpolation
- european data stock slowly growing  
For an introduction to the package, see <https://bookdown.org/brry/rdwd>.

**Searchability Terms**

Weather Data Germany download with R, Climate Data Germany  
Deutscher Wetterdienst R Daten download Klimastationen  
DWD Daten mit R runterladen, Wetter und Klimadaten in R

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>

**See Also**

USA data: [countyweather](#), [noaa](#)  
 World data: [Global Surface Summary of the Day](#)  
 Dutch data (Netherlands): <https://github.com/bvhest/KNMIr>  
 Canadian data: <https://cran.r-project.org/package=weathercan>  
 UK data website <https://www.metoffice.gov.uk/climate/uk/data>

---

rdwdquiet	<i>global quiet option for rdwd</i>
-----------	-------------------------------------

---

**Description**

global quiet option. The default `rdwdquiet()` is FALSE.  
 Just write the following in your code and all subsequent calls will be quiet:  
`options(rdwdquiet=TRUE)`

**Usage**

```
rdwdquiet()
```

---

readDWD	<i>Process data from the DWD CDC FTP Server</i>
---------	---

---

**Description**

Read climate data that was downloaded with [dataDWD\(\)](#). The data is unzipped and subsequently, the file(s) are read, processed and returned as a `data.frame` / raster object.

For observational data, new users are advised to set `varnames=TRUE` to obtain more informative column names.

`readDWD` will call internal (but documented) subfunctions depending on the argument type, see the overview in [fileType\(\)](#).

Not all arguments to `readDWD` are used for all subfunctions, e.g. `fread` is used only by [readDWD.data](#), while `dividebyten` is used in [readDWD.raster](#) and [readDWD.asc](#).

`file` can be a vector with several filenames. Most other arguments can also be a vector and will be recycled to the length of `file`.



**Usage**

```

readDWD(
  file,
  type = fileType(file),
  varnames = FALSE,
  fread = NA,
  format = NA,
  tz = "GMT",
  hr = 0,
  dividebyten = TRUE,
  var = "",
  progbar = !quiet,
  quiet = rdwdquiet(),
  quietread = quiet,
  ...
)

```

**Arguments**

file	Char (vector): name(s) of the file(s) downloaded with <code>dataDWD()</code> , e.g. "~/DWD-data/tageswerte_KL_02575_akt.zip" or "~/DWDdata/RR_Stundenwerte_Beschreibung_Stationen.txt"
type	Character (vector) determining which subfunction to call. DEFAULT: <code>fileType(file)</code> .
varnames	Logical (vector): Expand column names? Only used in <code>readDWD.data()</code> . DEFAULT: FALSE (for backward compatibility)
fread	Logical (vector): read fast? Used in <code>readDWD.data()</code> . DEFAULT: NA
format, tz	Format and time zone of time stamps, see <code>readDWD.data()</code>
hr	Integer code to merge historical and recent file. Used here, but documented in detail in <code>readDWD.data()</code> . DEFAULT: 0 (ignore argument)
dividebyten	Logical (vector): Divide the values in raster files by ten? That way, [1/10 mm] gets transformed to [mm] units. Used in <code>readDWD.radar()</code> , <code>readDWD.raster()</code> and <code>readDWD.asc()</code> . DEFAULT: TRUE
var	var for <code>readDWD.nc()</code> . DEFAULT: ""
progbar	Logical: present a progress bar with estimated remaining time? If missing and <code>length(file)==1</code> , progbar is internally set to FALSE, unless binary files are to be read. DEFAULT: !quiet
quiet	Logical: suppress messages? DEFAULT: FALSE through <code>rdwdquiet()</code>
quietread	Logical: suppress message like "Reading 1 file with readDWD.data() and fread=TRUE ...". DEFAULT: quiet
...	Further arguments passed to the internal <code>readDWD.*</code> subfunctions (see <code>fileType</code> ) and from those to the underlying actual reading functions

**Value**

For observational data, an invisible data.frame of the desired dataset, or a named list of data.frames if `length(file) > 1`.

For gridded data, raster objects.

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Jul-Oct 2016, Winter 2018/19

**See Also**

[dataDWD\(\)](#), [readVars\(\)](#), [readMeta\(\)](#), [selectDWD\(\)](#), [fileType\(\)](#)  
<https://bookdown.org/brry/rdwd>

**Examples**

```
# see dataDWD and readDWD.* subfunctions
```

---

readDWD.asc	<i>read dwd gridded radolan asc data</i>
-------------	--

---

**Description**

read grid-interpolated radolan asc data. Intended to be called via [readDWD\(\)](#).  
 All layers (following selection if given) in all .tar.gz files are combined into a raster stack with [raster::stack\(\)](#).  
 To project the data, use [projectRasterDWD\(\)](#)

**Usage**

```
readDWD.asc(  
  file,  
  exdir = NULL,  
  dividebyten = TRUE,  
  selection = NULL,  
  quiet = rdwquiet(),  
  progbar = !quiet,  
  ...  
)
```

**Arguments**

file	Name of file on harddrive, like e.g. DWDdata/grids_germany/hourly/radolan/historical/asc/2018_RW-201809.tar. Must have been downloaded with mode="wb"!
exdir	Directory to unzip into. Unpacked files existing therein will not be untarred again, saving up to 15 secs per file. DEFAULT: NULL (subfolder of <a href="#">tempdir()</a> )
dividebyten	Divide numerical values by 10? See <a href="#">readDWD</a> . If dividebyten=FALSE and exdir left at NULL (tempdir), save the result on disc with <a href="#">raster::writeRaster()</a> . Accessing out-of-memory raster objects won't work if exdir is removed! -> Error in .local(Object, ...) DEFAULT: TRUE
selection	Optionally read only a subset of the ~24*31=744 files. Called as f[selection]. DEFAULT: NULL (ignored)

quiet	Suppress progress messages? DEFAULT: FALSE through <code>rdwdquiet()</code>
progbar	Show progress bars? <code>readDWD()</code> will keep <code>progbar=TRUE</code> for asc files, even if <code>length(file)==1</code> . DEFAULT: !quiet, i.e. TRUE
...	Further arguments passed to <code>raster::raster()</code>

**Value**

data.frame

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, April 2019

**See Also**

[readDWD\(\)](#)

**Examples**

```
## Not run: # Excluded from CRAN checks, but run in localtests

# File selection and download:
datadir <- locdir()
radbase <- paste0(gridbase, "/hourly/radolan/historical/asc/")
radfile <- "2018/RW-201809.tar" # 25 MB to download
file <- dataDWD(radfile, base=radbase, joinbf=TRUE, dir=datadir,
               dbin=TRUE, read=FALSE) # download with mode=wb!!!

#asc <- readDWD(file) # 4 GB in mem. ~ 20 secs unzip, 30 secs read, 10 min divide
asc <- readDWD(file, selection=1:5, dividebyten=TRUE)
plotRadar(asc[[1]], main=names(asc)[1])

viddir <- paste0(tempdir(), "/RadolanVideo")
dir.create(viddir)
png(paste0(viddir, "/Radolan_%03d.png"), width=7, height=5, units="in", res=300)
plotRadar(asc, layer=1:3, main=names(asc)) # 3 secs per layer
dev.off()
berryFunctions::openFile(paste0(viddir, "/Radolan_001.png"))

# Time series of a given point in space:
plot(as.vector(asc[800,800,]), type="l", xlab="Time [hours]")

# if dividebyten=FALSE, raster stores things out of memory in the exdir.
# by default, this is in tempdir, hence you would need to save asc manually:
# raster::writeRaster(asc, paste0(datadir, "/RW2018-09"), overwrite=TRUE)

## End(Not run)
```

---

readDWD.binary	<i>read dwd gridded radolan binary data</i>
----------------	---

---

### Description

read gridded radolan binary data. Intended to be called via [readDWD\(\)](#).

### Usage

```
readDWD.binary(
  file,
  exdir = sub(".tar.gz$", "", file),
  toraster = TRUE,
  quiet = rdwdquiet(),
  progbar = !quiet,
  selection = NULL,
  ...
)
```

### Arguments

file	Name of file on harddrive, like e.g. DWDdata/daily_radolan_historical_bin_2017_SF201712.tar.gz
exdir	Directory to unzip into. If existing, only the needed files will be unpacked with <a href="#">untar()</a> . Note that exdir size will be around 1.1 GB. exdir can contain other files, these will be ignored for the actual reading with <a href="#">dwdradar::readRadarFile()</a> . DEFAULT exdir: sub(".tar.gz\$", "", file)
toraster	Logical: convert output (list of matrixes + meta informations) to a list with dat ( <a href="#">raster::stack</a> ) + meta (list from the first subfile, but with vector of dates)? DEFAULT: TRUE
quiet	Suppress progress messages? DEFAULT: FALSE through <a href="#">rdwdquiet()</a>
progbar	Show progress bars? <a href="#">readDWD()</a> will keep progbar=TRUE for binary files, even if length(file)==1. DEFAULT: !quiet, i.e. TRUE
selection	Optionally read only a subset of the ~24*31=744 files. Called as f[selection]. DEFAULT: NULL (ignored)
...	Further arguments passed to <a href="#">dwdradar::readRadarFile()</a> , i.e. na and clutter

### Value

list depending on argument toraster, see there for details

### Author(s)

Berry Boessenkool, <berry-b@gmx.de>, Dec 2018. Significant input for the underlying [dwdradar::readRadarFile\(\)](#) came from Henning Rust & Christoph Ritschel at FU Berlin.

**See Also**

`readDWD()`, especially `readDWD.radar()`  
<https://wradlib.org> for much more extensive radar analysis in Python  
 Kompositformatbeschreibung at <https://www.dwd.de/DE/leistungen/radolan/radolan.html>  
 for format description

**Examples**

```
## Not run: # Excluded from CRAN checks, but run in localtests

# SF file as example: ----

SF_link <- "/daily/radolan/historical/bin/2017/SF201712.tar.gz"
SF_file <- dataDWD(url=SF_link, base=gridbase, joinbf=TRUE, # 204 MB
                  dir=locdir(), read=FALSE)
# exdir radardir set to speed up my tests:
SF_exdir <- "C:/Users/berry/Desktop/DWDbinarySF"
if(!file.exists(SF_exdir)) SF_exdir <- tempdir()
# no need to read all 24*31=744 files, so setting selection:
SF_rad <- readDWD(SF_file, selection=1:10, exdir=SF_exdir) #with toraster=TRUE
if(length(SF_rad)!=2) stop("length(SF_rad) should be 2, but is ", length(SF_rad))

SF_radv <- plotRadar(SF_rad$dat, layer=1:3, main=SF_rad$meta$date)
plotRadar(SF_radv, layer=1, project=FALSE)

# RW file as example: ----

RW_link <- "hourly/radolan/reproc/2017_002/bin/2017/RW2017.002_201712.tar.gz"
RW_file <- dataDWD(url=RW_link, base=gridbase, joinbf=TRUE, # 25 MB
                  dir=locdir(), read=FALSE)
RW_exdir <- "C:/Users/berry/Desktop/DWDbinaryRW"
if(!file.exists(RW_exdir)) RW_exdir <- tempdir()
RW_rad <- readDWD(RW_file, selection=1:10, exdir=RW_exdir)
RW_radv <- plotRadar(RW_rad$dat[[1]], main=RW_rad$meta$date[1], extent="rw")

# ToDo: why are values + patterns not the same?

# list of all Files: ----
data(gridIndex)
head(grep("historical", gridIndex, value=TRUE))

## End(Not run)
```

---

readDWD.data

*read regular dwd data*


---

**Description**

Read regular dwd data. Intended to be called via `readDWD()`.

**Usage**

```
readDWD.data(
  file,
  fread = FALSE,
  varnames = FALSE,
  format = NA,
  tz = "GMT",
  hr = 0,
  quiet = rdwdquiet(),
  ...
)
```

**Arguments**

file	Name of file on harddrive, like e.g. DWDdata/daily_kl_recent_tageswerte_KL_03987_akt.zip
fread	Logical: read faster with <code>data.table::fread</code> ? When reading many large historical files, speedup is significant. When called from <code>readDWD()</code> , <code>fread=NA</code> can also be used, which means TRUE if R package <code>data.table</code> and system command <code>unzip</code> are available. Hint for Windows users: <code>unzip</code> comes with <code>Rtools</code> . See <a href="https://bookdown.org/brry/rdwd/fread.html">https://bookdown.org/brry/rdwd/fread.html</a> DEFAULT: FALSE
varnames	Logical (vector): add a short description to the DWD variable abbreviations in the column names? E.g. change FX, TNK to FX.Windspitze, TNK.Lufttemperatur_Min, see <code>newColumnNames()</code> . DEFAULT: FALSE (for backwards compatibility)
format	Char (vector): Format passed to <code>as.POSIXct()</code> (see <code>strptime()</code> ) to convert the date/time column to POSIX time format. If NULL, no conversion is performed (date stays a factor). If NA, <code>readDWD</code> tries to find a suitable format based on the number of characters. DEFAULT: NA
tz	Char (vector): time zone for <code>as.POSIXct()</code> . "" is the current time zone, and "GMT" is UTC (Universal Time, Coordinated). DEFAULT: "GMT"
hr	Integer code to automatically merge historical and recent datasets. If set, <code>readDWD</code> returns a <code>data.frame</code> instead of a list. If multiple historical files are present, the longest date range (per file name) is used. This is not actually used in <code>readDWD.data</code> , but in <code>readDWD()</code> . 0 (default): ignore this argument 1: sort by hr (if given) + merge 2: also remove duplicated dates from recent 3: also remove columns QN3,QN4,eor 4: also remove column STATIONS_ID DEFAULT: 0
quiet	Suppress empty file warnings? DEFAULT: FALSE through <code>rdwdquiet()</code>
...	Further arguments passed to <code>read.table()</code> or <code>data.table::fread()</code>

**Value**

data.frame

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>

**See Also**

[readDWD\(\)](#), Examples in [dataDWD\(\)](#)

---

readDWD.deriv	<i>read derived dwd data</i>
---------------	------------------------------

---

**Description**

Read dwd data from /CDC/derived\_germany/. Intended to be called via [readDWD\(\)](#).

**Usage**

```
readDWD.deriv(file, gargs = NULL, todate = TRUE, quiet = rdwdquiet(), ...)
```

**Arguments**

file	Name of file on harddrive, like e.g. DWDdata/soil_daily_historical_derived_germany_soil_daily_historic
gargs	If fread=FALSE: Named list of arguments passed to <a href="#">R.utils::gunzip()</a> , see <a href="#">readDWD.raster()</a> . DEFAULT: NULL
todate	Logical: Convert char column 'Datum' or 'Monat' with <a href="#">as.Date()</a> ? The format is currently hard-coded. Monthly data gets mapped to yyyy-mm-15 DEFAULT: TRUE
quiet	Ignored. DEFAULT: FALSE through <a href="#">rdwdquiet()</a>
...	Further arguments passed to <a href="#">read.table()</a> or <a href="#">data.table::fread()</a>

**Value**

data.frame

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>

**See Also**

[readDWD\(\)](#), <https://bookdown.org/brry/rdwd/use-case-derived-data.html>

---

readDWD.grib2                    *read nwp forecast data*

---

## Description

read gridded numerical weather prediction data. Intended to be called via [readDWD\(\)](#).

## Usage

```
readDWD.grib2(
  file,
  pack = "terra",
  bargs = NULL,
  toraster = TRUE,
  quiet = rdwdquiet(),
  ...
)
```

## Arguments

file	Name of file on harddrive, like e.g. cosmo-d2_germany_regular-lat-lon_single-level_2021010100_005_T_2M.grib2.bz2
pack	Char: package used for reading. One of "terra" (the default), "stars" or "rgdal" (for the deprecated cosmo-d2 data). See <a href="#">issue</a> . "rgdal" will be deprecated in 2023. DEFAULT: "terra"
bargs	Named list of arguments passed to <a href="#">R.utils::bunzip2()</a> , see gargs in <a href="#">readDWD.raster()</a> . DEFAULT: NULL
toraster	Logical: convert <a href="#">rgdal::readGDAL</a> output with <a href="#">raster::raster()</a> ? Only used if pack="rgdal". DEFAULT: TRUE
quiet	Silence readGDAL completely, including warnings on discarded ellps / datum. DEFAULT: FALSE through <a href="#">rdwdquiet()</a>
...	Further arguments passed to <a href="#">terra::rast()</a> or <a href="#">stars::read_stars()</a> .

## Value

rgdal or raster object, depending on toraster

## Author(s)

Berry Boessenkool, <berry-b@gmx.de>, Jan 2021.

## See Also

[readDWD\(\)](#)  
[https://www.dwd.de/EN/ourservices/nwp\\_forecast\\_data/nwp\\_forecast\\_data.html](https://www.dwd.de/EN/ourservices/nwp_forecast_data/nwp_forecast_data.html)  
<https://www.dwd.de/EN/aboutus/it/functions/Teasergroup/grib.html>



## Examples

```
## Not run: # Excluded from CRAN checks, but run in localtests
nwp_t2m_base <- "ftp://opendata.dwd.de/weather/nwp/icon-d2/grib/15/soiltyp"
nwp_urls <- indexFTP("", base=nwp_t2m_base, dir=tempdir())
# for p instead of soiltyp, icosahedral_model-level files fail with GDAL errors,
# see https://github.com/brry/rdwd/issues/28
# regular-lat-lon-pressure-level files work with pack="terra" or "stars"

nwp_file <- dataDWD(tail(nwp_urls,1), base=nwp_t2m_base, dir=tempdir(),
                   joinbf=TRUE, dbin=TRUE, read=FALSE)
nwp_data <- readDWD(nwp_file)
terra::plot(nwp_data) # same map with sp::plot
addBorders() # the projection seems to be perfectly good :)

# index of GRIB files
if(FALSE){ # indexing takes about 6 minutes!
grib_base <- "ftp://opendata.dwd.de/weather/nwp/icon-d2/grib"
grib_files <- indexFTP("", base=grib_base, dir=tempdir())
for(f in unique(substr(grib_files, 1,3))) print(grib_files[which(substr(grib_files, 1,3)==f)[1]])
View(data.frame(grep("regular",grib_files, value=TRUE)))
}

## End(Not run)
```

---

readDWD.meta	<i>read dwd metadata (Beschreibung*.txt files)</i>
--------------	--

---

## Description

read dwd metadata (Beschreibung\*.txt files). Intended to be called via `readDWD()`. Column widths for `read.fwf()` are computed internally. `if(any(meta))`, `readDWD()` tries to set the locale to German (to handle Umlaute correctly). It is hence not recommended to call `rdwd::readDWD.meta` directly on a file! Names can later be changed to ascii with `berryFunctions::convertUmlaut()`.

## Usage

```
readDWD.meta(file, quiet = rdwdquiet(), ...)
```

## Arguments

file	Name of file on harddrive, like e.g. DWDdata/daily_kl_recent_KL_Tageswerte_Beschreibung_Stationen.
quiet	Ignored. DEFAULT: FALSE through <code>rdwdquiet()</code>
...	Further arguments passed to <code>read.fwf()</code>

## Value

data.frame

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>

**See Also**

[readDWD\(\)](#)

**Examples**

```
## Not run: # Excluded from CRAN checks, but run in localtests

link <- selectDWD(res="daily", var="kl", per="r", meta=TRUE)
link <- link[!grepl("mn4", link)] # for mn4 file May 2022
link <- grep(".txt$", link, value=TRUE)
if(length(link)!=1) stop("length of link should be 1, but is ", length(link),
                        ":\n", berryFunctions::truncMessage(link,prefix="",sep="\n"))

file <- dataDWD(link, dir=locdir(), read=FALSE)
meta <- readDWD(file)
head(meta)

cnm <- colnames(meta)
if(length(cnm)!=8) stop("number of columns should be 8, but is ", length(cnm),
                       ":\n", toString(cnm))

## End(Not run)
```

---

readDWD.multia	<i>read multi_annual dwd data</i>
----------------	-----------------------------------

---

**Description**

read multi\_annual dwd data. Intended to be called via [readDWD\(\)](#).  
 All other observational data at [dwdbase](#) can be read with [readDWD.data\(\)](#), except for the multi\_annual and subdaily/standard\_format data.

**Usage**

```
readDWD.multia(
  file,
  fileEncoding = "latin1",
  comment.char = "\032",
  quiet = rdwdquiet(),
  ...
)
```

**Arguments**

file	Name of file on harddrive, like e.g. DWDdata/multi_annual_mean_81-10_Temperatur_1981-2010_aktStandort.txt or DWDdata/multi_annual_mean_81-10_Temperatur_1981-2010_Stationsliste_aktStandort.txt
fileEncoding	<code>read.table()</code> file encoding. DEFAULT: "latin1" (needed on Linux, optional but not hurting on windows)
comment.char	<code>read.table()</code> comment character. DEFAULT: "\032" (needed 2019-04 to ignore the binary control character at the end of multi_annual files)
quiet	Ignored. DEFAULT: FALSE through <code>rdwdquiet()</code>
...	Further arguments passed to <code>read.table()</code>

**Value**

data.frame

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Feb 2019

**See Also**

[readDWD\(\)](#)

**Examples**

```
## Not run: # Excluded from CRAN checks, but run in localtests

# Temperature aggregates (2019-04 the 9th file, 2022-05 the 8th):
durl <- selectDWD(res="multi_annual", var="mean_81-10", per="")[8]
murl <- selectDWD(res="multi_annual", var="mean_81-10", per="", meta=TRUE)[8]

ma_temp <- dataDWD(durl, dir=locdir())
ma_meta <- dataDWD(murl, dir=locdir())

head(ma_temp)
head(ma_meta)

ma <- merge(ma_meta, ma_temp, all=TRUE)
berryFunctions::linReg(ma$Stationshoehe, ma$Jahr, main="annual average ~ elevation")
op <- par(mfrow=c(3,4), mar=c(0.1,2,2,0), mgp=c(3,0.6,0))
for(m in colnames(ma)[8:19])
{
  berryFunctions::linReg(ma$Stationshoehe, ma[,m], xaxt="n", xlab="", ylab="", main=m)
  abline(h=0)
}
par(op)

par(bg=8)
berryFunctions::colPoints(ma$geogr..Laenge, ma$geogr..Breite, ma$Jahr, add=F, asp=1.4)
```

```

load(system.file("extdata/DEU.rda", package="rdwd"))
pdf("MultiAnn.pdf", width=8, height=10)
par(bg="grey90")
for(m in colnames(ma)[8:19])
{
  raster::plot(DEU, border="grey40")
  berryFunctions::colPoints(ma[-262,]$geogr..Laenge, ma[-262,]$geogr..Breite, ma[-262,m],
                           asp=1.4, # Range=range(ma[-262,8:19]),
                           col=berryFunctions::divPal(200, rev=TRUE), zlab=m, add=T)
}
dev.off()
berryFunctions::openFile("MultiAnn.pdf")

## End(Not run)

```

---

readDWD.nc

*read dwd netcdf data*


---

## Description

Read netcdf data. Intended to be called via `readDWD()`.

Note that `R.utils` and `ncdf4` must be installed to unzip and read the `.nc.gz` files.

## Usage

```

readDWD.nc(
  file,
  gargs = NULL,
  var = "",
  toraster = TRUE,
  quiet = rdwdquiet(),
  ...
)

```

## Arguments

<code>file</code>	Name of file on harddrive, like e.g. <code>DWDdata/grids_germany/daily/Project_TRY/humidity/RH_199509_c</code>
<code>gargs</code>	Named list of arguments passed to <code>R.utils::gunzip()</code> , see <code>readDWD.raster()</code> . DEFAULT: <code>NULL</code>
<code>var</code>	if <code>toraster=FALSE</code> : Charstring with name of variable to be read with <code>ncdf4::ncvar_get()</code> . If not available, an interactive selection is presented. DEFAULT: <code>""</code> (last variable)
<code>toraster</code>	Read file with <code>raster::brick()</code> ? All further arguments will be ignored. Specify e.g. <code>var</code> through ... as <code>varname</code> . DEFAULT: <code>TRUE</code>
<code>quiet</code>	Logical: Suppress time conversion failure warning? DEFAULT: <code>FALSE</code> through <code>rdwdquiet()</code>
...	Further arguments passed to <code>raster::brick()</code> or <code>ncdf4::nc_open()</code>

**Value**

`raster::brick()` object. Alternatively, if `toraster=FALSE`, a list with `time`, `lat`, `lon`, `var`, `varname`, `file` and `cdf`. `cdf` is the output of `ncdf4::nc_open()`.

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Aug 2019

**See Also**

[readDWD\(\)](#)

**Examples**

```
## Not run: # Excluded from CRAN checks, but run in localtests

library(berryFunctions) # for seqPal and colPointsLegend

url <- "daily/Project_TRY/pressure/PRED_199606_daymean.nc.gz" # 5 MB
url <- "daily/Project_TRY/humidity/RH_199509_daymean.nc.gz" # 25 MB
file <- dataDWD(url, base=gridbase, joinbf=TRUE, dir=locdir(), read=FALSE)
nc <- readDWD(file)
ncp <- plotRadar(nc, main=paste(nc@title, nc@z[[1]]), layer=1:3,
                 col=seqPal(), proj="nc", extent="nc")
str(nc, max.level=2)

raster::values(nc[[1]]) # obtain actual values into memory

raster::plot(nc[[1]]) # axes 0:938 / 0:720, the number of grid cells
raster::plot(ncp[[1]]) # properly projected, per default onto latlon

rng <- range(raster::cellStats(nc[[1:6]], "range"))
raster::plot(nc, col=seqPal(), zlim=rng, maxnl=6)

# Array instead of raster brick:
nc <- readDWD(file, toraster=FALSE)
image(nc$var[,1], col=seqPal(), asp=1.1)
colPointsLegend(nc$var[,1], title=paste(nc$varname, nc$time[1]))

# interactive selection of variable:
# nc <- readDWD(file, var="-") # uncommented to not block automated tests
str(nc$var)

## End(Not run)
```

**Description**

open pdf file. This leads to less failures in the new meta=TRUE

**Usage**

```
readDWD.pdf(file, quiet = rdwdquiet(), ...)
```

**Arguments**

file	Name of file on harddrive, like e.g. monthly_kl_historical_DESCRIPTION_obsgermany_climate_monthl
quiet	Ignored. DEFAULT: FALSE through <a href="#">rdwdquiet()</a>
...	Further arguments passed to <a href="#">berryFunctions::openFile()</a> and from there to <a href="#">system2()</a>

**Value**

[berryFunctions::openFile\(\)](#) output

system in [selectDWD\(\)](#).

Intended to be called via [readDWD\(\)](#).

**Author(s)**

Berry Boessenkool, <[berry-b@gmx.de](mailto:berry-b@gmx.de)>, May 2022.

**See Also**

[readDWD\(\)](#)

**Examples**

```
## Not run: # Excluded from CRAN checks, but run in localtests
link <- selectDWD(res="hourly", var="sun", per="r", meta=TRUE)[2]
file <- dataDWD(link, dir=locdir(), read=FALSE)
readDWD(file)

## End(Not run)
```

---

readDWD.radar	<i>read dwd gridded radolan radar data</i>
---------------	--

---

## Description

read gridded radolan radar data. Intended to be called via [readDWD\(\)](#).

## Usage

```
readDWD.radar(
  file,
  gargs = NULL,
  toraster = TRUE,
  dividebyten = TRUE,
  quiet = rdwquiet(),
  ...
)
```

## Arguments

file	Name of file on harddrive, like e.g. DWDdata/hourly/radolan/recent/bin/ raa01-rw_10000-1802020250-dwd—bin.gz
gargs	Named list of arguments passed to <a href="#">R.utils::gunzip()</a> , see <a href="#">readDWD.raster()</a> . DEFAULT: NULL
toraster	Logical: convert output (list of matrixes + meta informations) to a list with data ( <a href="#">raster::stack</a> ) + meta (list from the first subfile, but with vector of dates)? DEFAULT: TRUE
dividebyten	Logical: Divide the numerical values by 10? See <a href="#">readDWD.toraster???</a> DEFAULT: TRUE
quiet	Ignored. DEFAULT: FALSE through <a href="#">rdwquiet()</a>
...	Further arguments passed to <a href="#">dwdradar::readRadarFile()</a> , i.e. na and clutter

## Value

Invisible list with dat (matrix or raster, depending on toraster) and meta (list with elements from header)

## Author(s)

Berry Boessenkool, <berry-b@gmx.de>, Aug 2019. Significant input for the underlying [dwdradar::readRadarFile\(\)](#) came from Henning Rust & Christoph Ritschel at FU Berlin.

**See Also**

`readDWD()`, especially `readDWD.binary()`  
<https://wradlib.org> for much more extensive radar analysis in Python  
 Kompositformatbeschreibung at <https://www.dwd.de/DE/leistungen/radolan/radolan.html>  
 for format description

**Examples**

```
## Not run: # Excluded from CRAN checks, but run in localtests
# recent radar files
rrf <- indexFTP("hourly/radolan/recent/bin", base=gridbase, dir=tempdir())
lrf <- dataDWD(rrf[773], base=gridbase, joinbf=TRUE, dir=tempdir(), read=FALSE)
r <- readDWD(lrf)
plotRadar(r$dat, main=paste("mm in 24 hours preceding", r$meta$date))

## End(Not run)
```

---

readDWD.raster	<i>read dwd gridded raster data</i>
----------------	-------------------------------------

---

**Description**

Read gridded raster data. Intended to be called via `readDWD()`.  
 Note that R.utils must be installed to unzip the .asc.gz files.

**Usage**

```
readDWD.raster(file, gargs = NULL, dividebyten, quiet = rdwdquiet(), ...)
```

**Arguments**

file	Name of file on harddrive, like e.g. DWDdata/grids_germany/seasonal/air_temperature_mean/16_DJF_grids_germany_seasonal_air_temp_mean_188216.asc.gz
gargs	Named list of arguments passed to <code>R.utils::gunzip()</code> . The internal defaults are: <code>remove=FALSE</code> (recommended to keep this so file does not get deleted) and <code>skip=TRUE</code> (which reads previously unzipped files as is). If file has changed, use <code>gargs=list(temporary=TRUE)</code> . The <code>gunzip</code> default <code>destname</code> means that the unzipped file is stored at the same path as file. DEFAULT: <code>gargs: NULL</code>
dividebyten	Logical: Divide the numerical values by 10? See <code>readDWD</code> . DEFAULT: <code>TRUE</code>
quiet	Ignored. DEFAULT: <code>FALSE</code> through <code>rdwdquiet()</code>
...	Further arguments passed to <code>raster::raster()</code>

**Value**

`raster::raster` object



**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Dec 2018

**See Also**

[readDWD\(\)](#)

**Examples**

```
## Not run: # Excluded from CRAN checks, but run in localtests

rasterbase <- paste0(gridbase, "/seasonal/air_temperature_mean")
ftp.files <- indexFTP("/16_DJF", base=rasterbase, dir=tempdir())
localfiles <- dataDWD(ftp.files[1:2], base=rasterbase, joinbf=TRUE,
                     dir=locdir(), read=FALSE)
rf <- readDWD(localfiles[1])
rf <- readDWD(localfiles[1]) # runs faster at second time due to skip=TRUE
raster::plot(rf)

plotRadar(rf, proj="seasonal", extent=rf@extent)

testthat::expect_equal(raster::cellStats(rf, range), c(-8.2, 4.4))
rf10 <- readDWD(localfiles[1], dividebyten=FALSE)
raster::plot(rf10)
testthat::expect_equal(raster::cellStats(rf10, range), c(-82, 44))

## End(Not run)
```

---

readDWD.rklim

*read dwd gridded radklim binary data*

---

**Description**

read gridded radklim binary data. Intended to be called via [readDWD\(\)](#).  
Note: needs `dwdradar >= 0.2.6` (2021-08-08)

**Usage**

```
readDWD.rklim(  
  file,  
  exdir = NULL,  
  unpacked = NULL,  
  selection = NULL,  
  toraster = TRUE,  
  quiet = rdwdquiet(),  
  progbar = !quiet,  
  ...  
)
```

**Arguments**

file	Name of file on harddrive, like e.g. DWDdata/5_minutes_radolan_reproc_2017_002_bin_2020_YW2017
exdir	Directory to unzip into. If existing, only the needed files will be unpacked with <code>untar()</code> . Note that exdir size will be around 17 GB for 5-minute files. If <code>unpacked=FALSE</code> , exdir can contain other files that will be ignored for the actual reading. DEFAULT: <code>basename(file)</code> at <code>tempdir</code>
unpacked	Manually indicate whether .tar.gz files within .tar file have already been unpacked before. DEFAULT: NULL: checks if 'yw.*-bin' file(s) are present
selection	Optionally read only a subset of the $\sim 12 \times 24 \times 30/31 = 8640$ files. Called as <code>f[selection]</code> . DEFAULT: NULL (ignored)
toraster	Logical: convert to raster stack? see <code>readDWD.binary</code> DEFAULT: TRUE
quiet	Suppress progress messages? DEFAULT: FALSE through <code>rdwdquiet()</code>
progbar	Show progress bars? DEFAULT: !quiet, i.e. TRUE
...	Further arguments passed to <code>dwdradar::readRadarFile()</code> , i.e. <code>na</code> and <code>clutter</code>

**Value**

list depending on argument `toraster`, see there for details

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Aug 2021.

**See Also**

`readDWD.binary()`, radar locations from [https://www.dwd.de/DE/leistungen/radarklimatologie/radklim\\_kompositformat\\_1\\_0.pdf?\\_\\_blob=publicationFile&v=1](https://www.dwd.de/DE/leistungen/radarklimatologie/radklim_kompositformat_1_0.pdf?__blob=publicationFile&v=1)

**Examples**

```
## Not run: # Excluded from CRAN checks, but run in localtests
yw_link <- "/5_minutes/radolan/reproc/2017_002/bin/2022/YW2017.002_202203.tar"
# 202006 has untar error on Mac, 2023-04, maybe due to incomplete download
yw_file <- dataDWD(url=yw_link, base=gridbase, joinbf=TRUE, dir=locdir(), read=FALSE)
# 207 MB
x <- readDWD(yw_file, selection=3641:3644)
# 00:30 for tar files, 01:40 for unpacking.
# If you need a preselection argument, let me know.
raster::plot(x$dat)

f <- system.file("tests//raa01-yw2017.002_10000-2006131525-dwd---bin", package="dwdradar")
# https://stackoverflow.com/a/72207233/1587132 on how to install with tests folder
if(!file.exists(f)) f <- paste0("/Users/berry/Dropbox/Rpack/dwdradar/tests/",
                               "raa01-yw2017.002_10000-2006131525-dwd---bin")
# Clone from https://github.com/brry/dwdradar
if(!file.exists(f)) stop("dwdradar test file not found")

x <- dwdradar::readRadarFile(f)
```

```

x$dat <- raster::raster(x$dat)
raster::plot(x$dat)
plotRadar(x$dat, extent=c(-360, 380, -4730, -3690))

radloc <- read.table(header=T, sep=",", text="
ND, NM, NS , ED, EM, ES
53, 33, 50.4, 06, 44, 53.9
51, 07, 26.5, 13, 45, 48.5
51, 24, 18.5, 06, 57, 49.8
47, 52, 21.3, 08, 00, 24.6
54, 10, 23.2, 12, 06, 25.3
52, 28, 40.3, 13, 23, 13.0
54, 00, 15.8, 10, 02, 48.7
51, 07, 28.7, 13, 46, 07.1
49, 32, 26.4, 12, 24, 10.0
53, 20, 19.4, 07, 01, 25.5
51, 24, 20.2, 06, 58, 01.6
47, 52, 25.0, 08, 00, 13.0
51, 20, 06.0, 08, 51, 09.0
51, 18, 40.3, 08, 48, 07.2
50, 03, 06.0, 08, 34, 05.0
50, 01, 20.8, 08, 33, 30.7
53, 37, 16.5, 09, 59, 47.6
52, 27, 47.0, 09, 41, 53.9
52, 27, 36.2, 09, 41, 40.2
48, 10, 28.9, 12, 06, 06.3
48, 02, 31.7, 10, 13, 09.2
48, 20, 10.9, 11, 36, 42.1
50, 30, 00.4, 11, 08, 06.2
50, 06, 34.7, 06, 32, 53.9
49, 59, 05.1, 08, 42, 46.6
52, 38, 55.2, 13, 51, 29.6
54, 10, 32.4, 12, 03, 29.1
48, 35, 07.0, 09, 46, 58.0
52, 09, 36.3, 11, 10, 33.9")
radloc$x <- radloc$ED + radloc$EM/60 + radloc$ES/3600
radloc$y <- radloc$ND + radloc$NM/60 + radloc$NS/3600
for(i in 1:29) berryFunctions::circle(radloc$x[i], radloc$y[i], 0.9)

## End(Not run)

```

---

readDWD.stand

*read subdaily/standard\_format dwd data*


---

## Description

read subdaily/standard\_format dwd data. Intended to be called via `readDWD()`.

All other observational data at [dwdbase](#) can be read with `readDWD.data()`, except for the multi\_annual and subdaily/standard\_format data.

**Usage**

```
readDWD.stand(
  file,
  fast = TRUE,
  fileEncoding = "latin1",
  formIndex = formatIndex,
  quiet = rdwdquiet(),
  ...
)
```

**Arguments**

file	Name of file on harddrive, like e.g. DWDdata/subdaily_standard_format_kl_10381_00_akt.txt or DWDdata/subdaily_standard_format_kl_10381_bis_1999.txt.gz
fast	Logical: use <code>readr::read_fwf()</code> instead of <code>read.fwf()</code> ? Takes 0.1 instead of 20 seconds but requires package to be installed. if fast=TRUE, fileEncoding is ignored. DEFAULT: TRUE
fileEncoding	<code>read.table()</code> file encoding. DEFAULT: "latin1" (potentially needed on Linux, optional but not hurting on windows)
formIndex	Single object: Index used to select column widths and NA values. To use a current / custom index, see the source code of <code>updateIndexes()</code> at <a href="https://github.com/brry/rwd/blob/master/R/updateIndexes.R">https://github.com/brry/rwd/blob/master/R/updateIndexes.R</a> . DEFAULT: <code>formatIndex</code>
quiet	Ignored. DEFAULT: FALSE through <code>rdwdquiet()</code>
...	Further arguments passed to <code>read.fwf()</code> or <code>readr::read_fwf()</code>

**Value**

data.frame with column names as per `formatIndex`. "Q"-columns have "\_parameter" appended to their name. A "Date" column has been added. NA-indicators have been processed into NAs.

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Oct 2019

**See Also**

[readDWD\(\)](#)

**Examples**

```
## Not run: # Excluded from CRAN checks, but run in localtests

link <- selectDWD(res="subdaily", var="standard_format", per="r")
link <- link[grep1("10381", link, fixed=TRUE)]
# Not ID, according to meta data, hence no longer in column id (2023-04).
file <- dataDWD(link, dir=locdir(), read=FALSE)
sf <- readDWD(file)
```

```

sf2 <- readDWD(file, fast=FALSE) # 20 secs!
stopifnot(all.equal(sf, sf2))

plot(sf$Date, sf$SHK, type="l")

# Plot all columns:
if(FALSE){ # not run in any automated testing
tmp <- tempfile(fileext=".pdf")
char2fact <- function(x)
{
  if(all(is.na(x))) return(rep(-9, len=length(x)))
  if(!is.numeric(x)) as.factor(x) else x
}
pdf(tmp, width=9)
par(mfrow=c(2,1),mar=c(2,3,2,0.1), mgp=c(3,0.7,0), las=1)
for(i in 3:ncol(sf)-1) plot(sf$Date, char2fact(sf[,i]), type="l", main=colnames(sf)[i], ylab="")
dev.off()
berryFunctions::openFile(tmp)
}

## End(Not run)

```

---

readMeta

*Process data from the DWD CDC FTP Server*


---

## Description

Read climate meta info textfiles in zip folders downloaded with [dataDWD\(\)](#).

## Usage

```
readMeta(file, progbar = TRUE, ...)
```

## Arguments

file	Char (vector): name(s) of the zip file(s) downloaded with <a href="#">dataDWD()</a> , e.g. "~/DWD-data/tageswerte_KL_02575_akt.zip"
progbar	Logical: present a progress bar with estimated remaining time? If missing and <code>length(file)==1</code> , progbar is internally set to FALSE. DEFAULT: TRUE
...	Further arguments passed to <a href="#">read.table()</a>

## Value

Invisible named list of data.frames; or a list of lists, if `length(file)>1`.

## Author(s)

Berry Boessenkool, <berry-b@gmx.de>, 2016 + March 2019

**See Also**

[dataDWD\(\)](#), [readVars\(\)](#), [readDWD\(\)](#)

**Examples**

```
# see dataDWD
```

---

readVars

*Process data from the DWD CDC FTP Server*

---

**Description**

Read climate variables (column meta data) from zip folders downloaded with [dataDWD\(\)](#). The metadata file "Metadaten\_Parameter.\*txt" in the zip folder file is read, processed and returned as a data.frame.

file can be a vector with several filenames.

**Usage**

```
readVars(file, params = dwdparams, quiet = rdwdquiet(), progbar = TRUE)
```

**Arguments**

file	Char (vector): name(s) of the file(s) downloaded with <a href="#">dataDWD()</a> , e.g. "~/DWD-data/tageswerte_KL_02575_akt.zip"
params	data.frame: Parameter explanations. DEFAULT: <a href="#">dwdparams</a>
quiet	Suppress message about non-abbreviated parameters? DEFAULT: FALSE through <a href="#">rdwdquiet()</a>
progbar	Logical: present a progress bar with estimated remaining time? If missing and length(file)==1, progbar is internally set to FALSE. DEFAULT: TRUE

**Value**

data.frame of the desired dataset, or a named list of data.frames if length(file) > 1.

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Jun 2018

**See Also**

[dataDWD\(\)](#), [readDWD\(\)](#), [dwdparams](#), [newColumnNames\(\)](#)  
[readMeta\(\)](#) for complete Metadaten\_Parameter file.  
[website use case](#)

**Examples**

```
# see dataDWD
```

---

rowDisplay	<i>Create leaflet map popup from data.frame rows</i>
------------	--

---

**Description**

Create display character string for leaflet map popup from data.frame rows. This function is not exported, as it is only internally useful. A generic version is available in [berryFunctions::popleaf\(\)](#).

**Usage**

```
rowDisplay(x)
```

**Arguments**

x                    data.frame with colnames

**Value**

Vector of character strings, one for each row in x.

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Feb 2017

**See Also**

[geoIndex](#)

---

runLocalTests	<i>run local tests of rdwd</i>
---------------	--------------------------------

---

**Description**

Run rdwd tests on local machine. Due to time-intensive data downloads, these tests are not run automatically on CRAN.

**Usage**

```
runLocalTests(  
  dir_data = locdir(),  
  dir_exmpl = berryFunctions::packagePath(file = "misc/ExampleTests"),  
  start = 1,  
  quiet = rdwdquiet()  
)
```

**Arguments**

dir_data	Reusable data location. Preferably not under version control. DEFAULT: <code>locdir()</code>
dir_exmpl	Reusable example location. DEFAULT: local directory
start	Number to start tests at, helpful for partially successful runs. DEFAULT: 1
quiet	Suppress progress messages? DEFAULT: FALSE through <code>rdwdquiet()</code>

**Value**

Time taken to run tests in minutes

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Apr-Oct 2019

**See Also**

`locdir()`

---

selectDWD	<i>Select data from the DWD CDC FTP Server</i>
-----------	--

---

**Description**

Select data files for downloading with `dataDWD()`.

The available res/var/per folders with datasets are listed [online](#).

Set res="", var="", per="" to avoid the default interactive selection.

The arguments name/id and res/var/per can be vectors.

**Usage**

```
selectDWD(
  name = "",
  res = NA,
  var = NA,
  per = NA,
  expand = TRUE,
  id = findID(name, exactmatch = exactmatch, mindex = mindex, quiet = quiet, failempty =
    failempty),
  exactmatch = TRUE,
  mindex = metaIndex,
  failempty = TRUE,
  findex = fileIndex,
  current = FALSE,
  base = dwdbase,
  meta = FALSE,
  quiet = rdwdquiet(),
  ...
)
```



**Arguments**

name	Char: station name(s) passed to <code>findID()</code> , along with <code>exactmatch</code> , <code>mindex</code> and <code>failempty</code> . All 3 arguments are ignored if <code>id</code> is given. DEFAULT: "" (all stations at <code>res/var/per</code> )
res	Char: temporal <b>resolution</b> at base, e.g. "hourly", "daily", "monthly". See section 'Description' above and <code>fileIndex</code> . Use <code>res=""</code> for matching options from all resolutions. DEFAULT: NA for interactive selection
var	Char: weather <b>variable</b> of interest, e.g. "air_temperature", "cloudiness", "precipitation", "soil_moisture". See section 'Description' above and <code>fileIndex</code> . DEFAULT: NA for interactive selection
per	Char: desired time <b>period</b> , e.g. "recent" (up to date records from the last 1.5 years) or "historical" (long time series). Can be abbreviated. To get both datasets, use <code>per="hr"</code> . DEFAULT: NA for interactive selection
expand	Logical: get all possible <code>res/var/per</code> combinations? Set to FALSE if you want only the given combinations. If FALSE, they cannot be NA or "". DEFAULT: TRUE
id	Char/Number: station ID with or without leading zeros, e.g. "00614" or 614. Is internally converted to an integer. Use NA (the default from <code>findID</code> ) to get all data at <code>res/var/per</code> . DEFAULT: <code>findID(name, exactmatch, mindex, failempty)</code>
exactmatch	Logical passed to <code>findID()</code> : match name with <code>==</code> ? Else with <code>grepl()</code> . DEFAULT: TRUE
mindex	Single object: Index with metadata passed to <code>findID()</code> . DEFAULT: <code>metaIndex</code>
failempty	Fail if no matching station is found in <code>findID()</code> ? Avoid downloading all files. DEFAULT: TRUE
findex	Single object: Index used to select filename, as returned by <code>createIndex()</code> . To use a current / custom index, see <code>current</code> and <a href="https://bookdown.org/brry/rdwd/fileindex.html">https://bookdown.org/brry/rdwd/fileindex.html</a> . DEFAULT: <code>fileIndex</code>
current	Single logical when <code>res/var/per</code> is given: instead of <code>findex</code> , use a list of the currently available files at <code>base/res/var/per</code> ? This will call <code>indexFTP()</code> , thus requires availability of the RCur1 package. See <a href="https://bookdown.org/brry/rdwd/fileindex.html">https://bookdown.org/brry/rdwd/fileindex.html</a> . DEFAULT: FALSE
base	Single char: main directory of DWD ftp server. Must be the same base used to create <code>findex</code> . DEFAULT: <code>dwdbase</code>
meta	Logical: select Beschreibung file from <code>ismeta</code> entries in <code>findex</code> ? See <code>metaIndex</code> for a compilation of all Beschreibung files. See the 'Examples' section for handling pdf and txt files. DEFAULT: FALSE
quiet	Suppress id length warnings? DEFAULT: FALSE through <code>rdwdquiet()</code>
...	Further arguments passed to <code>indexFTP()</code> if <code>current=TRUE</code> , except folder and base.

**Value**

Character string with file path and name(s) in the format "base/res/var/per/filename.zip"

**Author(s)**

Berry Boessenkool, <berry-b@gmx.de>, Oct 2016, rewritten May 2022

**See Also**

[dataDWD\(\)](#), [metaIndex](#), [website station selection chapter](#)

**Examples**

```
# Give weather station name (must exist in metaIndex):
selectDWD("Potsdam", res="daily", var="kl", per="historical")

# all files for all stations matching "Koeln":
tail(selectDWD("Koeln", res="", var="", per="", exactmatch=FALSE)) # 686 files
findID("Koeln", FALSE)

## Not run: # Excluded from CRAN checks to save time

# selectDWD("Potsdam") # interactive selection of res/var/per

# directly give station ID:
selectDWD(id="00386", res="daily", var="kl", per="historical")
selectDWD(id=537, "", "", "", "") # 8 files

# period can be abbreviated:
selectDWD(id="5419", res="daily", var="kl", per="h")

# selectDWD is vectorizable!
# since version 1.5.28 (2022-05-12) outer product, not elementwise comparison:
selectDWD("Freiburg", res="daily", var="kl", per="rh")
selectDWD("Freiburg", res=c("daily","monthly"), var="kl", per="r")
selectDWD("Freiburg", res=c("daily","monthly"), var="kl", per="hr")
# get old behaviour (needed e.g. in nearbyStations):
ids <- c(3761,3761, 3603)
# all combinations:
selectDWD(id=ids, res="daily", var="kl", per=c("h","r","r")) # 4
# only given combinations:
selectDWD(id=ids, res="daily", var="kl", per=c("h","r","r"), expand=FALSE) # 3

# all files in all paths matching id:
head( selectDWD(id=c(1050, 386), res="",var="",per="") ) # 277 files
# all files in a given path (if ID is empty):
head( selectDWD(id="", res="daily", var="kl", per="recent") ) # 585 files

selectDWD(id=386, res="monthly", var="kl", per="h")

# Meta data - Description and Beschreibung txt/pdf files.:
# manually select .txt (not pdf) files for automated opening with readDWD.
link <- selectDWD(res="monthly", var="kl", per="h", meta=TRUE) # omit ID/Name!
link
link2 <- grep("\\.txt$", link, value=TRUE) ; link2
m <- dataDWD(link2, dir=locdir())
```

```

head(m)
#
# Open PDF files with your system's default Viewer:
dataDWD(link[1], dir=locdir())

## End(Not run)

```

---

updateRdwd

*Update rdwd development version*


---

### Description

Update rdwd to the latest development version on github, if necessary. If the version number or date is larger on github, `remotes::install_github()` will be called.

### Usage

```

updateRdwd(
  pack = "rdwd",
  user = "brry",
  vignette = NA,
  quiet = rdwdquiet(),
  ...
)

```

### Arguments

pack	Name of (already installed) package. DEFAULT: "rdwd"
user	Github username. repo will then be user/pack. DEFAULT: "brry"
vignette	build_vignettes in <code>remotes::install_github()</code> ? DEFAULT: NA (changed to TRUE if rmarkdown and knitr are available)
quiet	Suppress version messages and <code>remotes::install</code> output? DEFAULT: FALSE through <code>rdwdquiet()</code>
...	Further arguments passed to <code>remotes::install_github()</code>

### Value

data.frame with version information

### Author(s)

Berry Boessenkool, <brry-b@gmx.de>, Nov 2019

### See Also

`remotes::install_github()`

**Examples**

```
# updateRdwd()
```

---

validFileTypes

*valid fileType values*

---

**Description**

fileType values that have a reading subfunction readDWD.ftype().

**Usage**

```
validFileTypes
```

**Format**

An object of class character of length 13.

# Index

- \* **aplot**
  - addBorders, 3
  - plotRadar, 27
  - projectRasterDWD, 29
- \* **character**
  - findID, 16
  - rowDisplay, 55
- \* **chron**
  - readDWD, 32
- \* **datasets**
  - DEU, 10
  - dwdbase, 12
  - dwdparams, 13
  - EUR, 13
  - index, 17
  - metaInfo, 23
  - validFileTypes, 60
- \* **data**
  - dataDWD, 8
- \* **debugging**
  - runLocalTests, 55
- \* **documentation**
  - rdwd, 31
- \* **file**
  - dataDWD, 8
  - dirDWD, 11
  - fileType, 14
  - indexFTP, 18
  - locdir, 22
  - readDWD, 32
  - readMeta, 53
  - readVars, 54
  - selectDWD, 56
  - updateRdwd, 59
- \* **hplot**
  - plotDWD, 26
- \* **iplot**
  - app, 4
- \* **manip**
  - createIndex, 6
- \* **package**
  - checkSuggestedPackage, 5
  - rdwd, 31
- \* **spatial**
  - lldist, 21
  - plotRadar, 27
- ==, 16, 57
- addBorders, 3, 11, 14
- addBorders(), 29
- app, 4
- as.Date(), 39
- as.POSIXct(), 38
- asc, 15, 31
- berryFunctions::climateGraph(), 10
- berryFunctions::convertUmlaut(), 41
- berryFunctions::monthAxis(), 10
- berryFunctions::newFilename(), 7, 20
- berryFunctions::openFile(), 46
- berryFunctions::popleaf(), 55
- berryFunctions::seqPal(), 28
- binary, 15, 31
- browseURL(), 9
- cat(), 5
- checkIndex, 4
- checkIndex(), 7
- checkSuggestedPackage, 5
- createIndex, 5, 6
- createIndex(), 4, 17, 18, 20, 57
- crs, 31
- data, 14
- data.table::fread, 38
- data.table::fread(), 20, 38, 39
- dataDWD, 8
- dataDWD(), 7, 12, 22, 32–34, 39, 53, 54, 56, 58
- DEU, 3, 10, 14, 28

- dirDWD, 11
- download.file, 9
- download.file(), 9, 10
- dwdbase, 6, 8, 12, 14, 17, 19, 42, 51, 57
- dwdparams, 13, 25, 54
- dwdparams(), 25
- dwdradar::readRadarFile(), 36, 47, 50
  
- EUR, 3, 11, 13, 28
- extent, 31
  
- fileIndex, 5–7, 18, 57
- fileIndex (index), 17
- fileType, 14, 33
- fileType(), 32, 34
- findID, 16, 57
- findID(), 18, 57
- formatIndex, 52
- formatIndex (index), 17
  
- geoIndex, 5–7, 55
- geoIndex (index), 17
- getOption, 22
- getwd, 22
- getwd(), 7, 12, 20
- graphics::plot, 26
- grepl(), 16, 57
- grib2, 15
- gridbase, 9, 15, 17, 18
- gridbase (dwdbase), 12
- gridIndex, 18
- gridIndex (index), 17
  
- index, 7, 17
- indexFTP, 18
- indexFTP(), 6, 7, 9, 17, 18, 57
  
- lldist, 21
- locdir, 22
- locdir(), 9, 56
  
- max(), 21
- maxlldist (lldist), 21
- meta, 14
- metaIndex, 5–7, 16, 23, 24, 57, 58
- metaIndex (index), 17
- metaInfo, 23
- metaInfo(), 17, 18
- multia, 14
  
- nc, 15, 31
- ncdf4::nc\_open(), 44, 45
- ncdf4::ncvar\_get(), 44
- nearbyStations, 23
- newColumnNames, 25
- newColumnNames(), 25, 38, 54
- newFilename(), 9
  
- par, 26
- pdf, 14
- plotDWD, 26
- plotRadar, 3, 27
- plotRadar(), 31
- print, 23
- projectRaster, 31
- projectRasterDWD, 29
- projectRasterDWD(), 28, 29, 34
  
- R.utils::bunzip2(), 40
- R.utils::gunzip(), 39, 44, 47, 48
- radar, 15, 31
- raster, 15, 31
- raster::brick(), 44, 45
- raster::crs(), 30
- raster::extent(), 30
- raster::plot(), 3, 28
- raster::raster, 48
- raster::raster(), 35, 40, 48
- raster::stack, 36, 47
- raster::stack(), 34
- raster::writeRaster(), 34
- RCurl::getURL(), 19, 20
- rdwd, 4, 31
- rdwd-package (rdwd), 31
- rdwdquiet, 32
- rdwdquiet(), 5, 7, 9, 12, 16, 20, 22, 24, 28, 30, 33, 35, 36, 38–41, 43, 44, 46–48, 50, 52, 54, 56, 57, 59
- read.fwf(), 41, 52
- read.table(), 38, 39, 43, 52, 53
- readDWD, 32, 34, 47, 48
- readDWD(), 9, 10, 13–15, 25, 27–29, 34–49, 51, 52, 54
- readDWD.asc, 32, 34
- readDWD.asc(), 33
- readDWD.binary, 36, 50
- readDWD.binary(), 48, 50
- readDWD.data, 26, 32, 37
- readDWD.data(), 14, 25, 33, 42, 51

readDWD.deriv, 39  
readDWD.grib2, 40  
readDWD.meta, 41  
readDWD.multia, 42  
readDWD.nc, 44  
readDWD.nc(), 33  
readDWD.pdf, 45  
readDWD.radar, 47  
readDWD.radar(), 33, 37  
readDWD.raster, 32, 48  
readDWD.raster(), 33, 39, 40, 44, 47  
readDWD.rklim, 49  
readDWD.stand, 51  
readLines(), 20  
readMeta, 53  
readMeta(), 14, 34, 54  
readr::read\_fwf(), 52  
readVars, 54  
readVars(), 13, 25, 34, 54  
remotes::install\_github(), 59  
requireNamespace(), 6  
rgdal::readGDAL, 40  
rklim, 15  
rowDisplay, 55  
runLocalTests, 55  
runLocalTests(), 22  
  
selectDWD, 56  
selectDWD(), 7, 8, 10, 16–18, 24, 34, 46  
setwd(), 12  
shiny::runApp(), 4  
stand, 14  
stars::read\_stars(), 40  
strptime(), 38  
Sys.sleep(), 9, 20  
system2(), 46  
  
tempdir(), 22, 34  
tempfile(), 7  
terra::rast(), 40  
  
untar(), 36, 50  
updateIndexes(), 7, 17, 20, 52  
updateRdwd, 59  
  
validFileTypes, 60